D2.2 System Architecture, MIMs and Sensor Guidelines

ExPEDite

Horizon Europe

101139527

Deliverable information

Deliverable Number	**D2.2**
Date of Issue	31/4/2025
Nature of Deliverable	Report (R)
Dissemination Level	Public
Main Editor(s)	Nikolaos Bakalos (NTUA), Stavros Sykiotis (NTUA), Sotiris Athanasoulias (NTUA)

Document History

Date	Version	Remarks
01/02/2025	0.1	Initial Table of Contents
15/3/2025	0.2	Initial Section completed
31/3/2025	0.3	Final Sensors Guidelines Section updated
10/4/2025	0.4	Final MIMs and Architecture Sections
14/4/2025	0.5	1st integrated Version ready for internal Review
20/4/2025	0.6	Version with comments from internal quality review
29/4/2025	0.7	Final Version ready for submission

List of Contributors

Beneficiary	Contributor(s)
NTUA	Nikos Bakalos, Stavros Sykiotis, Sotiris Athanasoulias
OASC	Vincent Demortier
PLEGMA	Stelios Kalogridis

Document Reviewers

Beneficiary	Peer Reviewer(s)
EXUS	Aris Bonanos
TPEB	Martin Hromada

Disclaimer

Tl
Eu
10

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Climate, Infrastructure and Environment Executive Agency (CINEA). Neither the European Union nor the granting authority can be held responsible for them.

Contents

List of Acronyms....6

Executive Summary....8

1. Introduction....9

1.1. Purpose and Scope....9

1.2. Document Structure....9

1.3. Relation with other Deliverables....10

2. Minimum Interoperability Mechanisms....11

2.1. Mapping of the relevant MIMs in the ExPEDite architecture....12

2.1.1. MIM 1 - Context information....12

2.1.2. MIM 2 - Context information....13

2.1.3. MIM 3 - Contracts....14

2.2. MIMs compliance assessment methodology....16

2.2.1. MIM.meter introduction....16

2.2.2. The MIM.meter repository: specific weights of capabilities and requirements....17

2.3. Incremental MIM.meter evaluation of the ExPEDite DT components....19

3. Guidelines for Sensor Network Consolidation....21

3.1. Main Smart Cities Use Cases: Purpose and Technical Requirements....22

3.1.1. Energy Management....22

3.1.2. Mobility and Transport....24

3.1.3. Environmental Monitoring....25

3.1.4. Public Safety and Security....26

3.2. Overview of Communication Protocols for Smart City Networks....28

3.2.1. Wired Protocols....28

3.2.2. Wireless Protocols....31

3.3. Network Design for Smart City Sensor Networks....37
3.3.1. Topological Considerations....37
3.3.2. Network Redundancy and Reliability in Smart City Sensor Networks....45
3.3.3. Integration of Various Sensor Types - Interoperability....46
3.3.4. Data Acquisition Rates and Data Synchronization in Smart City Sensor Networks....48
3.3.5. Physical Infrastructure Planning Guidelines....50
3.3.6. Power Management in Smart City IoT Sensor Networks....51
3.3.7. Assessment of Deployment in Different Environments....52
3.4. Mapping Smart City Use Cases to Communication Protocols....54
3.4.1. Energy Management....55
3.4.2. Mobility and Transport....57
3.4.3. Environmental Monitoring....59
3.4.4. Public Safety....61
3.5. Sensor Network Testing and Validation Strategy....64
3.5.1. Testing Objectives and Scope....64
3.5.2. Key Testing Areas....65
3.5.3. Validation....67
3.5.4. Risk Management and Troubleshooting....69
3.6. The ExPEDite Sensors....71
3.6.1. Energy management sensors....71
3.6.2. Environmental monitoring sensors....79
3.6.3. Crowd Monitoring Sensors....81
3.6.4. Traffic Monitoring Sensors....80
4. System Architecture and Technical Specifications....83
4.1. Architecture Elicitation Procedure....83

4.2. System Overview and Purpose 84
4.2.1. Key Functionalities and Capabilities 86
4.3. Detailed Description of Components and Modules 87
4.3.1. Software Systems and Major Modules 87
4.3.2. Sensor Integration and Communication Protocols 88
4.3.3. Data Processing and Analytics Modules 90
4.4. User Roles and Interactions 93
4.5. Architecture Overview 96
4.5.1. System Context Diagram 97
4.5.2. Internal Architecture and Component Interactions 98
4.5.3. Simulation Toolset 100
4.5.4. Compliance with Requirements 102
4.5.5. Interoperability Mechanisms and Sensor Guidelines 104
4.5.6. Sensor Network Consolidation Strategy: 106
4.5.7. Security and Privacy Considerations 107
5. Conclusions 113
6. References 114
7. Annexes 127
7.1. Annex 1: Architectural Refinement Internal Questionaire 127
7.2. Annex 2: Per Tool Specific Requirements 131

List of Acronyms

Acronym	Meaning	Acronym	Meaning
5G	Fifth Generation Mobile Network	**LTE**	Long Term Evolution
6G	Sixth Generation Mobile Network	**LTE-M**	LTE for Machines
AI	Artificial Intelligence	**MAN**	Metropolitan Area Network
AMI	Advanced Metering Infrastructure	**ML**	Machine Learning
AODV	Ad hoc On-Demand Distance Vector	**MQTT**	Message Queuing Telemetry Transport
API	Application Programming Interface	**NB-IoT**	Narrowband Internet of Things
BACnet	Building Automation and Control Network	**NO_2**	Nitrogen Oxides
BLE	Bluetooth Low Energy	**OGC**	Open Geospatial Consortium
BMS	Building Management System	**P2P**	Peer-to-Peer
CCTV	Closed-Circuit Television	**PLC**	Power Line Communication
CoAP	Constrained Application Protocol	**PM**	Particulate matter
CO_2	Carbon Dioxide	**PoE**	Power over Ethernet
CSV	Comma-Separated Values	**RES**	Renewable Energy Sources
D2D	Device to Device	**REST**	Representational State Transfer
DAC	Digital-to-Analog Converter	**RFID**	Radio-Frequency Identification
DAS	Domain Awareness System	**RS-232**	Recommended Standard 232

DER	Distributed Energy Resource	**RS-485**	Recommended Standard 485
EMS	Emergency Medical Services	**SO_2**	Sulfur Dioxide
EV	Electric Vehicle	**SSL**	Secure Sockets Layer
FiWARE	Future Internet Ware	**UART**	Universal Asynchronous Receiver-Transmitter
GPS	Global Positioning System	**URLLC**	Ultra-Reliable Low-Latency Communication
GSM	Global System for Mobile Communications	**USB**	Universal Serial Bus
HIN	Hierarchical Interconnection Network	**UTC**	Coordinated Universal Time
HEVC	High Efficiency Video Coding	**V2I**	Vehicle to Infrastructure
HVAC	Heating, Ventilation and Air Conditioning	**V2V**	Vehicle to Vehicle
ICT	Information and Communication Technologies	**VOCs**	Volatile Organic Compounds
IEEE	Institute of Electrical and Electronics Engineers	**VPN**	Virtual Private Network
IP	Internet Protocol	**WAN**	Wide Area Network
ITS	Intelligent Transport Systems	**WSN**	Wireless Sensor Network
IoT	Internet of Things	**Wi-Fi**	Wireless Fidelity
JSON	JavaScript Object Notation	**XML**	Extensible Markup Language
LAN	Local Area Network	**Zigbee**	Zigbee (specification for low-power mesh networks)
LPWAN	Low Power Wide Area Network		

Executive Summary

This deliverable, D2.2 "System Architecture, MIMs and Sensor Guidelines," defines the technical architecture, interoperability mechanisms, and sensor integration approach for the ExPEDite platform—an open, modular digital ecosystem designed to enable the deployment and operation of Digital Twins (DTs) for Positive Energy Districts (PEDs).

The deliverable builds upon the functional and non-functional requirements identified in D2.1 and translates them into a layered, component-based system architecture that supports scalable, secure, and standards-compliant deployment in real urban environments. The architecture is guided by a pragmatic design philosophy, focused on modular integration, cross-domain interoperability, and real-world implementation constraints. It accommodates tools and components developed across different technical partners and work packages, while ensuring future compatibility with evolving European data governance frameworks.

A central focus of the deliverable is the alignment with the **Living-in.EU Minimum Interoperability Mechanisms (MIMs)**. Specifically, the deliverable maps:

- **MIM1** (Context Information): For managing real-time data flows using standard context brokers and interfaces.
- **MIM2** (Data Models): To ensure semantic interoperability and cross-domain data harmonization.
- **MIM3** (Contracts): In its emerging form, to support secure and controlled service and data transactions.

The architecture covers both **Design Time** and **Runtime** aspects of the Digital Twin, encompassing configuration tools, real-time engines, core backend services (e.g., context brokers, object storage, access control, messaging systems), and advanced analytics and visualization modules. Components communicate through open APIs and are integrated using standard protocols to ensure platform-agnostic deployment.

Additionally, the deliverable provides clear guidelines for **sensor and IoT integration**, detailing how data from heterogeneous sources—such as environmental sensors, mobility systems, and building infrastructure—can be ingested, harmonized, and leveraged within the broader DT framework.

Throughout the document, roles and responsibilities are explicitly assigned to technical partners, ensuring transparency, coordination, and effective development management. The system architecture is designed to be iterative and extensible, allowing it to evolve as new requirements emerge during pilot implementations and integration with broader EU ecosystems such as the Local Digital Twin (LDT) Toolbox and Data Spaces.

This document serves as a pivotal technical reference for all subsequent implementation activities within the ExPEDite project. It ensures a coherent, aligned approach to software development, system integration, and pilot deployment, laying the groundwork for delivering a robust, scalable, and future-proof digital twin platform for PEDs across Europe.

1. Introduction

This document outlines the system architecture, minimum interoperability mechanisms (MIMs), and sensor integration guidelines for the ExPEDite platform—an open, modular, and standards-compliant ecosystem designed to enable the deployment of Digital Twins (DTs) for Positive Energy Districts (PEDs). The architecture reflects a pragmatic, implementation-driven methodology and is intended to ensure that technical components developed across work packages and by different partners interoperate seamlessly within real-world urban environments.

The approach taken is based on a layered and service-oriented architecture, integrating modern interoperability standards such as the **Living-in.EU MIMs Plus Framework**, while embracing technologies from the broader **smart city and data spaces** domains. Central to the design is the alignment with EU-level initiatives in urban data governance, cross-platform integration, and open-source digital twin toolchains.

The deliverable also reflects the **evolution of the project's technical strategy** from conceptual specifications (as defined in D2.1) to a concrete architecture ready for implementation and integration. By addressing interoperability at all levels—data, platform, and service—it aims to overcome common technical fragmentation challenges faced by city ecosystems.

1.1. Purpose and Scope

The main objectives of this deliverable are:

- To define the **technical architecture** of the ExPEDite platform, including its core components, internal interactions, and interfaces with external systems.
- To map and align the ExPEDite implementation with the **Minimum Interoperability Mechanisms (MIMs)** as promoted by Living-in.EU.
- To provide guidelines for the **integration of sensors and IoT infrastructures**, including data harmonization, ingestion mechanisms, and interoperability protocols.
- To offer a **reference model** that supports deployment in heterogeneous urban environments while enabling reusability and scalability of the Digital Twin components.

The scope includes both design-time (DT-Design Time) and runtime (DT-Runtime) aspects of the system, and spans backend services, APIs, data management components, and end-user applications. Special emphasis is placed on the **foundational layer** of interoperability (MIM1, MIM2, and MIM3) and their role in enabling modular integration between components developed by different partners.

1.2. Document Structure

This document is structured as follows:

- **Chapter 2**: Describes the Minimum Interoperability Mechanisms (MIMs) and their relevance to the ExPEDite architecture, including mappings and implementation considerations.
- **Chapter 3**: It outlines the key hardware and software elements involved in sensing and actuation, describing physical devices, sensor types, installation requirements, and interfacing elements.
- **Chapter 4**: Presents the overall **system architecture**, its layered structure, and the technical roles of each component and interaction.
- **Chapter 5**: Concludes the deliverable with a summary of the architectural vision and the next steps in terms of implementation and conformance.

Additional annexes and references are included to support the formal description of the tools and alignments with external frameworks.

1.3. Relation with other Deliverables

This deliverable builds directly upon and affects the following project outputs:

- **D2.1: Report on Requirements and Functionalities**
  - Provides the functional and non-functional requirements that form the basis for the system design described here. The architecture addresses all high-level requirements specified in D2.1 and translates them into modular, actionable components.
- **D1.1: Project Management and Governance Plan**
  - Supports the coordination mechanisms and technical responsibilities reflected in the architecture, especially in terms of data ownership, component interoperability, and lifecycle management.
- **D3.x and D4.x (Data Knowledge Management and Modelling and Simulation Suites)**
  - These upcoming deliverables will make use of the system architecture and MIM guidelines defined here to implement, test, and validate the Digital Twin services across pilot sites.
- **D5.1: District Digital Twin**
  - This document interfaces with the system architecture through its use of backend analytics services, visualization tools, and data ingestion pipelines.
- **D6.1: DT Testing and integration plan**

As such, D2.2 is a central technical reference for both horizontal (cross-WP) and vertical (WP3-WP4-WP5) integration activities across the project.

2. Minimum Interoperability Mechanisms

In ExPEDite deliverable D2.1 "*Report on Requirements and functionalities",* the general concept and specifications of the Minimum Interoperability Mechanisms (MIMs) have been introduced as a *"set of principles which describe the minimal, yet sufficient capabilities needed to share, use and re-use data across systems*".

In the meantime, the significance of the adoption of the MIMs to support the pragmatic approach applied in ExPEDite project for "Enabling Positive Energy Districts through Digital Twins" has been reinforced by 3 major recent evolutions within the European initiatives:

- The new MIMs Plus framework proposed by Living-in.eu has been published to better address this generic and clear challenge: "*Many public sector organizations struggle with high costs and inefficiencies when trying to integrate different digital systems. Complex procurement rules, a lack of standardization, and resistance to change often make it difficult to connect various platforms and data sources*".
- The Interoperability Test Bed will be used by the Local Digital Twin Toolbox initiative to achieve one of its the main goals : "*to support the ecosystem with the ability to test for conformance against the interoperability framework defined by the MIMs Plus*"

In the version 7 of MIMs Plus specification, the MIM3 related to "Contracts / Ecosystem transaction management" is planned to evolve to converge with the Data Spaces architecture, in the same perspective that it has been considered for ExPEDite.



Figure 1: The new targeted MIMs Plus Framework proposed by Living-in.eu



Figure 2: Standard structure of the MIMs Plus as a reference for the LDT Toolbox conformance test

2.1. Mapping of the relevant MIMs in the ExPEDite architecture

As envisaged in the ExPEDite deliverable D2.1 "Report on Requirements and functionalities", and in alignment with the new MIMs Plus Framework (MIMs Plus V7.0), the scope of application in ExPEDite is focused on MIM1, MIM2 and MIM3:

2.1.1. MIM 1 - Context information

MIM 1 **(MIMs PLUS V7.0)**	Context Information
Objectives	To enable context information from different systems within or across organisations, such as cities or communities, originating from heterogeneous sources, to be brought together using a Web based API. To enable comprehensive and integrated use, reuse and sharing of data as well as management of context information To turn data into a strategic resource

Capabilities and requirements:

Capability 1	**Applications are able to access data from different sources (such as cities, communities and vertical solutions)**
Requirement 1	Context can be managed through the Web

Requirement 2	Information from all sources should use the same concepts, so called data information models
Capability 2	**Applications are able to use both current and historical data, use geospatial querying and be automatically updated when the source data changes**
Requirement 3	The web based API shall support retrieval of current data
Requirement 4	The web based API should support retrieval of historical data when applicable
Requirement 5	The web based API should support geospatial querying when applicable
Requirement 6	The web based API should support subscription to changes when applicable
Capability 3	**Applications can discover and retrieve data relevant to their context from a variety of sources**
Requirement 7	Relevant data sources to any required context (such as location and/or time period) should be discoverable and retrievable according to their context
Capability 4	**Applications can retrieve a subset of data from a larger data set**
Requirement 8	Specific subsets of data relevant to the context should be retrievable from within larger data sets and size limits can be set

2.1.2. MIM 2 - Context information

MIM 2 **(MIMs PLUS V7.0)**	**Data Models**
Objectives	To support cities and communities to use consistent and machine-understandable definitions of all the entities about which data is being captured in a data ecosystem, along with a consistent set of identifiers of individual instances of each entity, so that data about any entity can be combined with other data referring to that entity, and every instance of that entity, in the confidence that they refer to the same thing.

Capabilities and requirements:

Capability 1	**All entities included in data sources are described using consistent data models to enable interoperability for applications and systems.**
Requirement 1	Data models used for all entities in any data source shall be made explicit.
Requirement 2.a	Data models used shall be based (wherever possible) on commonly recognised sets of machine-understandable standardised data models as listed in the section below.
Requirement 2.b	Where it is not possible to use existing standardised data models, efforts shall be made to extend existing standardised data models that are most closely aligned or to define new ones, following best practice and conventions of the community or organisation defining the data models.
Requirement 3	Data models used shall support the exchange of data via the context management API (MIM1).
Capability 2	**All data sources in a data ecosystem use consistent identifiers for individual instances of each entity.**
Requirement 4	The type of identifiers used for entities shall be made explicit.
Requirement 5	Unique and persistent identifiers shall be used to identify particular instances of any entity used in data sets.

2.1.3. MIM 3 - Contracts

MIM3 is still in a redesign phase by the global community, especially considering the approaches inducted by the Data Spaces paradigm. Then, following the implementation driven and pragmatic principles described in the ExPEDite deliverable D2.1 "*Report on Requirements and functionalities"*, a specific and limited version of the MIM3 has been drafted and proposed for the ExPEDite architecture based on the current status of the available deliverables of the European data space for smart communities - DS4SSC project. In this perspective, the focus has been put on the concrete requirements of the various public and private stakeholders involved in ExPEDite considering 3 main aspects:

- Multiple IoT data sources from different public and private stakeholders including actuation services impacting the systems efficiency
- External advanced services (3D rendering, simulation tools, mobile apps,...) consuming and producing significantly complex/large datasets
- Wide variety of potential users (public servants, urban public service, inhabitants, energy experts etc.) with various levels of expertise and responsibility.

To address these ExPEDite challenges related to heterogeneous data sharing and management of decentralized / distributed complex data services, the proposed local MIM3 specification aims to partially cover the capabilities of the following building blocks from the DS4SCC blueprint catalogue:

- Data products definition and publication (capability 1)
- Organizational and operational agreements (capability 2)
- Data usage accounting (capability 3)

Intentionally, other important capabilities related to the "marketplace" concept, that might be covered in the global MIM3 specification, such as data products discovery, monetization / revenue sharing, etc., have NOT been included in the scope of the ExPEDite project.

MIM 3 **(ExPEDite version)**	**Contracts - ExPEDite SPECIFIC**
Objectives	Formalize, implement and track the decentralized digital services as data products to facilitate, clarify and flexibize the interaction between the various ExPEDite stakeholders, under a public governance.

Capabilities and requirements:

Capability 1	**All interoperable data services enabling interactions between internal systems or with solutions provided by a third party are systematically characterized in order to establish usage contracts between the stakeholders.**
Requirement 1	Possible or required interactions with digital assets are formalized for each relevant data model (MIM2) and for each relevant API (MIM1)
Requirement 2	The framework for using interaction services is characterized in the form of roles or profiles or context explaining the reasons or goals of these interactions.
Capability 2	**The responsibilities of stakeholders operating digital asset interaction services are formalized by specifying the limits to be respected.**
Requirement 3	Access to interaction services for each stakeholder is formalized in a form of contract listing the assigned roles/profiles/context
Requirement 4	Each role/interaction profile assigned to a stakeholder can be limited in time, space, or dynamically, depending on the context

Capability 3	The responsibilities of stakeholders operating digital asset interaction services are implemented and auditable
Requirement 5	The access control and security system (MIM6) implements the terms of interaction contracts during the actual use of services by stakeholders
Requirement 6	A transaction logging system allows auditing the use of interaction services by stakeholders and verifying the correct application of contracts

2.2. MIMs compliance assessment methodology

In the logic and in anticipation of the availability of the Interoperability Test Bed to support the Local Digital Twins Toolbox for Smart Communities which "*one of the main goals is to support the ecosystem with the ability to test for conformance against the interoperability framework defined by the MIMs Plus*", a first simple MIMs compliance assessment methodology has been proposed for the ExPEDite project. This methodology, called the MIM.meter, is leveraging the Y.MIM structure of the MIM **capabilities** and their associated **requirements** in order to evaluate the **mechanisms** that have been implemented and that should cover these requirements. The assessment is a simple rating calculation in which the capabilities and the requirements are weighted depending on the concrete needs and priorities of the involved stakeholders. The result is a percentage of compliance for each evaluated MIM, that can be used:

To rationalize the comparison (namely within a procurement process or an experimentation) of different possible mechanisms covering the same requirement in a specific situation
To identify expected improvements and to support the setting up of a roadmap aiming to upgrade implemented mechanisms

In the ExPEDite project the purpose of the MIM.meter would be limited to the identification of possible improvements and recommendations for possible upgrade or replacement of the implemented mechanisms to better comply with the MIMs.

2.2.1. MIM.meter introduction

One transparent, single - but granular - indicator: the compliance rate is a percentage calculated for each MIM and in the same way for all the MIMs. The percentage calculation is based on the following principles implementing a double weighting mechanism, at the **capability** level and at the **requirement** level:

- Each capability is linked to one single MIM, each requirement is linked to one single capability
- A relative weight is associate to each capability and to each requirement, depending on their relative importance to reach the maximum level of compliance with stakeholders expectations
- The value of a relative weight is an integer from 0 (criteria with no influence, for information only) to 10 (criteria is a non-negotiable "MUST")
- To meet a required requirement, one must describe (and, if possible, demonstrate) all the mechanisms implemented or envisaged to cover this required requirement. If it is

clearly established that all the mechanisms described effectively cover the required requirement, the score obtained is 1; otherwise, the score obtained is 0.

- The score obtained for the coverage of a capability is a percentage equal to the weighted average of the scores obtained by the responses to its related requirements.
- And finally, the level of compliance with the MIM is a percentage equal to the weighted average of the scores obtained for the coverage of its capabilities.

In this current version of the MIM.meter calculation, it is not possible to consider partial coverage of a requirement by a set of mechanisms. In a future version, the assessment would be able to be refined to take into account possible partial coverage, by adding a third level of specifications that breaks down requirements into more precise technical expectations.



Figure 3: Indicative interpretation of the weights for the MIM.meter

The weights assigned to each capability and each requirement are fundamentally important for obtaining relevant and useful results from the MIM.meter tool.

To achieve a good balance between flexibility, relevance, and transparency, the weights are limited to integer values, between 0 and 10. To frame this delicate task of reflecting and deciding on the relative importance of a capability and each requirement, the Figure 3 can be used as a reference.

2.2.2. The MIM.meter repository: specific weights of capabilities and requirements

The MIM.meter repositories are the core and decisive elements that could make the MIM.meter framework a valuable and relevant tool for the interested stakeholders. That's why, beyond the ExPEDite operational needs, in a more strategic perspective, the content of these repositories should be managed in a collaborative way with a "public interest" driven governance, integrating both "demand side" and "supply side". To refine the repository, and have the possibility to ponder the importance of each capability and each requirement (to comply with a MIM), a "double-weighting" mechanism is integrated in the repository, as described in the previous section.

In the tables below, a proposal of MIM.meter repositories for MIM1, MIM2 and MIM3 (specific ExPEDite version):

MIM.meter REPOSITORY for MIM 1 - Version 7.0 / march 2025						
MIM	**Cap. ID**	**Capability**	**Weight**	**Req. ID**	**Requirement**	**Weight**
1	**C1**	Applications are able to access data from different sources (such as cities, communities and vertical solutions)	**10**	**R1**	Context can be managed through the Web	10
				R2	Information from all sources should use the same concepts, so called data information models	8
					weighted total	**180**
	C2	Applications are able to use both current and historical data, use geospatial querying and be automatically updated when the source data changes.	**8**	**R3**	The web based API shall support retrieval of current data	10
				R4	The web based API shall support retrieval of historical data	8
				R5	The web based API shall support geospatial querying	6
				R6	The web based API shall support subscription to changes	6
					weighted total	**240**
	C3	Applications can discover and retrieve data relevant to their context from a variety of sources	**8**	**R7**	Relevant data sources to any required context (such as location and/or time period) should be discoverable and retrievable according to their context	10
					weighted total	**80**
	C4	Applications can retrieve a subset of data from a larger data set	**6**	**R8**	Specific subsets of data relevant to the context should be retrievable from within larger data sets and size limits can be set	10
					weighted total	**60**
					weighted total	**500**

MIM.meter REPOSITORY for MIM 2 - Version 7.0 / march 2025						
MIM	**Cap. ID**	**Capability**	**Weight**	**Req. ID**	**Requirement**	**Weight**
2	**C1**	All entities included in data sets are described using consistent data models to enable interoperability for applications and systems.	**10**	**R1**	Data models used for all entities in any data set shall be made explicit.	10
				R2a	Data models used shall be based (wherever possible) on commonly recognised sets of machine-understandable standardised data models as listed in the section below.	8
				R2b	Where it is not possible to use existing standardised data models, efforts shall be made to extend existing standardised data models that are most closely aligned or to define new ones, following best practice and conventions of the community or organisation defining the data models.	5
				R3	Data models used shall support the exchange of data via the context management API (MIM1).	10
					weighted total	**330**
	C2	All data sources in a data ecosystem use consistent identifiers for individual instances of each entity.	**8**	**R4**	The type of identifiers used for entities shall be made explicit.	10
				R5	Unique and persistent identifiers shall be used to identify particular instances of any entity used in data sets.	10
					weighted total	**160**
					weighted total	**490**

MIM.meter REPOSITORY for MIM 3 - Version exPEDite SPECIFIC / march 2025						
MIM	**Cap. ID**	**Capability**	**Weight**	**Req. ID**	**Requirement**	**Weight**
3	**C1**	All interoperable data services enabling interactions between internal systems or with solutions provided by a third party are systematically characterized in order to establish user contracts between the parties involved.	**10**	**R1**	Possible or required interactions with digital assets are formalized for each relevant data model (MIM2) and for each relevant API (MIM1)	10
				R2	The framework for using interaction services is characterized in the form of roles, profiles, etc. explaining the reasons or goals of these interactions.	8
					weighted total	**180**
	C2	The responsibilities of stakeholders (organization) operating digital asset interaction services are formalized by specifying the scopes and quotas to be respected.	**8**	**R3**	Access to interaction services for each stakeholder (organization) is formalized in a form of contract listing the assigned roles/profiles	10
				R4	Each role/interaction profile assigned to a stakeholder can be limited in time, space, or dynamically, depending on the context	5
					weighted total	**120**
	C3	Third party systems and applications (possible trusted "data services consumers") can access the relevant data services following agreed and formalized conditions (C2)	**7**	**R5**	The access control and security system (MIM6) implements the terms of the interaction contracts during the actual use of the services by the stakeholders	10
					weighted total	**70**
					weighted total	**370**

2.3. Incremental MIM.meter evaluation of the ExPEDite DT components

The above MIM.meter repositories will be applied and continuously improved in the framework of the WP3 activities, especially in the task T3.3 "Data Spaces integration suite" that is also strongly connected to Task 3.1 "Core data services".

Through T3.3, the ExPEDite Data Spaces Integration Suite (DSIS) is aiming to implement interoperability between the "internal" ExPEDite components and also interoperability with "external" systems, namely complementary sectoral data spaces such the ones federated around the BRIDGE EC initiative that brings together projects with a focus on smart energy systems (for instance OMEGA-X, EnerShare). In this perspective, the ExPEDite DSIS might reach a reasonable level of compliance with the MIMS, to get aligned with the approach of the European data space for smart communities - DS4SSC project.



Figure 4: A first evaluation of the MIM.meter will be performed for the first distribution of the implemented Core Data Services (performed within Task 3.1)

The MIM.meter will be used in WP3 in order to evaluate the implemented or envisaged mechanisms aiming to cover the requirements to enable the capabilities of MIM1, MIM2 and MIM3 following the approach described in this report. This will be done in an incremental manner in order to elaborate recommendations and decision making about the way to continuously improve the interoperability and then the replicability, scalability and sovereignty of the deployed ExPEDite solutions.

3. Guidelines for Sensor Network Consolidation

Sensor networks constitute a core element of smart cities, providing real-time data crucial for monitoring the dynamic conditions in urban environments. As cities rapidly expand, the demand for intelligent infrastructure that can enhance sustainability, efficiency, and overall quality of life continues to grow. Smart cities leverage advanced technologies to -among others- optimize urban management, with sensor networks playing a key role in data collection, processing, and analysis to support essential functions and decision-making. By transforming raw data into actionable insights, sensor networks can optimize energy management, enhance mobility tracking, improve real-time environmental monitoring, and strengthen public safety. More details on the importance of sensor network integration into the above-mentioned fields - relevant to the ExPEDite project - are presented below [1]:

- Effective energy management in smart cities poses a critical challenge due to rapid urbanization. Smart grids powered by IoT-enabled sensors provide real-time insights into energy usage patterns, enabling better resource management. IoT sensors integrated with renewables (e.g., solar panels, wind turbines) improve the efficiency of decentralized renewable energy sources (RES) systems by optimizing energy distribution and mitigating grid congestion. Additionally, smart buildings use sensors for Heating, Ventilation, and Air Conditioning (HVAC) equipment control, occupancy-based lighting, and energy conservation strategies, reducing unnecessary energy consumption. Through advanced energy analytics, sensor networks help lower carbon footprints, reduce energy costs, and enhance sustainability in urban environments [2].
- Urban mobility also benefits from sensor networks, which play a crucial role in traffic management, public transport optimization, and emissions reduction. Sensors embedded in traffic lights, electric vehicles (EV) charging stations, and public transport systems help regulate mobility and improve transport efficiency. Real-time traffic monitoring, utilizing sensors placed on roads and intersections, along with adaptive signal control, reduces congestion. Smart parking systems detect available spaces, lowering emissions caused by unnecessary driving. GPS-enabled sensors provide live updates on public transport services, reducing waiting times for passengers and improving overall accessibility [3].
- Environmental monitoring is a central use case of smart-cities sensor networks, enabling cities to track air quality, noise pollution, and other key environmental indicators in real time. Sensors embedded throughout urban infrastructure gather continuous streams of data, which help authorities identify anomalies, anticipate problems, and take proactive measures during emergencies. Beyond monitoring, this real-time insight supports smarter design and resource management, leading to more efficient city operations and improved service delivery [4].
- Public safety and emergency response also rely heavily on sensor networks. Seismic, flood, and fire sensors can provide early warnings for natural disasters, enabling faster response times and minimizing casualties. AI-powered surveillance networks assist in crime prevention and real-time threat detection, while motion-sensing streetlights improve pedestrian safety and optimize energy use [5].

The following sections explore the requirements of key smart city applications (section 3.1), provide an overview of the main communication protocols used in these use cases (section 3.2) and examine network design aspects, including topology, integration, and infrastructure planning (section 3.3). Section 3.4 maps each application to the most suitable protocol, while section 3.5 presents a plan for implementing, validating, and testing a sensor network deployment, including risk management and trouble shooting. Finally, section 3.6 focuses on hardware adaptations for energy sensing.

3.1. Main Smart Cities Use Cases: Purpose and Technical Requirements

This section addresses four key use cases in which sensor networks can find applications in the smart city context and examines their unique technical requirements. Parameters such as data volume, transmission frequency, latency thresholds, and reliability vary significantly across these applications, directly influencing the design and scalability of sensor systems. By understanding these needs, tailored solutions that balance performance, cost, and resilience, ensure seamless integration into the urban environment can be successfully deployed.

Note on Terminology: Terms such as latency, frequency, and data volume are used qualitatively throughout this document. These terms are context-dependent, but generally follow this pattern:

- **Latency**: ultra-low (<10 ms), real-time (10–100 ms), low (up to 1 s), delay-tolerant (>1 s).
- **Data** Acquisition Rate: high (≤10 s), moderate (10 s–1 min), low (>1 min), event-driven (on trigger).
- **Data Size**: small (KB/day), moderate (MB/day), large (few GB/day), very large (10+ GB/day)

These guide protocol and system recommendations across domains.

3.1.1. Energy Management

Energy Consumption Monitoring
Smart cities are increasingly deploying sensor networks to enhance energy consumption monitoring, ensuring efficient energy use and reducing unnecessary wastage. Real-time monitoring systems, integrated with IoT middleware, collect and analyze data from HVAC units, smart meters, and other high-consumption appliances. These systems track energy patterns and provide insights into power usage trends, enabling automated adjustments that optimize efficiency. Advanced metering infrastructure (AMI) and wireless sensor networks (WSN) facilitate continuous data acquisition, allowing for immediate corrective actions to prevent inefficiencies. Furthermore, AI and big data analytics can enhance demand-side management strategies and enable adaptive control of energy loads, particularly in commercial and residential buildings. By integrating predictive analytics with sensor data, these systems can anticipate peak demand periods and shift energy consumption accordingly, reducing stress on the grid [6] [7] [8] [9].

Needs:

- Data Size: Moderate to large, depending on the resolution scale of the energy monitoring.
- Data Acquisition Rate: 15-minute is the usual practice, while even higher frequency might be applied in specific use cases.
- Latency: Low, to support immediate load adjustments and ensure system responsiveness.
- Additional Requirements: Edge computing may be utilized for fast, localized processing and cloud-based analytics are usually utilized for in-depth historical trend analysis.

Grid Optimization

To improve grid stability and efficiency, sensor networks play a crucial role in real-time power flow monitoring and fault detection. Smart grids, enabled by IoT and AI-based decision systems, dynamically manage electricity distribution across grid nodes. Sensor nodes collect data on voltage levels, current flow, and power quality, allowing grid operators to balance loads and mitigate outages effectively.

Moreover, optimization techniques, such as particle swarm optimization (PSO) and genetic algorithms (GA), may be employed to enhance grid performance by optimizing the routing of electricity within microgrids. These methods help extend the network lifespan while minimizing energy loss during transmission.

Decentralized microgrids supported by peer-to-peer (P2P) energy trading ensure secure, real-time electricity transactions, reducing reliance on traditional utilities. Moreover, bi-directional energy flows allow smart cities to incorporate distributed renewable energy sources seamlessly [7] [8] [9] [10] [11].

Needs:

- Data Size: Very large due to real-time power flow and grid performance monitoring.
- Data Acquisition Rate: High-frequency updates for rapid grid balancing and resilience.
- Latency: Ultra-low to prevent power failures and maintain real-time responsiveness.

Decentralized Energy Production

Decentralized energy production in smart cities is driven by microgrids that connect distributed renewable energy sources such as solar panels and wind turbines. These microgrids operate on P2P energy trading platforms, allowing prosumers (energy-producing consumers) to sell excess electricity within the community. WSNs track energy generation, storage, and consumption in real-time, ensuring efficient energy balancing.

To enhance the efficiency of decentralized grids, bio-inspired algorithms are being used to improve routing strategies and minimize energy wastage. Advanced AI-based energy forecasting models further support smart grid optimization by predicting fluctuations in renewable energy supply and adjusting grid operations accordingly [8] [9] [10] [12] [13].

Needs:

- Data Size: Moderate to large depending on the number of prosumers and energy trading transactions.
- Data Acquisition Rate: Smart meters operate with a data rate of 5–15 minutes.
- Latency: The decentralized congestion management mechanism processes power flow decisions within 15-minute time steps.
- Additional Requirements: Secure IoT infrastructure ensuring low-latency, high-reliability, and scalable communication.

Real-Word Deployment: Use cases in Singapore and Los Angeles:

Singapore's Tengah eco-town is a pioneering example of sustainable energy management. This 42,000-home development integrates centralized cooling, solar-powered district air-conditioning, and an automated waste collection system to minimize carbon emissions. The entire town is designed around smart energy optimization, where water-cooled air conditioning reduces energy consumption by 30% compared to conventional units. Additionally, smart streetlights adjust their brightness based on pedestrian movement, further enhancing efficiency [14]. Similarly, Los Angeles has successfully implemented an intelligent lighting system where streetlights equipped with motion sensors reduce energy waste and improve public safety by illuminating areas only when needed [15].

3.1.2. Mobility and Transport

Traffic Flow Monitoring

Smart cities utilize sensor networks to optimize traffic flow monitoring, enabling real-time traffic management and congestion reduction. WSNs play a crucial role in gathering traffic data by detecting vehicle movements and road conditions. Intelligent Transport Systems (ITS) leverage data from GPS, roadside sensors, and connected vehicles to predict congestion patterns and adjust traffic signals accordingly.

Artificial intelligence (AI) and machine learning (ML) models help process large volumes of traffic data for forecasting and optimizing traffic light timing. Furthermore, cloud-based IoT applications enable the real-time integration of traffic information with navigation apps, improving route recommendations for commuters [16] [17] [18] [19].

Needs:

- Data Size: Large, as it involves continuous streaming from sensors, CCTV feeds, and GPS signals.
- Latency: Ultra-low to support immediate traffic flow and congestion adjustments and ensure system responsiveness.
- Data Acquisition Rate: High for responsive traffic light adjustments and rerouting.
- Latency: Ultra-low for effective congestion prediction and response.

Electric Vehicle (EV) Charging Stations

With the global push towards sustainability, smart cities are integrating sensor-driven EV charging networks to support electric mobility. Smart charging stations use IoT-enabled sensors to monitor grid demand, optimize energy distribution, and reduce the charging wait time.

AI-driven predictive models analyze traffic patterns to anticipate EV charging demand, ensuring optimal station placement. Wireless communication technologies, such as 5G and Vehicle-to-Infrastructure (V2I) networks, support seamless EV-to-grid interaction [7] [17] [19] [20] [21].

Needs:

- Data Size: Moderate to large, depending on charging transactions and grid analytics (several GB/day).
- Data Acquisition Rate: High-frequency updates for real-time load balancing.
- Latency: Low, for seamless charging station availability updates.
- Additional requirements: Strong encryption is utilized to secure energy transactions and prevent fraud.

Public Transport Tracking

Efficient public transport tracking systems leverage multi-agent sensor networks to provide real-time updates on bus and train schedules. GPS, RFID, and AI-based demand prediction models help optimize routes based on commuter density.

Passengers benefit from mobile applications providing live updates on public transport locations, expected arrival times, and seat availability. Dynamic scheduling, enabled by machine learning algorithms, adjusts transit frequency based on real-time passengers [20] [22] [23].

Needs:

- Data Size: Low to medium, as it involves continuous updates from GPS, ticketing, and passenger-count sensors.
- Data Acquisition Rate: High-frequency updates for real-time scheduling and commuter information.
- Latency: Ultra-low to ensure real-time tracking and scheduling.

Real-Word Deployment: Use case in Tokyo

Tokyo's smart mobility strategy revolves around seamless multi-modal integration, allowing commuters to switch effortlessly between trains, subways, buses, and bicycles. The city leverages real-time information systems to provide live updates on delays and platform changes, enhancing travel efficiency and reducing congestion. AI-powered traffic management optimizes public transport schedules, while digital fare collection and smart ticketing improve user convenience. To further promote sustainability, Tokyo invests in electric buses, high-speed rail, and widespread bicycle-sharing programs. The city also experiments with autonomous vehicles and AI-driven traffic signals, ensuring future-ready, efficient, and eco-friendly urban transport [24].

3.1.3. Environmental Monitoring

Air Pollution Monitoring

Urban air pollution is a significant public health concern, caused primarily by traffic emissions, industrial activities, and energy consumption. IoT-based pollution sensors detect multiple health-related parameters, such as particulate matter (PM2.5, PM10), carbon monoxide (CO), nitrogen oxides (NO_2), sulfur dioxide (SO_2), and volatile organic compounds (VOCs) in real-time. Data is analyzed and visualized in cloud platforms, allowing policymakers and citizens to respond effectively to pollution spikes [25] [26] [27].

Needs:

- Data Size & Storage: Medium datasets, due to continuous sensor readings, often requiring cloud-based storage and big data analytics.
- Data Acquisition Rate: Low frequency monitoring, typically every 5-15 minutes, to capture pollution fluctuations.
- Latency: Low latency is essential for real-time alerts, particularly for hazardous gas leaks or high-pollution episodes.
- Additional requirements: Pollution data are often integrated with traffic and industrial emission control systems to automate mitigation actions.

Weather Monitoring

Weather sensor networks in smart cities play a crucial role in climate adaptation, disaster response, and energy optimization. IoT-based weather stations measure temperature, humidity, wind speed, and precipitation, providing real-time meteorological data to inform decision-making. These systems improve storm tracking, flood prevention, and heatwave management [28] [29] [30] [31] [32] [33].

Needs:

- Data Size & Storage: Moderate to large datasets i.e. hundreds of megabytes (MB) to gigabytes (GB) of data per day, depending on sensor density and resolution, often requiring cloud-based processing.
- Data Acquisition Rate: Varies from hourly for general weather reports, to every 1 minute for storm tracking and extreme weather events.
- Latency: Low latency, every 1-15 minutes, mostly critical for disaster alerts and flood warnings to ensure timely responses.
- Energy Efficiency: Remote weather sensors need solar or battery power for long-term operation with minimal maintenance, as they are usually placed in high-grounds and remote areas with no physical infrastructure, such as power availability.

Noise Pollution Tracking

Urban noise pollution, primarily from traffic, nightlife, and construction, negatively impacts public health and quality of life. Smart acoustic sensors monitor decibel levels, helping cities enforce noise regulations, optimize traffic flow, and improve urban planning. Some systems incorporate AI-based sound classification to detect emergencies (e.g., car crashes, gunshots) and automatically alert authorities [25] [29] [34] [35] [36].

Needs:

- Data Size & Storage: Small datasets per sensor (10.5 MB/ year), as audio monitoring requires high-resolution sampling and long-term trend analysis.
- Data Acquisition Rate: Moderate monitoring to detect sudden spikes in noise levels.
- Latency: Emergency noise event detection requires low latency, while noise mapping can afford minutes to hours of delay.
- Additional Requirements: This aspect may be combined with smart city security systems for AI-driven event detection and emergency response.

Real-Word Deployment: Use case in Stockholm & Amsterdam

Stockholm is a leader in environmental monitoring through its smart waste management system, using underground pneumatic waste transportation to reduce truck emissions, noise, and congestion. The city also monitors air and water quality through a sensor network, enabling real-time pollution tracking and response. Amsterdam, under the CITY-zen project, has implemented smart water and air quality sensors to track pollution levels and manage urban heat islands. The city also integrates smart stormwater systems to prevent flooding and optimize water resource management [37].

3.1.4. Public Safety and Security

Smart Surveillance Systems

Modern surveillance goes beyond passive CCTV. AI-enhanced cameras, motion sensors, and real-time analytics now detect and prevent crime before it happens. These systems identify faces, track vehicles, and analyze crowd movements, alerting law enforcement within seconds if something suspicious occurs. Fog computing processes video feeds closer to their source, ensuring low-latency alerts and faster police responses [38] [39] [40] [41].

Needs:

- Data Size: Terabytes of high-resolution video footage, which demand scalable storage
- Data Acquisition Rate: 24/7 streaming requires high-bandwidth, low-latency networks
- Latency: Ultra-low latency to ensure instant threat detection for relevant use cases in smart cities deployments

Emergency Response Systems

Traditional emergency response relies on human reporting and dispatch delays. Smart cities, however, use IoT-connected sensors to detect accidents, fires, and medical emergencies instantly [40]. For example, impact sensors in vehicles may automatically alert Emergency Medical Services (EMS) after a crash. Moreover, AI-driven fire detection systems may send real-time updates before flames spread [38] [40] [42] [43].

Needs:

- Data Size: Moderate to large, depending on the use case of the sensor data streams.
- Data Acquisition Rate: Moderate, 10-50 second updates, in order to allow for instant detection of emergency situations.
- Latency: Ultra-low latency ensures immediate first responder dispatch.
- Additional Requirements: End-to-end encryption and AI-driven prioritization ensure secure and efficient responses.

Critical Infrastructure Monitoring

A city's power, water, and transport systems must remain operational to prevent chaos. IoT sensors monitor infrastructure health, detecting failures before they occur. For example, vibration sensors on bridges detect stress fractures early, while AI-driven predictive maintenance prevents electrical grid overloads [38] [39] [42].

Needs:

- Data Size: Medium to large data stream, depending on the infrastructure needs.
- Data Acquisition Rate: High, as real-time diagnostics ensure proactive maintenance.
- Latency: Real-time, to allow timely responses to failures.
- Additional requirements: AI-driven diagnostics protect critical assets.

Real-Word Deployment: Use cases in Singapore & New York City

Singapore has established itself as a "city of sensors," deploying an extensive network of surveillance cameras and sensors to monitor public spaces, deter criminal activities, and ensure citizen safety. This comprehensive system enables real-time data collection and analysis, facilitating prompt responses to potential threats. Similarly, New York City's Domain Awareness System (DAS) exemplifies the use of IoT in urban security. Developed in collaboration with Microsoft, DAS integrates approximately 18,000 CCTV cameras, automated license plate readers, and various environmental sensors to monitor and respond to incidents across the city. This system enhances situational awareness and supports law enforcement in maintaining public safety [44] [45].

3.2. Overview of Communication Protocols for Smart City Networks

Smart city networks rely on a variety of communication protocols, each designed to meet specific requirements and to ensure seamless data exchange between various IoT devices and infrastructure components. The right communication protocol depends on the application—whether it's a low-power environmental sensor, a high-speed video surveillance system, or a large-scale smart grid.

3.2.1. Wired Protocols

Ethernet

Ethernet, based on the IEEE 802.3 standard, is the most widely used wired communication protocol for networking, including smart city applications [46]. It supports both Local Area Networks (LANs) and Metropolitan Area Networks (MANs) and is crucial in providing high-speed, reliable networking solutions. [46] [47] [48] [49].

Examples of Use Cases in Smart Cities:

- Smart traffic and transportation systems. Ethernet provides real-time sensor data to optimize traffic flow and road safety.
- Smart grid communication: Backbone for energy distribution and monitoring.
- Municipal surveillance and security camera networks.
- Smart city analytics: Supports real-time traffic monitoring, waste management, and energy planning.

Advantages:

- High Data Transfer Speeds: Ethernet supports data rates ranging from 10 Mbps up to 400 Gbps, making it suitable for smart cities that require real-time, high-bandwidth applications.
- Scalability: Due to its flexibility, Ethernet can be used for both short-range applications (home automation, smart buildings) and long-range applications (fiber-optic Ethernet for city-wide networks).
- Low Latency: The protocol ensures low network delays, making it ideal for real-time communication in smart cities, including intelligent transportation, smart traffic lights, and emergency response systems.
- Security: Since Ethernet operates on a wired infrastructure, it is less vulnerable to cyber threats compared to wireless networks.
- Industrial noise resistance: Works well in factories and outdoor environments.

Power over Ethernet (PoE) enables simultaneous power and data transmission, allowing Ethernet to support devices in locations without direct power access. This enhances deployment flexibility for remote IoT infrastructure.

Disadvantages:

- High Installation Costs: Requires extensive physical cabling infrastructure, increasing deployment and maintenance costs.
- Limited Mobility: Devices must be physically connected to the network, restricting movement and requiring additional cabling for network expansion.

Modbus

Modbus is a serial communication protocol developed for industrial automation, commonly used in smart city IoT networks due to its simplicity and reliability [49]. Originally developed by Modicon (now Schneider Electric), it operates on a client-server architecture and is widely used in monitoring municipal infrastructure [46] [47] [48] [49].

Examples of Use Cases in Smart Cities:

- Smart metering for electricity, water, and gas.
- Traffic light and road infrastructure control.
- Building automation for HVAC and lighting systems.
- Industrial automation in municipal services.

Advantages:

- Simplicity: Its straightforward master-slave structure makes it easy to implement and troubleshoot, reducing technical complexity.
- Reliability: Modbus is designed for harsh industrial environments, making it ideal for critical infrastructure such as smart water treatment plants and power grids.
- Low Bandwidth Requirements: Modbus can operate efficiently over low-bandwidth networks such as RS-485 and RS-232, making it suitable for low-data applications.

Disadvantages:

- Low Data Transfer Speed: Unlike Ethernet, Modbus has much lower transmission speeds, typically. ranging from 9.6 kbps to 115.2 kbps, making it unsuitable for high-speed data applications.
- Limited Distance: RS-485 Modbus networks have a maximum range of about 1.2 km, restricting city-wide applications.
- Security Vulnerabilities: Lacks built-in encryption, making it susceptible to cyber threats.
- Strict transmission rules (requires contiguous transmission).
- Complex configuration and programming requirements.

BACnet (Building Automation and Control Network)

BACnet is a specialized communication protocol for building automation, developed by ASHRAE (American Society of Heating, Refrigerating and Air-Conditioning Engineers). It is widely used in smart cities for HVAC, lighting, security, and energy management [46] [47] [48].

Examples of Use Cases in Smart Cities:

- Smart buildings and energy-efficient infrastructure.
- BACnet integrates HVAC, lighting, security, and fire detection into a single network.
- Fault detection & maintenance: Provides real-time diagnostics and alarms to improve building efficiency.
- Integration with smart power grids.
- Remote monitoring & control: Enables building managers to control automation systems remotely.

Advantages:

- Interoperability: It allows different building automation systems to communicate, making it highly flexible for integrating smart city infrastructure.
- Low Bandwidth Usage: BACnet is optimized for low-speed, low-data applications, making it efficient for monitoring smart buildings without requiring high-speed networks.
- Flexible Communication Options: It supports multiple communication media, including Ethernet, IP, and serial networks, allowing seamless integration.

Disadvantages:

- Slow Data Rates: BACnet is not designed for high-speed or real-time applications, with speeds ranging from 9.6 kbps to 100 Mbps.
- Complex Setup: Integrating BACnet into an existing smart city network requires specialized knowledge, increasing installation complexity.
- Limited Use Cases: It is mainly suited for building automation and not ideal for transportation or city-wide communication networks.

Table 1 : Overview of wired communication protocols for smart cities

Feature	Protocols		
	Ethernet	**Modbus**	**BACnet**
Data Speed	10 Mbps – 400 Gbps	9.6 kbps – 115.2 kbps	9.6 kbps – 100 Mbps
Latency	Low	Medium	Medium
Security	High	Low	Medium
Scalability	High	Medium	Medium
Power Efficiency	Moderate (with PoE)	High	High



Figure 5: Ranking of wired communication protocols by core features

3.2.2. Wireless Protocols

Below is a comprehensive overview of the main wireless communication protocols used in smart cities, their typical use cases, and their advantages and disadvantages in terms of data transfer speeds, bandwidth requirements, and physical infrastructure.

Low-Power Wide-Area Networks (LPWAN) technologies are designed to support long-range communication with low power consumption, making them ideal for smart city applications requiring extended battery life and widespread coverage. These networks support relatively low data rates but excel in covering large areas, often requiring minimal infrastructure.

LoRaWAN (Long Range Wide Area Network)

LoRaWAN is one of the most widely used LPWAN technologies, specifically designed to enable long-range wireless communication between IoT devices and centralized gateways. It also operates in the unlicensed spectrum, enabling cost-effective deployment. LoRaWAN is particularly well-suited for applications where devices need to send small amounts of data periodically while maintaining low power consumption. [46] [48] [50] [51].

Examples of Use Cases in Smart Cities:

- Smart metering (electricity, water, gas).
- Environmental monitoring (air quality, temperature, humidity).
- Noise pollution tracking.
- Smart street lighting (remote monitoring and control).
- Smart agriculture (soil moisture and weather monitoring).
- Smart parking (public spaces) and EV charging stations.
- HVAC in large public buildings – updates expected with climate change.

Advantages:

- Long-range communication – Up to 15 km in rural areas and up to 5 km in urban settings, depending on the urban density and physical topology.
- Low power consumption – Devices can last up to 10 years on a single battery.
- Cost-effective – Operates in an unlicensed spectrum, reducing infrastructure and operational costs.
- Bidirectional communication – Enables remote control and configuration of IoT devices.

Disadvantages:

- Low data rate – Limited to 0.3-50 kbps, making it unsuitable for high-bandwidth applications.
- High latency – Not ideal for real-time applications due to transmission delays.
- Requires dedicated gateways – Needs infrastructure to connect devices to the internet.
- Limited scalability in dense networks – Performance can degrade in high-node deployments.

Sigfox

Sigfox operates similarly to LoRaWAN, offering ultra-low-power, long-range connectivity but with even lower data rates. It is particularly useful for applications that require infrequent small data transmissions. [46] [48] [51].

Examples of Use Cases in Smart Cities:

- Asset tracking and logistics.
- Remote monitoring of infrastructure (pipelines, bridges).
- Smart waste management (sensor-based garbage collection).
- Smart agriculture (livestock tracking).

Advantages:

- Ultra-low power consumption – Devices can operate for over 10 years on battery power.
- Wide coverage – Can cover up to 40 km in rural areas and 10 km in urban areas.
- Minimal infrastructure requirements – Operates on a global network with pre-existing coverage.
- Cost-effective – Uses an unlicensed spectrum, making deployments affordable.

Disadvantages:

- Extremely low data rate – Limited to 100 bps, restricting its use to small periodic messages.
- High network latency – Data transmission delays make it unsuitable for real-time applications.
- Limited downlink communication – Mainly supports uplink data, with minimal ability to send data back to devices.
- Dependency on Sigfox's proprietary network – Limited coverage in regions where Sigfox infrastructure is unavailable.

Cellular networks provide a well-established communication infrastructure with strong reliability and widespread coverage. However, they generally consume more power, making them less ideal for battery-powered IoT devices.

LTE (Long-Term Evolution)

LTE is a widely adopted cellular network technology that offers high-speed internet connectivity and robust performance, making it suitable for applications that require real-time data transfer [46] [48] [49] [51] [52].

Examples of Use Cases in Smart Cities:

- Smart traffic management (real-time congestion data).
- Surveillance cameras in smart cities.
- Public safety communication networks.
- Emergency services and disaster response.

Advantages:

- High data rates – Up to 100 Mbps, enabling real-time applications.
- Strong security – Advanced encryption and authentication features.
- Wide network coverage – Uses existing cellular infrastructure.
- Low latency – Suitable for time-sensitive applications like traffic control.

Disadvantages:

- High power consumption – Not ideal for battery-powered IoT devices.
- Costly deployment – Requires SIM cards and mobile subscriptions.
- Network congestion – Performance can degrade in densely populated areas.
- Limited penetration in underground environments – Weaker signals in basements and tunnels.

5G is the latest evolution of cellular networks, designed to provide ultra-fast data rates, ultra-low latency, and support for massive IoT deployments. Unlike previous generations of cellular networks, 5G operates on a combination of high-frequency millimeter-wave bands, mid-band spectrum, and low-band frequencies, allowing it to balance speed, coverage, and connectivity density [53] [54].

Examples of Use Cases in Smart Cities:

- Autonomous vehicles and smart transportation – Enabling real-time vehicle-to-vehicle (V2V) and vehicle-to-infrastructure (V2I) communication.
- Smart surveillance and emergency response systems.
- Smart healthcare – Remote robotic surgeries, telemedicine, and AI-assisted diagnostics.
- Smart grids and energy management – Real-time monitoring and predictive maintenance of power grids.
- Critical infrastructure monitoring.
- Noise pollution tracking.
- AI-driven smart city analytics – Real-time video analytics for security, traffic management, and urban planning.

Advantages:

- Extremely high data rates – Up to 10 Gbps, supporting real-time applications like AI-driven monitoring.

- Ultra-low latency – Less than 1 millisecond (ms), enabling instantaneous response for autonomous systems.
- Supports massive IoT connectivity – Can handle up to a million devices per square kilometer.
- Flexible network slicing – Allows customized network performance for different smart city applications.

Disadvantages:

- High infrastructure costs – Requires significant investment in small cell towers and fiber-optic backhaul.
- Limited range in high-frequency bands – Millimeter waves have poor penetration through buildings and require dense network coverage.
- High power consumption – Not suitable for low-power IoT devices needing years of battery life.
- Complex deployment – Requires integration with existing LTE networks and new standalone infrastructure.

NB-IoT (Narrowband IoT)

NB-IoT is a low-power cellular technology specifically designed for IoT applications, offering better power efficiency than LTE while still leveraging existing cellular networks. [46] [48] [49] [51].

Examples of Use Cases in Smart Cities:

- Smart parking and street lighting.
- Water quality and pipeline monitoring.
- Smart agriculture (for example, remote soil monitoring).
- Industrial automation (for example, predictive maintenance).

Advantages:

- Low power consumption – Devices can last up to 10 years on a single charge.
- Excellent penetration – Works well in underground and remote locations.
- Cost-effective – Uses a narrow bandwidth, reducing operational costs.
- Reliable connectivity – Operates on licensed spectrum, ensuring minimal interferences.

Disadvantages:

- Limited bandwidth – Not suitable for high-data applications like video streaming.
- Higher latency – Slower than LTE and 5G.
- Carrier-dependent – Requires support from network providers.
- Limited mobility support – Not optimized for fast-moving devices like vehicles.

Finally, **Local Wireless Networks** serve short-range IoT applications where high data rates, low latency, or device interoperability are essential. These include Wi-Fi, Zigbee, and Bluetooth, each optimized for different smart city use cases.

Wi-Fi

Wi-Fi is a widely used wireless communication technology that provides high-speed connectivity for urban areas. It is often deployed in smart buildings, public spaces, and enterprise environments, where reliable broadband connectivity is necessary [46] [51] [53].

Examples of Use Cases in Smart Cities:

- Smart surveillance cameras – High-definition video transmission for security applications.
- IoT-enabled smart buildings – Energy management, automated HVAC systems, and smart lighting.
- Connected healthcare – Hospital Wi-Fi for medical devices and patient monitoring.

Advantages:

- High-speed data transmission – Up to 1 Gbps with Wi-Fi 6, suitable for bandwidth-intensive applications.
- Broad device compatibility – Supports a vast range of consumer and industrial IoT devices.
- No carrier dependency – Unlike LTE and 5G, Wi-Fi does not require cellular network operators.
- Flexible deployment – Can be installed in homes, offices, and public spaces at a relatively low cost.

Disadvantages

- Limited range – Typically covers up to 100-300 meters indoors and requires multiple access points for larger areas.
- High power consumption – Not ideal for battery-operated IoT devices.
- Network congestion – Performance may degrade in crowded areas with many Wi-Fi networks.
- Security vulnerabilities – Susceptible to hacking if not properly encrypted.

Zigbee

Zigbee is a low-power wireless communication protocol designed for short-range applications in home automation, industrial monitoring, and smart city infrastructure. Unlike Wi-Fi, Zigbee operates in a mesh network, where devices communicate with each other rather than a central router [51] [52].

Examples of Use Cases in Smart Cities:

- Smart lighting systems – Automated streetlights that adjust brightness based on real-time conditions.
- Home and building automation – Smart thermostats, security systems, and energy monitoring.
- Industrial IoT monitoring – Sensor networks for tracking equipment performance.

Advantages:

- Low power consumption – Devices can operate for years on a small battery.
- Mesh networking capability – Extends coverage by allowing devices to relay messages.
- Reliable and scalable – Scalable in dense, short-range mesh networks, but not across large geographic areas, it can support thousands of nodes in a single network.

- Interoperability – Compatible with multiple IoT standards for smart homes and cities.

Disadvantages:

- Limited data rate – Up to 250 kbps, making it unsuitable for high-bandwidth applications.
- Short range – Typically 10-100 meters indoors, requiring multiple nodes for larger coverage.
- Interference issues – Operates in the 2.4 GHz band, which is shared with Wi-Fi and Bluetooth.
- Complex setup – Requires configuring and maintaining a mesh network.

Bluetooth

Bluetooth is a short-range wireless communication technology commonly used in smart city applications requiring low power and moderate data transfer speeds. The introduction of Bluetooth Low Energy (BLE) has significantly improved its efficiency for IoT devices [46] [51] [52].

Examples of Use Cases in Smart Cities:

- Smart wearables and healthcare – Fitness trackers, heart rate monitors, and medical devices.
- Indoor positioning and tracking – Smart beacons for navigation in airports, malls, and museums.
- Smart home automation – Bluetooth-enabled locks, thermostats, and appliances.
- Connected vehicles – Hands-free communication and infotainment systems.

Advantages:

- Low power consumption – BLE extends battery life for years in IoT applications.
- Widely adopted – Nearly all smartphones, tablets, and IoT devices support Bluetooth.
- Secure communication – Features encryption and authentication mechanisms.
- No infrastructure needed – Works in peer-to-peer or small network configurations.

Disadvantages:

- Limited range – Typically 10-100 meters, requiring repeaters for larger coverage.
- Low data rates – Supports up to 3 Mbps, insufficient for high-bandwidth applications.
- Susceptible to interference – Operates in the crowded 2.4 GHz band.
- Not suitable for large-scale IoT deployments – Unlike Wi-Fi and Zigbee, Bluetooth lacks robust networking capabilities.

Table 2: Overview of wireless communication protocols for smart cities.

Feature	LPWAN		Cellular			Local Wireless Networks		
	LoRaWAN	**Sigfox**	**LTE**	**NB-IoT**	**5G**	**Wi-Fi**	**Zigbee**	**Bluetooth**
Data Speed	0.3-50 kbps	100 bps	Up to 100 Mbps	Up to 250 kbps	Up to 10 Gbps	Up to 1 Gbps	Up to 250 kbps	Up to 3 Mbps
Latency	High	High	Low	Moderate	Very Low	Low	Moderate	Low
Security	Moderate (AES 128)	Low	High (LTE encryption)	High	Very High	High	Moderate	Moderate
Scalability	High	High	Moderate	High	High	High	Moderate	Low
Power Efficiency	Very High (10+ years battery life)	Very High (10+ years battery life)	Low	High	Low	Low	High	High



Figure 6: Ranking of wireless communication protocols by core features

3.3. Network Design for Smart City Sensor Networks

3.3.1. Topological Considerations

Energy Management

Effective topological configurations not only are crucial for the sustainability and functionality of smart city sensor networks but also enhance data transmission reliability and scalability. Among the most effective designs for energy management in smart cities are Mesh Networks and Hierarchical Networks. Their selection and implementation must balance redundancy, scalability, and operational efficiency to support the diverse needs of urban infrastructure.

Wireless Mesh Networks (WMN) provide a decentralized and self-healing structure, making them ideal for smart city applications. Their ability to reroute data dynamically enhances network reliability and ensures continued operation in case of node failures [55]. However, traditional WMNs can suffer from excessive energy consumption due to continuous data forwarding across multiple hops. To mitigate this, energy-aware routing protocols and adaptive node sleep strategies can help reduce power consumption during periods of low demand [56]. While mesh networks offer high resilience, their scalability can lead to increased interference and latency. Hierarchical network architectures address these limitations by structuring communication into multiple tiers. In this approach, lower-level nodes handle local data processing, reducing unnecessary transmissions to central hubs [57]. This organization enhances energy efficiency by aggregating sensor data at intermediary nodes before relaying it to higher-tier systems, thereby reducing overall power demands and transmission overhead.

The hybrid integration of mesh and hierarchical networks combines the strengths of both models, ensuring enhanced fault tolerance, scalable expansion, and optimized energy use. For example, hierarchical micro-cloud deployments can aggregate and process local sensor data before transmitting it via WMNs, balancing energy demands across the network [57]. For smart city sensor networks to be truly energy-efficient, network design must incorporate adaptive power control mechanisms that adjust transmission power based on traffic load and network congestion [56].



Figure 7: Hierarchical wireless sensor network architecture
https://www.researchgate.net/publication/51929133_A_Key_Establishment_Scheme_for_Mobile_Wireless_Sensor_Networks_UsingPost-Deployment_Knowledge



Figure 8: Wireless mesh network diagram
https://en.wikipedia.org/wiki/Wireless_mesh_network

Mobility and Transport

A well-designed smart sensor network for mobility and public transport requires an optimized network topology that ensures resilience, scalability, and high-speed communication. It has to provide seamless real-time data transmission but also demonstrates strong resistance to failures and disruptions, ensuring service continuity in a highly interconnected urban environment. Given the dynamic nature of urban transport, particularly for moving nodes such as buses, trams, and shared mobility systems, integrating 5G-enabled high-speed wireless links and robust topological structures is essential.

The resilience of public transport sensor networks is a key factor in ensuring uninterrupted mobility services, particularly in the face of disruptions such as network failures, congestion, or cyber threats. Recent studies highlight that transport networks designed with higher redundancy, shorter average path lengths, and greater connectivity density tend to recover more efficiently from disruptions [58]. For instance, cities with dense and interconnected metro networks, such as London, Paris, and New York, exhibit superior recoverability compared to more fragmented systems like those in Oslo or Rome, which suffer significant performance losses during failures [58]. Implementing layered and hierarchical network structures allows critical infrastructure nodes to be prioritized for rapid reconnection, thus minimizing downtime [27]. The integration of 5G and ultra-low-latency wireless networks is essential for real-time data exchange in smart city mobility systems. High-speed wireless networks improve vehicle-to-infrastructure (V2I) and vehicle-to-vehicle (V2V) communication, enhancing the responsiveness of transport services through dynamic route optimization and predictive analytics [59]. 5G connectivity also facilitates edge computing, enabling localized data processing on moving nodes, which reduces congestion in centralized systems and improves traffic management efficiency [60].

Smart city transport networks frequently exhibit small-world and scale-free characteristics, which contribute to greater efficiency and resilience [61]. These properties ensure that while a network remains highly connected, it also minimizes unnecessary path redundancies, reducing travel time and optimizing resource allocation. Studies indicate that metro systems with scale-free topology, where a few key nodes act as highly connected hubs, are more resilient to random failures but remain vulnerable to targeted attacks on critical infrastructure nodes [59]. This highlights the need for hybrid topological models, particularly in shared mobility networks such as public bicycle systems, where a combination of hub-and-spoke and mesh network topologies ensures robust connectivity, even in cases of localized failures [62].



Figure 9: Small-world network model structure
https://www.mdpi.com/1424-8220/21/21/7097



Figure 10: Scale free topology
https://en.wikipedia.org/wiki/Scale-free_network

To enhance fault tolerance, modern urban transport networks should be designed using hierarchical interconnection models, which provide multi-layered redundancy and self-healing capabilities. Research into hierarchical topologies demonstrates that these structures offer superior connectivity maintenance under stress conditions, making them ideal for large-scale urban mobility applications [63]. Moreover, transport networks with cyclic connectivity and inter-loop structures tend to display higher robustness, ensuring minimal service disruption in the event of station or link failures [61]. Such approaches should be prioritized in urban planning strategies to ensure long-term sustainability.



Figure 11: Multi-layer network architecture
https://www.researchgate.net/figure/Multi-layer-network-architecture_fig1_334073014

A well-planned sensor network should focus on high-traffic nodes and intersections to enhance monitoring efficiency. Public transport networks that utilize station clustering and dynamic route optimization can significantly reduce network congestion and improve passenger flow efficiency [61]. Additionally, decentralized and distributed sensor placements reduce single points of failure, ensuring that the public transport network remains operational even in the case of localized disruptions [58]. Deploying multi-layered network architectures ensures that no single failure can cause widespread disruptions, a crucial factor in designing next-generation smart city networks.



Figure 12: Hybrid Topological Model
https://hitechmv.com/what-is-hybrid-topology/



Figure 13: An example of a hub-and-spoke network topology
https://learn.microsoft.com/en-us/azure/cloud-adoption-framework/ready/azure-best-practices/hub-spoke-network-topology

Environmental Monitoring

For environmental monitoring in smart cities, a star network topology is an effective choice due to its low power consumption, simple deployment, and ease of maintenance. In this setup, multiple sensor nodes communicate directly with a central hub, eliminating the need for complex routing. This makes it ideal for urban environments where sensors are widely dispersed and need to operate on minimal energy [64].

One of the biggest advantages of the star topology is its energy efficiency. Since each sensor only transmits data to the central hub, there is no need for multi-hop communication, significantly reducing power consumption and extending sensor battery life [65]. This is particularly useful for remote environmental monitoring, where battery replacement can be difficult and costly. Technologies such as ZigBee and LoRa are commonly used for these networks, offering low-energy communication with reliable data transmission [66].

Scalability is another key benefit. New sensors can be added to the network with minimal impact on existing infrastructure, making it adaptable to the evolving needs of smart cities [67]. However, one major limitation is the single point of failure—if the central hub fails, the entire network is compromised. To mitigate this, redundancy measures like backup hubs or dual communication links should be considered [68].

Urban environments present challenges such as signal interference and physical obstructions. Buildings, traffic, and other wireless networks can disrupt data transmission. Implementing frequency hopping and spread spectrum techniques can help maintain signal integrity [69] Additionally, security concerns must be addressed through encryption and authentication protocols to prevent unauthorized data access [70].

For successful implementation, node placement is crucial. Sensors should be strategically positioned to ensure maximum coverage while maintaining reliable connectivity to the hub. Data aggregation at the hub can help reduce network congestion and improve processing efficiency [64]. Using energy-

harvesting techniques, such as solar-powered sensors, can further enhance sustainability and minimize operational costs [65].



Figure 14: Star Network Topology
https://www.boardinfinity.com/blog/star-topology/

Public Safety and Security

The increasing integration of the Internet of Things (IoT) in urban safety frameworks underscores the need for a well-structured network topology capable of supporting mission-critical applications [71]. Additionally, multi-node topological approaches help in optimizing communication pathways and ensuring effective data relay in real-time scenarios [69].

Public safety networks must be designed to withstand both physical and cyber threats. A multi-tiered approach using hierarchical interconnection networks (HINs) enhances coordination and rapid response [63]. Ensuring redundancy through mesh networking and fault-tolerant clustering mechanisms enhances the network's ability to sustain operations during emergencies [69].

As cities evolve and expand, network architectures must accommodate increasing sensor deployments. Multi-node topology models facilitate adaptive configurations where sensor nodes can adjust their roles based on demand, ensuring seamless data flow across the system [69]. Decentralized architectures, including Mobile Ad-hoc Networks (MANETs) and hybrid Wireless Sensor Networks (WSNs), enable scalability and fault tolerance [71]. Additionally, implementing cost-effective solutions for large-scale networks, such as lightweight protocols and LPWAN technologies, ensures broad coverage while maintaining energy efficiency [68].

Cluster-based topologies efficiently manage sensor nodes by grouping them based on geographic or functional parameters, reducing network congestion and improving response times. The use of small-world network models in public safety applications has also demonstrated improved data propagation efficiency and overall network resilience [69]

Hybrid models integrate traditional sensor networks with opportunistic sensing and crowdsensing approaches to leverage existing infrastructure [71]. These networks employ cloud-enabled platforms to analyze and distribute sensor data, improving response coordination in crisis scenarios.



Figure 15: Conceptual decentralized IoT architecture from a low-level perspective
https://www.researchgate.net/publication/350461668_A_Conceptual_Architecture_in_Decentralizing_Computing_Storage_and_Networking_Aspect_of_IoT_Infrastructure



Figure 16: Cluster-based network topology
https://www.researchgate.net/publication/369739253_Machine_learning-based_clustering_protocols_for_Internet_of_Things_networks_An_overview



Figure 17: Mobile Ad Hoc Network architecture (MANET)

www.researchgate.net/publication/316291648_A_combined_sceme_of_video_packet_transmission_to_improve_cross_layer_to_support_QoS_for_MANET

3.3.2. Network Redundancy and Reliability in Smart City Sensor Networks

Ensuring high availability and fault tolerance is crucial for smart city sensor networks, particularly for critical services such as energy monitoring, traffic management, and public safety. Network redundancy minimizes downtime by providing alternative pathways for data transmission, preventing service disruption due to failures in hardware, connectivity, or cyber-attacks [72].

Redundancy Strategies

Smart city infrastructures rely on multiple redundancy strategies to ensure uninterrupted service. Geographic redundancy ensures network availability by deploying multiple network nodes across different locations. Multi-RAT (Radio Access Technology) connectivity, incorporating cellular, Wi-Fi, and LPWAN technologies, enhances network resilience by allowing devices to switch between networks dynamically. Similarly, multi-IMSI SIMs enable devices to switch carriers automatically, ensuring continued connectivity in case of an outage [73].

Edge Computing for Fault Tolerance

To improve response time and reliability, edge computing plays a vital role by processing data closer to the source, reducing latency, and mitigating risks associated with cloud dependency. Cloud-based architectures allow local processing for real-time applications, such as emergency response systems, and ensure operational continuity even if centralized cloud services fail [74].

Redundant Routing and Self-Healing Mechanisms

Smart city networks implement redundant routing algorithms that reroute data in case of node failures. Techniques such as state-machine replication and consensus protocols enhance fault tolerance in distributed IoT environments [75]. Additionally, autonomous fault detection and recovery mechanisms, leveraging AI and machine learning, optimize network performance by predicting and mitigating failures in real time [76].

Ensuring Survivability in Disruptions

Resilience planning must account for large-scale disruptions such as cyber-attacks or natural disasters. The "islands of resilience" concept suggests building independent network segments capable of functioning autonomously if severed from the core infrastructure [77]. Moreover, deploying hardened corridors of resilience between network nodes ensures survivability and reduces the risk of total network failure [77].

By integrating multi-layer redundancy, real-time fault tolerance, and distributed intelligence, smart city sensor networks can ensure continuous service availability, critical for urban safety and efficiency. Future advancements in AI-driven anomaly detection and adaptive networking will further enhance reliability, making smart cities more resilient to failures.

3.3.3. Integration of Various Sensor Types - Interoperability

Integrating multiple sensor types into a unified smart city network is a significant challenge due to variations in communication protocols, data formats, and interoperability requirements. As urban areas become more reliant on the IoT to manage traffic, environmental monitoring, public safety, and energy consumption, ensuring seamless sensor integration is critical [78]. The heterogeneous nature of IoT devices requires cross-domain interoperability, including technical, syntactic, semantic, and cross-domain interoperability, to enable seamless communication [79].

The primary obstacle in sensor integration is the heterogeneity of sensor hardware and software. Sensors used in smart cities range from air quality monitors and surveillance cameras to traffic detectors and weather sensors, each operating on different communication standards such as LoRaWAN, Zigbee, and NB-IoT [80]. The competitive IoT market leads to fragmentation and a lack of universal standards, increasing the risk of non-interoperability across different sensor manufacturers [79]. Additionally, IoT devices vary in power consumption, communication bandwidth, and computational capabilities, requiring adaptive strategies for integration [79]. On the issue of scalability, as cities grow, the number of connected sensors increases, requiring a scalable architecture that can integrate new devices without major overhauls [81].

Smart city interoperability challenges can be categorized into four layers: (1) Sensing Layer, (2) Access Network Layer, (3) Internet/Cloud Layer, and (4) Application Layer. This structured approach helps in identifying challenges and implementing targeted solutions for seamless integration [82].

One of the proposed strategies to address the challenges of sensor integration is the Middleware platforms which serve as an essential bridge between disparate sensor networks, enabling seamless data translation and protocol conversion [78]. It abstracts the underlying hardware and software differences, allowing seamless integration. Implementing frameworks such as the Open Geospatial Consortium (OGC) SensorThings API and FIWARE allows for a standardized data flow across different IoT devices [83]. Standardized APIs enhance compatibility between sensors, enabling a unified data-sharing ecosystem [84].

To address network-level interoperability, policy-based management (PBM) and Media Independent Handover (MIH) frameworks may be utilized if necessary. These solutions help manage connectivity across heterogeneous wireless networks in complex environments, ensuring seamless transitions between different protocols such as 5G, Wi-Fi, and LoRaWAN. For example, PBM enforces network-wide policies to optimize Quality of Service (QoS) and ensure efficient bandwidth usage [82].

Additionally, efficient IoT communication protocols such as LoRaWAN, Zigbee, NB-IoT, MQTT, and Constrained Application Protocol (CoAP) are essential for multi-sensor integration in smart city networks [84]. Fog and cloud computing help manage large sensor networks by processing data locally at the edge before transmitting it to centralized storage [84]. One successful implementation is the Barcelona Smart City Initiative, which integrates various sensor types to optimize urban services. Using a combination of LoRaWAN for long-range communication and APIs for real-time data exchange, the city has improved traffic management, air quality monitoring, and public safety measures [81]. Additionally, hybrid integration models that combine network-based integration (sensors connecting via gateways) and independent integration (direct Internet connectivity for sensors) allow for greater deployment flexibility [79].

AI-driven data fusion techniques aggregate information from various sensors to improve data accuracy and decision-making in smart city applications [85]. Pattern recognition algorithms detect anomalies in traffic, environmental monitoring, and public safety networks, enhancing the reliability of sensor networks [85]. The combination of machine learning and IoT analytics ensures real-time adaptation to dynamic urban environments.

Heterogeneous smart city networks pose significant security challenges due to inconsistencies in authentication, encryption, and access control mechanisms. Many IoT platforms rely on proprietary security policies, making cross-platform authentication difficult. OAuth-based access control frameworks have been proposed as a solution to manage security interoperability between diverse systems [82]. Additionally, a zero-trust architecture can be employed to ensure secure data exchanges between devices operating on different protocols. This model enforces strict identity verification and continuous monitoring of data transactions, reducing the risk of unauthorized access and cyber threats [82].

Table 3: Interoperability challenges and proposed solutions across smart city architecture layers

	Interoperability Challenges	**Proposed Solutions**
Sensing Layer	• Heterogeneous sensor hardware & software • Inconsistent data formats (JSON, XML, CSV, etc.) • Variations in power consumption & connectivity	• Standardized data models (some examples include OGC SensorThings, NGSI-LD) • Use of Middleware platforms for seamless data translation and protocol conversion • Use of efficient protocols like LoRaWAN, Zigbee, NB-IoT, MQTT • IoT gateways for cross-protocol communication • Edge computing for local data processing

Access Network Layer	• Multiple wireless technologies (LoRaWAN, Zigbee, 5G, Wi-Fi, NB-IoT) • Network congestion & interference	• Use of adaptive multi-protocol communication frameworks • Load balancing algorithms to reduce congestion if necessary
Internet/Cloud Layer	• Data integration challenges (Semantic & Syntactic Interoperability) • Middleware incompatibility • Cloud security risks & data governance • Lack of data synchronization across heterogeneous sensors	• Standardized middleware integration (e.g. Thingsboard, oneM2M, FIWARE) • API management platforms for seamless cloud communication • Zero-trust security frameworks • Implementation of a unified time standard, such as Coordinated Universal Time (UTC), ensures accurate and consistent timestamping across all sensor networks.
Application Layer	• Incompatibility across platforms • Security vulnerabilities in open data platform • Lack of common standards for service interoperability	• Adoption of RESTful APIs for service interoperability • OAuth-based authentication mechanisms • Compliance with GDPR & open governance policies

3.3.4. Data Acquisition Rates and Data Synchronization in Smart City Sensor Networks

In the context of smart cities, the data acquisition rate is essential in determining the responsiveness and reliability of urban monitoring and management systems. It directly influences the accuracy, timeliness, and efficiency of services such as energy optimisation, traffic management, and environmental monitoring. The extensive deployment of heterogeneous sensors, ranging from energy meters to environmental monitors, result in high-volume and high-velocity data that must be processed rapidly to enable real-time or near-real-time responses. Without appropriate control of acquisition rates, systems risk either overloading infrastructure or missing critical decision windows [86].

Furthermore, data acquisition rate has broader implications for data quality, system scalability, and operational costs. While high-frequency sampling improves responsiveness and resolution, it also imposes greater demands on energy consumption and communication infrastructure. In contrast, lower-frequency sampling conserves resources but may reduce the granularity of insights. Dealing with temporal variability and managing the dimensionality of incoming data remain ongoing challenges in urban data systems. Consequently, adjustment of acquisition rates in accordance with the specific needs of each application, will ensure balance between performance, resource efficiency, and service quality [86]. The optimal data acquisition rate in smart city applications varies significantly depending on the functional and operational requirements of each domain. In energy management, for instance, acquisition intervals typically range from 5 to 15 minutes for applications like smart metering. These intervals strike a balance between responsiveness and energy efficiency. In more sensitive scenarios, such as grid optimization and load balancing, acquisition rates may further increase, in order to support

dynamic voltage control, fault detection, and predictive analytics. As previously noted, low-latency, high-frequency acquisition is vital for maintaining stability and efficiency in high-load grids and microgrid ecosystems.

For traffic and mobility systems, the requirement is continuous, high-frequency data streams, especially for real-time congestion management, traffic signal control, and vehicle tracking, to ensure responsive decision-making and reduce delays.

Environmental monitoring, such as air and noise pollution tracking, typically operates on a low acquisition cycle, with 5–15-minute intervals sufficient for most use cases. Lastly, public safety and emergency systems rely on real-time acquisition and streaming, particularly in surveillance and incident detection, where even small delays can compromise outcomes.

Data synchronization is a critical requirement in sensor networks, especially in the context of smart cities where diverse sensors collect, transmit, and analyze data either in real-time or at scheduled intervals, depending on the application. Proper synchronization ensures consistency in timestamping, prevents data conflicts, and enhances the reliability of decision-making processes. Wireless sensor networks (WSNs) and Internet of Things (IoT) applications rely on precise synchronization to facilitate tasks such as event detection, localization, data aggregation, and security monitoring [12]. However, synchronization in WSNs faces several challenges, including clock drift and offset, where sensor nodes use independent clocks that tend to drift due to environmental factors like temperature fluctuations, hardware inconsistencies, and voltage variations [87]. Additionally, limited computational and energy resources present a challenge, as sensor nodes operate with constrained power and processing capacity, making it impractical to use computationally heavy synchronization algorithms [88]. Network latency and jitter also impact synchronization accuracy, as communication delays caused by propagation time, medium access control (MAC) layer latencies, and queuing effects can introduce inconsistencies [89].

To mitigate these issues, various synchronization techniques are employed in sensor networks. Network Time Protocol (NTP) is widely used in traditional networking for synchronizing clocks across distributed systems. However, due to its high resource consumption, it is often unsuitable for energy-constrained sensor networks [90]. Precision Time Protocol (PTP), as defined in IEEE 1588, is a high-precision synchronization method that achieves sub-microsecond accuracy by reducing jitter and latency effects, making it suitable for applications like industrial automation, though it may still be resource-intensive for IoT deployments [87]. GPS-based timestamping provides highly accurate timestamps across sensor nodes but is power-intensive and not feasible for indoor or underground sensor deployments [88]. Another approach is receiver-to-receiver synchronization, in which reference broadcast synchronization (RBS) is used. A beacon node transmits a reference signal without a timestamp, and receiving nodes record their local timestamps and exchange them to compute offsets, thereby improving accuracy and reducing message exchange overhead [89].

The Flooding Time Synchronization Protocol (FTSP) is another widely used approach, which employs a hierarchical method where a root node disseminates its clock information in a multi-hop manner. This method is effective for large-scale sensor networks but is susceptible to congestion and delay variation [90]. Some approaches focus on data-driven synchronization rather than synchronizing node clocks. This method, known as per-hop synchronization, reduces energy consumption by avoiding frequent clock adjustments [87].

To further enhance synchronization efficiency, the Skew Integrated Timestamp (SIT) method integrates skew correction at the physical layer, allowing synchronization with a single timestamp exchange. SIT significantly reduces computational overhead, thus making it highly suitable for resource-limited smart city nodes [91]. Explicit guidelines on protocol selection can further optimize synchronization accuracy and efficiency—highly precise protocols like PTP or SIT should be employed for real-time applications

such as grid optimization or public safety, whereas less demanding methods like simplified FTSP or RBS may suffice for environmental monitoring, where ultra-high precision is less critical.

Despite the existing methods, perfect synchronization remains unattainable due to inherent network constraints. Future research should focus on hybrid approaches that combine multiple synchronization techniques, such as GPS-assisted NTP, to balance accuracy and energy efficiency. AI-driven synchronization can further enhance accuracy by leveraging machine learning to predict and correct clock drifts dynamically.

However, the integration of such advanced synchronisation mechanisms is not considered necessary as the majority of relevant use cases, such as those targeted within the exPEDite project, do not require sub-second precision. Instead, achieving a time accuracy within a range of a few seconds is sufficient for ensuring coherence across data streams. This level of accuracy can be reliably maintained by verifying consistent timestamping practices and ensuring all data sources are aligned to a defined time scale, such as the Coordinated Universal Time (UTC).

3.3.5. Physical Infrastructure Planning Guidelines

As previously discussed, smart city sensor networks require a well-structured communication infrastructure that balances reliability, scalability, and cost-effectiveness. The choice between wired and wireless networks depends on application-specific needs such as latency, bandwidth, power availability, and environmental constraints.

Wired networks provide high reliability, security, and low latency, making them essential for critical applications like traffic control, public safety systems, and energy management [92]. Ethernet-based solutions, including the Ethernet Advanced Physical Layer (Ethernet-APL), offer a unified industrial networking approach that simplifies cabling while enabling power-over-data capabilities. This reduces the need for separate power lines, improving deployment efficiency [93]. Although Ethernet and fiber networks require higher upfront investment, they offer long-term reliability and lower maintenance costs compared to cellular-based solutions.

For automation systems, Modbus and BACnet remain widely used due to their seamless integration with industrial controllers and IoT systems. Single Pair Ethernet (SPE) is emerging as an alternative to traditional Ethernet, reducing cabling complexity while ensuring long-distance communication at lower installation costs [94]. However, deploying wired infrastructure requires careful planning of cable routing, shielding against electromagnetic interference, and ensuring environmental durability [95].

A key challenge in deploying smart city and industrial sensor networks is ensuring reliable power supply, especially in locations where grid access is unavailable or unstable. For instance, when deploying environmental or motion sensors along roads or in public parks, cities must ensure access to reliable power in locations that may lack utility connections. In cases like this, integrating PoE-compatible cabling within new light poles or traffic signal masts is an increasingly adopted strategy, allowing future sensor nodes, cameras, or air quality monitors to be powered directly from the city's communication backbone without needing separate electrical circuits. Such planning reduces trenching and installation costs, and ensures long-term scalability.

Equally important is the matter of internet connectivity. In cases of limited or intermittent connectivity, whether due to lack of wired backhaul, signal interference, or cost barriers, smart infrastructure must also be designed to cope with these constraints. Ensuring robust and redundant network connections is vital for the real-time transmission of data from sensors to central systems. This may involve planning for both wired and wireless communication channels to accommodate different environmental and operational scenarios within a large-scale smart city deployment. For instance, wired Ethernet for core

operations and wireless networks for edge connectivity provides flexibility without compromising reliability [96].

Wireless networks provide flexibility and ease of deployment, making them ideal for distributed sensor networks, air quality monitoring, and smart metering. LoRaWAN is a preferred option for smart cities due to its low power consumption, long-range capabilities, and ability to support large-scale deployments at minimal cost. However, the optimal placement of LoRaWAN gateways is crucial to ensure maximum coverage and minimal interference, particularly in urban environments with high signal obstructions [96]. Critical systems (e.g., emergency response networks) usually have both wired and wireless backup paths to prevent service disruptions. Implementing failover mechanisms where LTE or Wi-Fi can serve as a backup in case of wired connection failure.

For applications requiring real-time data processing, such as autonomous transport systems, LTE-M and 5G networks provide higher bandwidth and lower latency [97]. However, the dependency on telecom operators and infrastructure costs should be carefully evaluated when selecting LTE-based solutions.

Ethernet-based networks provide stronger security, while wireless networks require robust encryption and authentication measures [95]. Smart city networks should be designed for future expansion with minimal infrastructure modifications [92]. A hybrid approach leverages wired backbones for high-bandwidth applications, such as traffic systems and video surveillance, while wireless nodes connect sensors in difficult-to-reach locations [98].

3.3.6. Power Management in Smart City IoT Sensor Networks

The increasing reliance on IoT sensors in smart cities presents a fundamental challenge: ensuring a stable and efficient power supply. Continuous energy availability is essential for real-time monitoring of traffic, environmental conditions, and security systems. However, large-scale deployments often face issues such as high energy consumption, inconsistent power distribution, and inefficiencies across networks [98]. These challenges are particularly severe in remote or inaccessible areas where grid power is unreliable, necessitating the integration of alternative energy sources such as solar panels, kinetic energy harvesting, and fuel cells [72] [99].

To address these power constraints, energy harvesting techniques have gained traction. Strategically placing sensors in high-sunlight or high-motion areas enhances self-sufficiency and reduces dependence on frequent battery replacements, which is especially beneficial in locations where maintenance is impractical [72] [99]. Furthermore, integrating battery storage solutions and decentralized energy management models such as smart grids can bolster system resilience and sustainability [98].

Optimizing energy consumption at the sensor level is also crucial. Employing energy-efficient hardware like low-power microcontrollers, adaptive sensing methods, and optimized power cycling significantly extends battery life [99]. Communication protocols such as duty cycling and power scaling help minimize unnecessary energy drain, while edge computing reduces data transmission overheads, further lowering energy requirements [98] [72].

In terms of network design, clustering sensor nodes and using multi-hop communication can effectively distribute energy loads, preventing premature depletion in high-traffic nodes [100]. Adaptive routing algorithms that consider real-time power availability further enhance efficiency and prolong operational life [101]. Sleep-wake scheduling mechanisms, particularly those powered by AI-driven optimization, ensure sensors remain active only when needed—conserving energy without sacrificing data reliability [102].

Table 4: Energy management challenges and solutions in IoT-Based urban infrastructure

Challenge	Description	Proposed Solutions
Power Supply Instability	Unreliable power distribution in urban infrastructure affects sensor network reliability	• Integration of smart grids and decentralized energy systems • Power-aware distribution and monitoring using ML
Power Accessibility in Remote Areas	Remote sensor nodes lack consistent grid access and are difficult to maintain	• Use of renewable energy sources (solar, kinetic, fuel cells). • Deployment in high-exposure locations • Battery storage solutions
High Energy Consumption at Node Level	Sensors consume excessive energy, especially during sensing and data transmission	• Low-power hardware and microcontrollers • Adaptive sensing, power cycling techniques, edge computing to reduce transmission loads • Calibration on data frequency depending on use case
Uneven Energy Load Distribution	Certain nodes deplete power faster due to their location or data traffic volume	Clustering, multi-hop communication, and adaptive routing algorithms that respond to real-time power levels
Inefficient Activity Scheduling	Continuous operation leads to wasted energy during idle periods	AI-driven sleep-wake schedules; adaptive duty cycling based on network demand and node priority

3.3.7. Assessment of Deployment in Different Environments

Dense Urban Centers

Urban environments pose unique challenges due to high building density, signal interference, and limited space for sensor placement. Optimal deployment strategies in these areas must prioritize three key factors. Ensuring that critical areas such as roadways, pedestrian zones, and public transport hubs are well covered. Given the complexity of urban landscapes, deploying sensors with adaptive placement strategies that rely on real-time data collection and feedback mechanisms can enhance coverage. Optimizing sensor density using machine learning models helps identify high-priority areas and adjust node placement dynamically [103]. Additionally, leveraging mesh networks and multi-hop communication can mitigate signal blockage from tall structures. Rather than a one-size-fits-all approach, a hybrid method that incorporates short-range and long-range communication ensures that urban sensors remain connected despite obstacles [102].

Implementing energy-aware routing protocols to extend sensor lifespan in power-constrained environments. Approaches such as low-power communication modes and optimized transmission intervals have been proposed to minimize energy consumption while maintaining data accuracy. Some studies also recommend the use of ambient energy sources such as solar-powered nodes, particularly in areas where infrastructure constraints make frequent maintenance challenging [104].

Suburban areas present different challenges, such as larger deployment zones and fewer obstacles. Key considerations include deploying modular sensor nodes that can be expanded as urbanization progresses [100] and combining fixed and mobile sensors to enhance adaptability and reduce blind spots [99]. Lastly, optimizing sensor density can balance cost and performance while maintaining adequate coverage [105].

Physical Obstructions and Signal Interference

Numerous obstructions such as high-rise buildings, dense foliage, and large metallic structures, can block or reflect wireless signals. This results in signal attenuation, increased packet loss, and reduced connectivity [101].

Solutions may involve: first of all, positioning sensors at higher elevations or near reflective surfaces to optimize signal propagation. In dense urban environments, this could involve mounting sensors on existing infrastructure like streetlights and traffic signals to ensure stable connectivity [102]. Secondly, utilizing alternative communication pathways will ensure uninterrupted data transmission. This approach is particularly useful in dynamically changing environments where temporary obstructions such as large vehicles or construction sites may intermittently block signals. Research indicates that routing protocols designed to detect and adjust to fluctuating signal conditions improve overall data reliability [104].

Impact of Weather Conditions & Electromagnetic Interference

Temperature fluctuations can affect sensor materials and electronic components, leading to calibration drift and inaccurate readings. In extreme heat, sensors may experience increased resistance, signal noise, and potential degradation of internal components, while extreme cold can cause battery depletion and mechanical failures [101]. To mitigate temperature effects, adaptive calibration techniques allow sensors to adjust to extreme heat or cold, ensuring accurate readings over time. Additionally, thermally stable materials and sealed enclosures protect sensor electronics from temperature-induced degradation [106]. Humidity and prolonged exposure to moisture can lead to corrosion, short circuits, and erratic sensor behavior, particularly in marine and industrial environments. Water ingress can affect electrical conductivity and degrade sensor enclosures over time. Waterproof casings, hydrophobic coatings, and desiccants are commonly used solutions [107]. For mission-critical applications, moisture-resistant sensors with sealed protective housing and built-in humidity compensation can improve reliability [106].

In this context, the required IP (Ingress Protection) rating of a sensor plays a crucial role in ensuring reliability under specific environmental conditions. The IP code defines the degree of protection a sensor enclosure provides against the ingress of solid particles and liquids. For instance, sensors deployed in coastal regions must withstand salt-laden air and persistent humidity, conditions that can rapidly corrode components and degrade performance thus requiring IP66 or higher to ensure durability [101]. In heavily polluted urban or industrial zones, airborne particulates and chemical pollutants can impair sensor function, necessitating at least IP6X-rated housings to block dust and fine particles [108]. Similarly, IP67 or IP68 protection is critical in flood-prone areas or installations exposed to sustained rainfall [106]. For marine or offshore environments, where submersion, salt spray, and mechanical vibration are common, robust and corrosion-resistant enclosures are essential [107].

Precipitation can weaken wireless signals, particularly in high-frequency sensor networks. Rain can scatter and absorb radio waves, leading to increased attenuation and reduced transmission range, especially in millimeter-wave and optical sensor networks [109]. Snow and fog have a similar impact, as water vapor absorbs electromagnetic signals, reducing effective network coverage. Error correction algorithms and redundancy mechanisms may help ensure stable data transmission during extreme weather [108]. Lastly, sensors deployed in high-traffic zones, industrial sites, and transportation networks face continuous vibrations and mechanical stress, which can affect sensor calibration and data accuracy [108]. Shock-absorbing materials, rigid enclosures, and mechanical dampers help protect sensors from physical damage.

Electromagnetic interference (EMI) also poses a significant challenge to the reliability of wireless sensor networks in smart cities. EMI can originate from intentional sources, such as jamming and high-power electromagnetic pulses, or unintentional sources, including industrial equipment, power lines, and other wireless networks [110]. The impact of EMI can result in data corruption, signal loss, and degraded sensor functionality, necessitating robust mitigation strategies. Unintentional Electromagnetic Interference arises from industrial machinery, nearby wireless systems, and urban infrastructure, causing signal degradation and packet loss [111]. Moreover, intentional Electromagnetic Interference (IEMI), includes jamming attacks and high-power microwave (HPM) sources designed to disable communication in critical networks. These attacks can affect both individual sensor nodes and access points, leading to network-wide failures. High EMI levels can lead to packet errors, communication lags, and complete data loss, particularly in high-frequency wireless sensor networks operating in the 2.4 GHz and 5 GHz bands [110]. EMI also affects Bluetooth and Wi-Fi-based sensors, causing performance degradation in real-time applications such as traffic monitoring and emergency response systems [140].

Advanced strategies for mitigating EMI in Sensor Networks include the use of EMI-shielded enclosures and laminated encapsulation materials which can protect sensors from high-power interference [110]. Materials such as ProofCap have also been shown to effectively block electromagnetic fields while allowing selective frequency transmission for communication. [110]. Multi-band communication protocols allow sensor networks to switch frequencies dynamically to avoid interference [111]. Spread-spectrum techniques, such as Bluetooth frequency hopping and direct sequence spread spectrum (DSSS), help reduce EMI susceptibility by distributing signals over multiple frequencies. If one channel is disturbed by a narrow-band source, the impact on overall communication is minimal due to the large number of remaining channels. [110]. For Cyber-Physical Security, intrusion detection systems (IDS) and EMI monitoring tools can be used to detect intentional interference in real time [112]. AI-driven interference detection enables proactive responses by adjusting communication channels dynamically.

3.4. Mapping Smart City Use Cases to Communication Protocols

Selecting optimal communication protocols for different smart city networks demands a balanced evaluation of data volume, transmission frequency, latency, power efficiency, coverage, security, and cost. Each application has unique requirements which directly influence system efficiency, scalability, and performance. An overview of these factors and their implications follows below.

For high-bandwidth applications, for instance – like real-time video surveillance, smart traffic systems, and AI-driven analytics – protocols such as Ethernet, LTE, and 5G are suggested. On the other hand, low-bandwidth applications (e.g., smart metering, environmental monitoring, waste management, and infrastructure diagnostics) can benefit from lightweight protocols like LoRaWAN, Sigfox, Modbus, or Zigbee, which minimize data overhead while ensuring reliability.

Applications requiring (near-) real-time data exchange, such as smart grids, emergency response, autonomous vehicles, and live security monitoring, rely on low-latency/ high-frequency protocols like

5G, LTE, or Wi-Fi. Non-time-sensitive systems, including smart waste management, water metering, air quality monitoring, and asset tracking, can utilize more energy-efficient protocols like LoRaWAN and Sigfox, which transmit intermittent data packets, extending battery life for IoT devices.

Ultra-low latency is critical for autonomous vehicles, traffic coordination, smart grids, and remote healthcare, making 5G and Ethernet ideal. Less time-sensitive applications, like smart agriculture, parking sensors, and waste management can use NB-IoT, LoRaWAN, or Zigbee, prioritizing energy savings over speed.

Battery-dependent deployments (e.g. water monitoring, smart street lighting, parking, air quality sensors) often operate in locations without easy access to the power grid, such as remote water tanks, street poles, or underground parking lots. These scenarios require low-power communication protocols (LoRaWAN, Sigfox, NB-IoT) to extend battery life and minimise maintenance needs. In contrast, grid-powered use cases (e.g. energy consumption monitoring in buildings, smart surveillance systems, electric vehicle charging stations) can rely on high-power protocols (Ethernet, 5G, LTE, Wi-Fi) that support higher data rates and consistent connectivity.

LPWAN protocols (LoRaWAN, Sigfox, NB-IoT) can offer city-wide coverage for traffic monitoring, smart metering, infrastructure diagnostics, HVAC in large buildings, waste management, logistics, and street lighting. Cellular networks (LTE, 5G) offer medium-range solutions for smart grids, public safety, autonomous vehicles, and city analytics, while short-range protocols (Wi-Fi, Zigbee, Bluetooth) serve localized needs like smart buildings, industrial automation, and home energy management.

Critical infrastructure (energy grids, emergency services, government networks) demands high-security protocols like Ethernet, LTE, and 5G. LPWAN technologies (LoRaWAN, Sigfox) require additional encryption layers for vulnerable applications. Moderate-security uses, such as smart buildings and industrial IoT, can employ Zigbee, BACnet, or LoRaWAN – preferably – with enhanced security extensions.

In terms of cost-effectiveness, LPWAN solutions (LoRaWAN, Sigfox) can be implemented in rural, agricultural, and waste management applications, with minimal infrastructure, while Wi-Fi, Zigbee, and NB-IoT can combine affordability and performance for urban IoT applications. High-cost, high-performance options (e.g., 5G, LTE, fiber-based Ethernet) are essential for mission-critical systems despite significant infrastructure investments.

Concluding, successful protocol selection relies heavily on balancing real-time needs, power constraints, coverage, security, and budget.

- High-speed, low-latency applications prioritize 5G, LTE, or Ethernet.
- Battery-operated, long-range deployments leverage LPWAN.
- Localized systems benefit from Wi-Fi or Zigbee.

By aligning these considerations, cities can deploy scalable, efficient networks tailored to diverse IoT ecosystems and urban challenges [113] [114] [115] [116] [117].

3.4.1. Energy Management

When consolidating sensor networks for energy management in smart cities and industrial applications, selecting the right communication protocol is crucial for balancing reliability, scalability, and efficiency. Both wired and wireless protocols offer distinct advantages depending on the use case, infrastructure constraints, and energy efficiency requirements.

Wired protocols like Modbus and Ethernet are widely used in industrial automation and energy monitoring due to their stability, low latency, and high data throughput. Modbus-Ethernet integration enables real-time power consumption monitoring, temperature tracking, and humidity control, ensuring precise data acquisition from industrial meters [115]. The Modbus RTU (RS485-based) variant is often preferred for deterministic communication in smart grids and industrial environments [118]. Ethernet, on the other hand, supports high-bandwidth IP-based communication, making it ideal for smart city sensor networks that require seamless integration with cloud-based analytics and IoT frameworks [119].

For sensor networks in smart cities, wireless protocols such as Zigbee, LoRaWAN, and NB-IoT provide scalable, cost-effective solutions. Zigbee is ideal for short-range, low-power communication, particularly in building automation and demand-response coordination [120]. Its mesh networking capabilities enhance redundancy and self-healing, making it suitable for distributed sensor deployments.

For long-range, low-power applications, LoRaWAN is effective in energy metering and remote sensor data collection, offering several kilometers of coverage with minimal infrastructure. However, LoRaWAN and Sigfox suffer from interference and packet loss, leading to potential latency issues in real-time applications. These findings align with recent research emphasizing that LoRaWAN and Sigfox, while excellent for wide-area coverage with low power consumption, are unsuitable for time-sensitive applications such as real-time grid monitoring or rapid demand response [121] [122] [123].

Additionally, 5G and upcoming 6G networks are emerging as enablers of low-latency, high-reliability sensor communications, making them particularly useful for demand response mechanisms and distributed energy resource (DER) integration. These networks provide real-time data exchange with near-instantaneous feedback, improving the efficiency of sensor-driven automation in smart grids and microgrid operations [123]. Furthermore, 5G and Wi-Fi are also shown to improve local energy processing, reducing latency and enhancing real-time analytics, allowing for faster decision-making in energy management applications [124].

To ensure optimal sensor network performance, a hybrid communication model integrating wired (Ethernet, Modbus) and wireless (Zigbee, LoRa, 5G, NB-IoT) is recommended. This combination allows flexibility, enabling real-time data collection from critical wired infrastructure while extending connectivity to remote, mobile, or hard-to-wire environments. 5G's ultra-reliable low-latency communication (URLLC) capabilities make it ideal for rapid-response energy control, while LoRa and NB-IoT provide cost-efficient solutions for wide-area monitoring [123].

Security remains a major concern: LoRa and Sigfox networks are vulnerable to interference-based attacks, and authentication is being explored to secure peer-to-peer energy transactions [122]. Ensuring that data integrity and secure IoT gateways are part of the sensor network consolidation plan is critical for preventing cyber threats in energy management networks [123].

Table 5: Optimized communication protocols for various energy management applications

Primary Use Cases	Best Protocols	Why?
Industrial automation, real-time power monitoring	Modbus (RTU/Ethernet)	High reliability, deterministic communication
Smart city infrastructure, cloud data aggregation	Ethernet (IP-based)	High bandwidth, seamless cloud integration
Building automation, demand-response coordination	Zigbee	Low-power, scalable mesh network
Remote sensor monitoring, energy metering	LoRaWAN	Long-range, low-power operation
Low-power wide-area connectivity for smart grids	NB-IoT	Reliable wide-area communication
Low-latency energy management, DER integration	5G/6G	Ultra-reliable, high-speed data transfer
Local real-time analytics, real-time monitoring in multiple control panels, microgrid optimization	Wi-Fi	Improves real-time local processing

Real-Word Deployment: Use case in Bosnia & Herzegovina

Gradiška, Bosnia & Herzegovina, has implemented an innovative LoRaWAN network for intelligent street lighting as part of its transition toward smart urban living. Through this network, individual lights or groups of lights can be remotely monitored and controlled, adjusting their brightness based on time, weather conditions, or specific events. The smart street lighting solution reduces energy consumption and maintenance costs while increasing public safety and improving urban aesthetics. This deployment exemplifies the integration of IoT technologies in energy management to enhance sustainability and operational efficiency in public infrastructure [125].

3.4.2. Mobility and Transport

Selecting the right communication protocol is essential for mobility and transport applications, ensuring efficient data collection, real-time processing, and network optimization. The three dominant technologies—NB-IoT, LTE, and 5G—each serve distinct roles based on latency, bandwidth, and power efficiency.

5G is transforming mobility with its ultra-low latency (<10ms) and massive connectivity, making it indispensable for autonomous vehicle communication, real-time traffic analytics, and smart transport management [126]. Its ultra-reliable low-latency communication (URLLC) is particularly valuable in emergency response systems, where instantaneous data transfer is required for accident prevention and dynamic rerouting [117]. Trials in smart intersections and urban mobility networks have proven 5G's

ability to enable real-time sensor fusion between vehicles and infrastructure, improving safety and efficiency.

Long-Term Evolution (LTE) remains a widely used protocol in traffic and fleet management due to its moderate latency, broad network coverage, and sufficient bandwidth for real-time monitoring. LTE is the backbone of many Intelligent Transport Systems (ITS), supporting applications such as dynamic traffic signal control, vehicle telemetry, and GPS-based tracking [126].

Despite its versatility, LTE struggles with ultra-low latency demands, making it insufficient for applications requiring split-second decision-making, such as autonomous driving.

For low-bandwidth, energy-efficient applications, NB-IoT is the optimal choice. It is particularly suited for smart parking systems, roadside environmental monitoring, and vehicle tracking [114]. With superior power efficiency, NB-IoT sensors can last over 10 years on a single battery, making them ideal for long-term roadside sensor networks. However, frequent cell handovers limit NB-IoT's effectiveness in high-speed mobility applications.

A comparative analysis of NB-IoT and LTE-M found that LTE-M outperforms NB-IoT in vehicle telemetry and dynamic fleet management, thanks to its higher throughput and lower latency [127]. LTE-M supports higher mobility speeds (above 100 km/h), making it more suitable for real-time vehicle diagnostics and connected public transport systems, whereas NB-IoT struggles with frequent network transitions in fast-moving vehicles [127]. Thus, NB-IoT remains ideal for static, energy-sensitive transport applications, while LTE-M excels in real-time monitoring of moving vehicles.

Table 6: Optimized communication protocols for various mobility and transport applications

Primary Use Cases	Best Protocols	Why?
Smart Traffic Lights	LTE / 5G	Adaptive control of congestion based on real-time traffic data
Fleet Management	LTE	Supports live tracking, vehicle diagnostics, and telemetry
Autonomous Vehicles (V2X)	5G	Enables instant vehicle-to-infrastructure communication for safety
Traffic Data Sensors	NB-IoT	Long-range, low-power connectivity for environmental monitoring
Smart Parking Systems	NB-IoT	Reliable, low-cost, battery-efficient communication for static sensors

Real-Word Deployment: Use case in The Netherlands

The Netherlands has emerged as a global leader in smart transportation, particularly through national projects like Talking Traffic and ParkShuttle. These initiatives leverage 5G and IoT to facilitate real-time traffic management and support autonomous public transit systems. Talking Traffic enables connected vehicles and infrastructure to communicate in real-time, optimizing traffic signals and improving flow. ParkShuttle operates as an autonomous shuttle service, showcasing the potential of high-speed, low-latency 5G networks in ensuring safe and responsive autonomous vehicle operation. These projects demonstrate how modern communication technologies are revolutionizing urban mobility across Dutch cities [126].

3.4.3. Environmental Monitoring

When designing an environmental monitoring network, selecting the right communication protocol is critical. The ideal choice depends on factors like power consumption, range, data transmission needs, and deployment constraints. Given that most environmental monitoring sensors are deployed in remote or urban settings with limited power sources, reliable, energy-efficient, and long-range wireless protocols such as LoRaWAN, NB-IoT, and Sigfox would be the most viable options.

LoRaWAN is a widely used LPWAN protocol that operates in the unlicensed spectrum, making it cost-effective for large-scale environmental monitoring. It has been widely tested for city-scale deployments due to its low power consumption and long-range capabilities.

A key advantage of LoRaWAN over cellular-based solutions like NB-IoT is that anyone can deploy their own LoRaWAN gateway, whereas NB-IoT requires reliance on telecom operators [128]. However, LoRaWAN is limited in its data rate, making it less suitable for high-frequency data transmission needs [113].

Unlike LoRaWAN, NB-IoT operates in a licensed spectrum and is managed by cellular operators, providing a more structured and controlled network environment. Studies show that NB-IoT has higher data rates than LoRaWAN, making it more suitable for applications requiring continuous data streaming, such as high-resolution air pollution monitoring [129]. However, NB-IoT depends on existing telecom infrastructure, meaning that its availability varies by region, and it requires a data plan, making it potentially costly over time compared to LoRaWAN's private network model [130].

An additional benefit of NB-IoT is its strong penetration in buildings and underground environments, making it a strong candidate for subterranean environmental monitoring [113]. This is particularly useful for monitoring water quality in underground reservoirs or soil moisture levels.

Sigfox is another LPWAN protocol that prioritizes ultra-low power consumption, making it an excellent choice for long-term environmental monitoring where sensors need to last for years. Operating on the unlicensed spectrum, it enables cost-efficient, large-scale deployments for environmental monitoring applications. Sigfox networks can transmit data over long distances (up to 40 km in rural areas) but with strict limitations on message size and frequency [128] [130].

In a comparative analysis, Sigfox provided the longest battery life, but NB-IoT and LoRaWAN offered greater flexibility in network deployment [131]. For applications like forest fire detection, where sensors need to send only occasional, critical alerts, Sigfox would be a good option. However, for dynamic air quality monitoring, LoRaWAN or NB-IoT would be better suited due to their higher transmission frequency.

In indoor environmental monitoring applications, such as air quality monitoring, temperature, and humidity in schools, offices, hospitals, and residential complexes, Wi-Fi is a particularly effective communication protocol due to its bandwidth, and ease of integration. Most modern buildings are already equipped with Wi-Fi infrastructure, allowing for seamless deployment of IoT-based monitoring systems without the need for additional gateways or base stations [132]. This makes Wi-Fi highly suitable for transmitting large volumes of sensor data at high frequency, supporting real-time analytics and timely responses to environmental changes (e.g., ventilation adjustments or alerts for high CO_2 levels) [133] [134]. Moreover, Wi-Fi-enabled sensors can directly connect to cloud platforms for remote access and centralized management, which is especially advantageous in smart city environments where data interoperability and accessibility are key concerns [135].

Zigbee, on the other hand, offers a compelling alternative for power-sensitive indoor applications. It operates on the IEEE 802.15.4 standard, enabling mesh networking capabilities that are particularly useful in complex building environments where obstacles and interference can impact connectivity [134]. Although Wi-Fi consumes more power compared to protocols like Zigbee or LoRaWAN, this limitation is less critical in indoor deployments where sensors usually have access to mains electricity or can be combined with energy-efficient architectures and power-saving modes [136]. In scenarios requiring greater power efficiency or deployment in locations without stable power sources, Zigbee may be used as a complementary solution [113]. However, Wi-Fi's high data rate, stable performance in indoor environments, and widespread adoption across consumer and enterprise networks make it the dominant protocol for indoor environmental monitoring in smart cities, especially where real-time, data-intensive applications are prioritized [134] [135].

Table 7: Optimized communication protocols for various environmental monitoring applications

Primary Use Cases	Best Protocols	Why?

Air Quality Monitoring (Urban settings)	LoRaWAN	Low power, good urban coverage, scalable for city-wide deployment
Water Quality Monitoring (Underground or remote areas)	NB-IoT	Excellent penetration in underground environments, reliable in remote areas
Forest Fire Detection	Sigfox	Ultra-low power, long battery life, suitable for low-data alerts
Soil Moisture Monitoring (Agriculture)	LoRaWAN	Allows private network deployment, long-range
Noise & Pollution Monitoring (Smart cities)	NB-IoT	Higher data rates, real-time monitoring capability
Indoor Environmental Monitoring	Wi-Fi, Zigbee	WI-Fi for high data rate, real-time data transmission, easy integration with existing networks, Zigbee for greater power efficiency

Real-Word Deployment: Use case in in Southampton

In Southampton, UK, long-term deployment of a LoRaWAN-based wireless sensor network has enabled advanced environmental monitoring, particularly for air quality. This system, integrated across the city, collects real-time data on pollutants and transmits it using the LoRaWAN protocol — known for its low power consumption and long-range capabilities. Over 135,000 air quality messages were reliably transmitted during the pilot, highlighting LoRaWAN's effectiveness in urban sensing applications. The data informs public services and environmental planning, contributing to smarter and healthier urban living [128].

3.4.4. Public Safety

Ensuring reliable, robust, and efficient communication is paramount for public safety networks, especially in emergency scenarios where latency, coverage, and prioritization are critical. The selection of Wi-Fi, LTE, and 5G depends on the operational needs, ranging from localized incident response to nationwide emergency coordination.

Wi-Fi plays a crucial role in short-range, high-bandwidth applications, particularly in urban crisis zones, temporary command centers, and smart surveillance deployments. Wi-Fi mesh networks offer a quick-to-deploy, cost-effective solution for post-disaster communication when cellular networks are down [137]. Additionally, smart surveillance systems utilizing Wi-Fi-enabled sensors and IoT devices enhance real-time situational awareness. These systems leverage advanced compression techniques like HEVC for low-bandwidth, high-quality video streaming, ensuring efficient use of wireless networks for emergency monitoring [138].

A key strength of public Wi-Fi in emergency response is its ability to bridge the digital divide and provide low-cost connectivity in disaster-stricken areas where cellular services may be unavailable

[135]. However, Wi-Fi is limited by range, congestion, and lack of seamless mobility, making it less suitable for large-scale emergency operations compared to LTE or 5G.

LTE serves as the primary communication backbone for first responders, as evidenced by its deployment in networks like FirstNet (USA) and ESN (UK) [139]. LTE provides wide-area coverage, prioritized communication, and seamless mobility, ensuring mission-critical push-to-talk (MCPTT) and Proximity Services (ProSe) for direct device-to-device (D2D) communication in scenarios where cell towers are damaged or unavailable [140].

LTE's resilience in emergencies is enhanced through deployable LTE bubbles, which enable first responders to create independent, localized networks in disaster zones [141]. Furthermore, LTE supports real-time data exchange between different emergency agencies, solving interoperability issues that have historically hindered disaster response coordination [137].

5G revolutionizes public safety communications by introducing ultra-reliable low-latency communication (URLLC), network slicing, and edge computing, making it ideal for real-time emergency response applications [142].

Ethernet plays a supportive role in smart public street lighting systems, enabling reliable data transmission between smart poles and central control units, particularly in static infrastructure scenarios [42]. This makes it suitable for smart surveillance and public safety applications requiring high-bandwidth, low-latency connections.

Network slicing allows emergency services to receive guaranteed bandwidth, ensuring that public networks remain operational for critical communications during disasters [140].

One of the most significant 5G advancements for public safety is Edge Computing, which allows real-time data processing at the network edge. This is particularly useful for applications like AI-driven disaster response, autonomous search-and-rescue drones, and high-definition video surveillance [116]. Additionally, 5G-enabled IoT networks improve emergency response times by leveraging real-time environmental monitoring for early warning systems in fires, floods, and seismic activities [143].

Table 8: Optimized communication protocols for various energy management applications

Primary Use Cases	Best Protocols	Why?
Smart Surveillance & Threat Detection	5G + LTE, with edge computing, Ethernet	5G: ultra-low latency for real-time video analytics, AI-driven anomaly detection & drone surveillance. LTE for fallback connectivity, Ethernet for static infrastructure scenarios
Smart Traffic Management for Emergency Vehicles	5G V2X + LTE	5G Vehicle-to-Everything (V2X) optimizes emergency response routes. LTE for vehicle tracking and real-time coordination.

Urban Crisis Management (e.g. riots, large events) & Crowd Control	Wi-Fi Mesh + LTE	Wi-Fi Mesh enhances connectivity in congested areas, while LTE ensures stable communication for public safety teams.
Disaster Recovery & Crisis Coordination (Floods, Fires, Earthquakes)	LTE (Deployable Bubbles) + 5G	Portable LTE networks extend coverage where infrastructure is unavailable, while 5G enhances coordination and data sharing for first responders.

Real-Word Deployment: Use case in Lahore

In Lahore, Pakistan, public safety has been significantly enhanced through the deployment of LTE-enabled systems within its police field forces, namely the Dolphin Squad and PRU. These units are supported by IoT-based surveillance, LTE-enabled mobile devices, and a fog computing architecture that processes data close to the source. This infrastructure enables real-time video streaming, GPS tracking, and instant incident alerts, allowing law enforcement to respond proactively and efficiently. The integration of LTE and IoT ensures low latency and secure communication for real-time situational awareness and operational coordination [40].

Table 9: Mapping smart city use cases to their suitable communication protocols

	Energy Management	**Mobility & Transport**	**Environmental Monitoring**	**Public Safety**
Ethernet	✓			✓
Modbus	✓			
LoRaWAN	✓*	✓*	✓	
Sigfox			✓**	
LTE/5G	✓	✓		✓
NB-IoT	✓	✓*	✓	
Wi-Fi	✓		✓****	✓
Zigbee	✓		✓****	
Bluetooth	✓***			

✓*= Suitable for low-data, non-critical telemetry only.
✓**=Only suitable for rare-event monitoring (e.g., forest fire alerts), not continuous monitoring.
✓***=Limited to short-range applications (e.g., device-level communication within buildings).
✓****= Suitable for indoor environmental monitoring.

3.5. Sensor Network Testing and Validation Strategy

The testing and validation of sensor networks in smart city environments are critical to ensuring that deployed systems can deliver reliable, secure, and high-quality data across varied conditions and use cases. As sensor infrastructures expand in scope and complexity, validation is essential for guaranteeing network connectivity, protocol interoperability, performance stability, and compliance with functional requirements. A robust testing framework allows for early detection of system failures, inefficient data handling, and compatibility issues across heterogeneous technologies — all of which are key risks in large-scale, multi-vendor deployments typical of smart cities [144] [145]. Successful testing and validation, in this context, means verifying that smart city sensor networks maintain data integrity, meet specific requirements for latency, frequency, and energy efficiency, and remain resilient under peak demand [146]. It also enables seamless integration of new sensors over time, without compromising service quality or security.

This chapter builds on the technical and architectural discussions outlined in the preceding sections of this document. Having defined the requirements and design principles for sensor network consolidation in Sections 3.2 to 3.4, the focus now shifts to how these systems are tested, validated, and monitored. A robust testing strategy ensures that the network meets performance targets while aligning with the goals of replicability and operational effectiveness in smart city contexts.

3.5.1. Testing Objectives and Scope

Key Objectives

The testing and validation strategy presented below is structured around five primary objectives, each aligned with the operational goals of the project:

- Verify reliable connectivity under normal and degraded conditions across both wired and wireless segments of the network.
- Ensure interoperability between devices, sensors, and communication protocols — including Modbus, BACnet, Ethernet, LoRaWAN, Zigbee, Bluetooth, LTE, and 5G — used within and across deployments [147].
- Validate system performance under both average and peak data loads, with attention to throughput, jitter, packet loss, and synchronization delays [148].
- Confirm end-to-end compliance with predefined functional requirements (e.g., data acquisition rates, redundancy strategies, and power consumption metrics). Use-case-aligned validation applies here — for instance, low-latency for mobility; high-frequency for environmental monitoring (see Section 3.1 for use-case detail).
- Ensure data integrity, especially for use cases involving real-time decision-making, such as traffic routing or emergency response systems.

Scope

The scope includes both wired and wireless network infrastructures. Sensor-placement validation methods are applied, considering urban complexity to optimize data collection [149]. Testing is scenario-driven, with metrics evaluated per use case to ensure contextual relevance — for instance, packet delay variation is more critical in public safety applications than in static environmental monitoring.

3.5.2. Key Testing Areas

Connectivity Testing

Connectivity testing is crucial to ensure that smart city sensor networks consistently maintain stable and uninterrupted communication under a wide range of real-world conditions. Reliable connectivity helps prevent unexpected disconnections and ensures continuous network uptime, enabling smooth and timely data exchange—essential for real-time services such as mobility management, emergency response, and public safety.

- Metrics: Latency, packet loss, throughput, jitter.
- Approach: Connectivity testing employs both realistic simulations and field validations. Simulation tools such as NS-3 and OMNeT++ facilitate detailed modeling, allowing pre-deployment evaluations of network stability and scalability [150]. Subsequently, real-world tests verify the network's actual performance, confirming physical connectivity, gateway configurations, and wireless signal strength. Environmental factors — such as vegetation density, seasonal weather fluctuations, and physical obstacles — are evaluated, as they significantly affect wireless sensor network performance in urban deployments.
- Testing includes:
  - Wireless signal coverage mapping, using field-based RSSI and SNR measurements to ensure effective propagation and minimal dead zones, especially for LoRaWAN, Zigbee, and NB-IoT [151]. This is particularly relevant for environmental monitoring and energy management, where long-range communication is critical.
  - Wired infrastructure verification, including router configuration, gateway health, and port-level diagnostics [148].
  - Latency and jitter evaluations are prioritized for mobility and public safety scenarios, where real-time responsiveness is critical [145].

Interoperability Testing

Interoperability testing is crucial for ensuring seamless and reliable communication among diverse sensors, devices, and protocols within a smart city sensor network. Given the heterogeneous nature of urban IoT deployments, the ability for different technologies to effectively exchange data is fundamental to achieving scalability and supporting future network expansions.

- Focus: Interoperability testing verifies that diverse sensor types, data protocols, and communication layers can function together within the same infrastructure. Given the range of protocols adopted across smart cities, this is a critical task [147].
- Method: The validation process includes:
  - Protocol interoperability testing, ensuring devices using different communication stacks can share and interpret data coherently [146].
  - Data format harmonization, particularly through middleware that converts or normalizes payloads across platforms. Ensuring semantic consistency is key for data integration and

analytics [149]. This is especially critical in public safety, where data from disparate sources must be aggregated in real-time.
  - Vendor-neutral integration tests, focused on plug-and-play compatibility, especially in deployments with sensors from multiple manufacturers [144].
  - Advanced model-based testing approaches, including formal verification techniques and modular scenario testing, evaluate integration logic [144] [145].

Performance Testing

Performance testing is essential to verify that smart city sensor networks operate reliably and efficiently, even under challenging operational conditions such as high data loads and unexpected peak demands. By proactively evaluating critical metrics, such as latency, synchronization and energy consumption, cities can confidently deploy sensor networks that remain stable, responsive, and resilient under real-world pressures and future growth.

- Key Areas: This phase evaluates the network's behavior under varying operational conditions, including stress and peak loads. Performance is assessed across the four aforementioned use cases:
  - Environmental monitoring: Validating high-frequency data acquisition and energy efficiency.
  - Mobility and traffic: Ensuring synchronization and low-latency delivery.
  - Energy management: Assessing sustained throughput and long-range communication.
  - Public safety: Validating robustness, fast alerting, and minimal jitter.
- Tools and Methods: Performance testing utilizes a range of tools and simulation platforms:
  - OMNeT++ and NS-3 for modeling traffic loads, synchronization, and topology behavior [147].
  - Battery performance diagnostics for energy-sensitive nodes [149]. Battery drain simulations under various duty cycles are used to determine realistic lifespans, particularly in environmental and energy monitoring LPWAN deployments.
  - Stress testing using synthetic loads to emulate high-traffic scenarios, especially for star, mesh, and hybrid network topologies [151].
  - Edge computing simulations to verify latency impacts under partial processing scenarios are particularly relevant for mobility and public safety systems [146].

Assessment of Data Integrity in Connectivity Testing

Data integrity assessment during connectivity testing is crucial, especially for smart city scenarios involving real-time decision-making such as mobility management, emergency response, and critical infrastructure monitoring. Ensuring the accuracy and reliability of data transmitted across the network is fundamental for effective urban management and citizen safety.

- Metrics: Bit error rate (BER), packet integrity, payload consistency, checksum accuracy.
- Testing includes:
  - Simulation-based data integrity tests may be performed using platforms such as OMNeT++ and NS-3 to evaluate network performance under controlled scenarios. Simulations explicitly model scenarios including packet errors, interference, signal degradation, and congestion to measure their impact on payload accuracy and bit error rates [147] [150].
  - Field validation of payload integrity, complementing simulations through real-world tests conducted in actual urban environments. These tests verify end-to-end data integrity by measuring checksum accuracy, detecting malformed packets, and identifying corrupted

messages caused by environmental factors such as interference, structural obstructions, or network congestion [142] [144].
- Automated IoT testing frameworks, such as testRigor, providing targeted testing methodologies may be used to validate data transmission accuracy and security. Automated testing tools may identify data anomalies, payload corruption, and transmission vulnerabilities at early stages, significantly reducing deployment risks and ensuring reliable data delivery is essential for critical real-time applications [151].
- Middleware-based automated monitoring and logging, integrating middleware platforms may be used in order to continuously verify payload consistency, flag anomalies immediately upon detection, and facilitate real-time data integrity diagnostics [141].

3.5.3. Validation

Environmental Validation

Field and simulation testing account for real-world environmental factors (humidity, temperature, interference, seasonality), as these significantly affect signal strength, reliability, and energy usage. Security features (e.g., encryption, authentication) must also be tested for their impact on latency and energy consumption, especially in real-time and low-power applications, such as public safety and environmental monitoring [150].

Sensor deployments must consider the IP (Ingress Protection) ratings of sensors to ensure adequate protection against harsh environmental conditions such as dust, moisture, and temperature extremes. High IP-rated enclosures are particularly important for sensors deployed in outdoor environments, where weather exposure is continuous and unpredictable [151].

For example, in scenarios using solar-powered sensors, ensuring sufficient sunlight exposure throughout the year is critical. Validation methods should include sunlight availability analysis, proper panel orientation, and local seasonal patterns to guarantee consistent power harvesting. As demonstrated in LoRa-based environmental monitoring use cases, insufficient solar planning can lead to frequent energy shortages and sensor downtime [151].

Wireless communication interference due to physical obstacles (e.g. buildings, foliage, and terrain) must also be carefully evaluated. While technologies like LoRaWAN offer long-range communication in open areas, their effective range decreases substantially in dense urban environments. Field measurements and simulation-based modeling using tools like NS-3 or OMNeT++ are required to optimize sensor placement and ensure signal stability across varying topographies [151]. In addition to simulations, online platforms such as TTN Mapper can be used to visualize actual LoRaWAN signal coverage based on crowdsourced data collected from real-world transmissions. The tool allows users to assess signal strength, gateway reachability, and propagation patterns over time, helping to identify coverage gaps, validate theoretical models, and adjust gateway placement accordingly during planning and early deployment phases.

Environmental testing should also account for sensor aging and material degradation, especially in long-term outdoor deployments. Exposure to sun, wind, pollutants, and humidity over time can degrade sensor accuracy and housing durability. Pre-deployment endurance or accelerated aging tests are important to anticipate maintenance needs and ensure data quality over the network's lifecycle [142].

Finally, microclimate conditions within cities, including urban heat islands, shaded zones, or wind corridors, can affect sensor performance, particularly for those measuring environmental variables like

temperature, air quality, or solar energy intake. Validating network behavior across these variable micro-environments helps ensure consistency and accuracy across the entire deployment area [152].

Figure 18: Locations of LoRAWaN gateways in Piraeus region, Greece

Validation Against Requirements

Methodology: Explicit mapping between predefined network requirements and associated test cases is conducted to ensure clear, traceable validation. Each requirement — such as maximum latency thresholds for mobility applications or data acquisition frequency for environmental monitoring — is associated with clearly defined acceptance criteria.

Documentation: Test outcomes are comprehensively documented to link results explicitly to corresponding project requirements. This enhances traceability, and accountability, and supports the replicability of ExPEDite's sensor network deployment strategies across other urban contexts [149].

Tools and Methodologies

Key tools include:

- Network Analyzers (e.g., Wireshark, NetAlly) for packet inspection, loss detection, malformed message identification, and real-time bottleneck diagnosis.
- Simulation Software (e.g., NS-3, OMNeT++, MATLAB/Simulink) to model network performance under varying topologies and conditions, including physical and MAC layer behavior [147].
- Formal Verification Frameworks (e.g., SNOOPS), integrating emulation (QEMU) and logic modeling (SystemC, Light Esterel) to validate wireless sensor protocol properties during runtime [147] [148].
- Middleware Solutions (e.g., FIWARE, ThingsBoard) for integration testing, protocol translation (e.g., Modbus to MQTT), and real-time monitoring dashboards [152].

Test Environment

To ensure realism and replicability, testing is performed across:

- Controlled lab environments, where stress, load, and failure scenarios can be generated and monitored. These actions help fine-tune configurations, protocol settings, and error thresholds before deployment.
- Field deployments, such as living labs or smart campus prototypes, evaluate real-world variables — interference, terrain, signal obstruction, mobility, and energy constraints [153] [145].
- Hybrid validation, combining emulated network segments and live sensor deployments, enables comprehensive testing without requiring full urban-scale infrastructure [145] [148].

3.5.4. Risk Management and Troubleshooting

While sensor networks are designed to be robust, several risks can undermine operation or compromise data integrity. A proactive risk management strategy ensures stability, safety, and continuity. In this section, we analyse some of the main identified risks & relevant mitigation strategies:

- **Network Interference**: RF congestion in dense urban environments can degrade wireless performance, particularly for Zigbee, Wi-Fi, and LoRaWAN, which operate in unlicensed bands and are susceptible to overlapping frequencies and electromagnetic noise [144].

  Mitigation strategy:
  - Interference Management and Frequency Adaptation. Signal Remapping and Channel Allocation: Urban RF environments often experience heavy congestion due to the growing number of devices operating in unlicensed frequency bands. Dynamic channel switching and remapping protocols reduce the risk of signal collisions and cross-interference, especially for technologies like Zigbee and LoRaWAN operating at 2.4 GHz and 868 MHz respectively. Frequency agility, informed by real-time or scheduled spectrum scanning, helps maintain communication stability in environments where signal conditions change frequently due to temporary interference sources or shifting traffic patterns [144].

- **Connectivity Failures:** Sensor communication can be disrupted by gateway misconfiguration, firmware crashes, or localized power outages. These issues directly impact the delivery and timeliness of critical sensor data.

  Mitigation strategies:
  - Redundancy Mechanisms: To prevent communication breakdowns caused by isolated failures, the use of multi-hop routing, mirrored gateways, or fallback paths allows data to be rerouted through alternative routes in the event of a disruption. This is particularly important in critical applications where continuous data flow is essential. Strategic placement of redundant nodes or gateways ensures that the network remains operational even when one or more elements become unavailable, thereby improving service continuity and system uptime.
  - Synchronization Recovery Scripts: Desynchronization between nodes—caused by network jitter, latency, or temporary disconnections—can disrupt coordination and timing, particularly in time-sensitive applications. Automated reinitialization scripts help restore alignment quickly without requiring manual intervention or full system resets. These routines are triggered by anomaly detection mechanisms or periodic time-checks, enabling

seamless re-synchronization across nodes and preserving temporal accuracy across the network.

- **Environmental Variability:** Seasonal shifts (e.g., leaf coverage, snow), temperature fluctuations, and even urban development (e.g., new structures) can degrade wireless signal quality or increase power consumption in affected nodes. These environmental factors are among the most difficult to predict and must be tested under real-world conditions [151].

  Mitigation Strategies:
  - Testing Under Fault Conditions: Pre-deployment testing includes controlled simulation of realistic fault scenarios—such as abrupt node failures, signal interference, or partial network outages—to evaluate how the system responds under stress. These tests validate the network's ability to degrade gracefully, recover efficiently, and maintain baseline functionality when unexpected events occur. This ensures that real-world resilience isn't assumed, but actively verified under structured and repeatable conditions [143].
  - Site-Specific Environmental Testing: Urban deployments are rarely uniform; variables like building density, terrain elevation, and localized climate conditions can drastically impact network performance. On-site environmental testing captures these factors through empirical signal strength measurements and scenario-specific evaluations. Testing under different seasonal conditions (e.g., foliage changes, snow accumulation) ensures that the system is robust year-round. Early validation in such contexts prevents signal loss, performance drops, or system instability due to overlooked environmental interactions [152].

- **Power Depletion:** Battery-operated sensors may fail due to excessive data transmission, prolonged synchronization routines, or insufficient harvesting from solar panels. This is especially relevant in LPWAN deployments and in locations where environmental constraints limit power regeneration.

  Mitigation strategies:
  - Edge Logging and Local Analytics: During outages or gateway disconnections, sensor nodes equipped with onboard storage and lightweight processing continue collecting and analyzing data locally. Once connectivity is restored, buffered data is synchronized with the central system to preserve historical continuity. This not only prevents data loss, but also enables critical event detection to occur independently of the cloud, ensuring operational continuity in offline or semi-connected conditions.
  - Adaptive Duty Cycling and Low-Power Design: Energy-efficient network operation is achieved by adjusting sensing frequency, transmission intervals, and communication patterns based on current needs. For battery-powered or solar-reliant nodes, duty cycling helps reduce energy waste during low-activity periods while ensuring responsiveness during critical events. These optimizations are especially important for long-term deployments where maintenance access is limited, as they extend battery lifespan and reduce the likelihood of sudden node failure due to energy exhaustion [144].

Documentation and Reporting: Standardized templates are used to record procedures, results, anomalies, and corrective actions throughout all testing phases. This systematic documentation enhances transparency and supports the replication of validation workflows across other districts or projects.

The testing and validation strategy presented in this chapter ensures that consolidated smart city sensor networks meet technical and operational goals across a variety of deployment contexts. By validating connectivity, interoperability, performance, and functional requirements — while accounting for

environmental variability and security trade-offs — the strategy supports both immediate operational readiness and long-term scalability. These guidelines form a foundation for building sensor infrastructures that are technically robust, adaptable, resilient, and aligned with the broader ambitions of replicability and sustainability within the ExPEDite project.

3.6. The ExPEDite Sensors

In this section, we analyze the installation of a variety of sensors across the RTU campus that have been implemented to support the ExPEDite project. These sensors are grouped by function, with the following sections outlining their purpose, setup, and data utilization.

3.6.1. Energy management sensors

The RTU campus metering and buildings BMS update project includes the installation of thermal energy consumption meters for all pilot buildings.

- Measurements are taken at the building level.
- The planned measurement interval is 30 min, but the optimal measurement rate for thermal energy must still be determined based on models and digital twins.

Electrical energy consumption meters for all pilot buildings are included in RTU campus metering and building BMS update projects realized by RTU. Access will be provided to acquired data for ExPEDite project needs. Measurements are taken on the building level.

- The planned measurement rate is 15 min, but the best electrical energy measurement rate must be determined according to models and digital twins.

Additionally,

- Real-time electrical energy management sensors have been installed to monitor electrical energy (or power) consumption at each circuit breaker load in one building used for administrative, educational, and research activities.
- Real-time electrical energy management sensors have been installed to monitor the electrical energy (or power) consumption of each HVAC drive, 12 units in total. Because these sensors have been operational for more than two years, it would be possible to compare electrical energy consumption before and after the BMS system upgrade. Real-time electrical energy management sensors will be installed in one dormitory building to monitor electrical energy (or power) consumption per room and to assess students' living habits. The design of these sensors will be similar to those described above. Such installation will help to implement LivingLab activities.
- Real-time electrical energy management sensors have been installed to monitor the electrical energy (or power) consumption of three EV charging stations near the pilot building.
- All energy consumption meters and sensors are connected to the project's central database via the ICT infrastructure.

- The sensors utilize wi-fi for data transmission, following smart building best practices aligned with the project's use cases.

Real-time electrical energy management sensors

All real-time electrical power/energy management sensors were originally developed between 2019 and 2021 and have since been adapted to meet specific project requirements. A general overview is provided here.

The real-time electrical energy management sensors, installed per circuit breaker, are described below. These earlier in-house designs consist of several parts.

Current sensing clamp (Figure 19): non-invasive, electrically isolated, including two Hall-effect based magnetic field sensors positioned in opposite directions to minimize stray magnetic fields and differential operation amplifier with voltage level shit for micro-controller analog-to-digital converter (ADC) input midpoint (like AC "zero") setting;



Figure 19: Current sensing clamp

The parameter sensing micro-controller board (Figure 20) is based on IMXRT1062DVL6 Cortex-M7 32bit, floating point chip, running at 600 MHz clock speed. Here, the board provides:

- Six ADC inputs, reading type (RMS current, active power, or active energy).
- Data readings setting inputs (energy or power).
- Synchronization input.
- 3-phase AC voltage inputs, converted to low-level signal.
- UART (Universal Asynchronous Receiver-Transmitter) output with data output baud rate 115200 Hz.
- UART connection IC (integrated "logical OR" circuit) to overall output to avoid interference from other boards' UART outputs.



Figure 20: Parameter sensing micro-controller board

ADC readings are set to 10-bit resolution (reading precision better than 0.1%). Such a resolution is good for "outside of laboratory" readings[1].

Readings are acquired per 0.2-second blocks, practically simultaneously - taking into account micro-controller clock speed and optimized code. One 0.2-second block is 10 periods for 50 Hz mains frequency (IEC 61000-4-30 standard).

ADC sample rate is set to 2000 Hz or 40 samples per 50 Hz mains period. The 2000 Hz sampling rate allows us to achieve information about AC signals up to the 18th harmonic for non-sinusoidal voltage or current waveforms, which are widely observed today.

For each particular voltage and current reading, instant power value is calculated based on these readings. The instant power method is widely accepted today due to non-sinusoidal voltage and current waveforms in AC mains grids. Before the power value calculation, the voltage phase is detected to avoid miscalculation - not the same phase for voltage and current. Also, the current value is corrected to prevent/linearize the influence of the air gap in the current sensor magnetic circuit.

The mentioned 0.2-second blocks are combined over 3,5,10, 30, 60, or 300 seconds. Each block also gives information about maximum and minimum values over 0.2 seconds. On a larger scale, such an approach allows us to determine energy/power consumption swing as well as give valuable information for overall district real-time energy balancing, if necessary.

---

[1] See also https://www.fluke.com/en-us/learn/blog/power-quality/practical-applications-for-single-phase-voltage-recording

Data output contains only electrical energy data if not set for power data or RMS current values. This is done to avoid high communication traffic volumes and data storage volumes. Sensor calibration uses a precise power source, MTE PCS400.3 (Figure 21).

Figure 21: Precision power source for sensor calibration

Current clamps are calibrated at 230 V, 2 A sinusoidal waveform, considering that pilot building planned loads are below 1000 W. For higher loads, alternative types of real-time power sensors are used. The current clamps have a sensing range of 0.1-8 A, corresponding to about 20-1800 W of active power/energy load. Precision varies from clamp to clamp due to slightly different installations caused by the type of the circuit brake, connected wire diameter, and the influence of outside fields. In worst-case scenarios, the measurement accuracy remains better than ± 5%.



Figure 22: Communication micro-controller board left - PCB top, right - PCB bottom

The communication micro-controller board (Figure 22) is based on IMXRT1062DVJ6 Cortex-M7 32bit, floating point chip, running at 720 MHz clock speed. Board provides:

- Five UART inputs to collect data from up to five energy-sensing rows.
- Mains voltage sensing through isolating amplifier.

- Web-server to provide secure (SSL) data transmission to MQTT (Message Queues Telemetry Transport) broker.
- System power supply.
- Parameter sensing clock - 3, 5, 10, etc. seconds.
- Including-excluding individual current clamps from the data row.
- Received by UART CSV (coma separated values) conversion to JSON (JavaScript Object Notation in the form of name-value pairs) format to send to MQTT broker.

The overall image of the components mentioned above is shown in Figure 23.



Figure 23: Sensor system

For the project purposes, an additional board is added to perform data accumulation to the backup server utilizing a UART-to-WiFi converter (Figure 24). Converters include an onboard ST32 microcontroller and WiFi radio transmitter. Such a converter allows storage of data other than the data server, set up in other geographical locations, and, currently, also acts as an application programming interface (API) for sensor system management (Figure 25, for example).

Figure 24: UART-to-WiFi converter module



Figure 25: Sensor system management web API

The UART-to-WiFi converter module will be excluded from the system after the desired tasks are installed on the project's API. Partial sensor installation into the building floor electrical cabinet is shown in Figure 26.



Figure 26: Energy metering sensors installation in electrical cabinet



Figure 27: 3-phase electric energy/power sensing device, non-invasive Hall-effect current sensors NOT shown

Other real-time energy/power measurements are done by earlier-developed energy/power sensing devices (Figure 27). The device includes:

- Three galvanically isolated voltage sensors - isolated amplifiers AMC1100.
- Three Hall effect-based galvanically isolated current sensors HSTS 016L-10A, non-invasive, clamp-on.
- Twilio electric imp Murata imp003 module (imp003 LBWA1ZV1CD).

Figure 28: HVAC consumed power visualization, last two weeks

Initially, module imp003 was employed utilizing IEEE 802.11 b/g/n 2.4 GHz Wireless LAN IC BCM43362 and STM32 ARM Cortex-M4 micro-controller STM32F405 running 32-bit computation at 72 MHz clock frequency. Imp003 module programming and communication were carried out wirelessly via Wi-Fi.



Figure 29: Modified 3-phase electric energy/power sensing device (non-invasive Hall-effect current sensors NOT shown)



Figure 30: Registered waveforms near PV panel in-feed to grid

Accuracy field tests have demonstrated overall accuracy better (below) ± 1,2%.



Figure 31: Registered waveforms harmonics content near PV panel in-feed to grid

At the moment, such energy/power sensors are installed on HVAC devices in the pilot site building, with a total of 12 devices monitored. An example of the collected data is shown in Figure 28 which presents HVAC power consumption over the past two weeks (different visualization options are also available).

More advanced upgrades are being implemented for electrical energy/power sensing at the PV panel inverter feed-in points to the pilot buildings' electric cabinets.

The 72 MHz clock frequency of the imp003 was found to be too low, making it insufficient for for accurate harmonic component calculations of each voltage and current waveform.

To increase the computational power of the power meter, the imp003 module was replaced with an NXP IMXRT1062DVL6 microcontroller, running 32/64 bit at 600 MHz, as part of the Teensy 4.0 development board. Additionally, another Twilio electric imp imp001 module was employed to provide WiFi communication (Figure 29).

The Goertzel algorithm was implemented for harmonic component detection in relative scale, eliminating the need for narrow Fast Fourier Transformation (FFT) bins. Achieving the desired bin centre frequencies using FFT would otherwise be problematic, requiring manipulation of the micro-controller's clock frequency and frequency dividers.

The main drawback of implementing the Goertzel algorithm is the requirement for a low deviation from 50 Hz mains frequency in the grid frequency.

Currently, the system can decode decode non-sinusoidal mains voltage and current waveforms up to 15th harmonic and can also calculate the waveforms and THD.

The results are presented in Figure 30 (voltage, current, and power) and Figure 31 (one-phase harmonic content).

When discussing electrical energy/power today, it is essential to consider not only the well-known active, apparent, or full energy/power in AC grids but also the harmonic content, particularly in the electric current.

According to theory, "net energy is transmitted to the load only when the Fourier series of v(t) and i(t) contain terms at the same frequency", so only harmonics in the current waveform cause cable heating and increase losses without performing useful work.

3.6.2. Environmental monitoring sensors

Environment sensors for humidity, temperature and CO2 (RhT-CO2) are included in the RTU campus metering data update which is being carried out by RTU (Figure 32 and Figure 33). However, access to the collected data will be provided for exPEDite project needs. Installation is planned for May/June 2025. The sensors will transmit data through Wi-Fi.

Additionally, data from the weather station located on the pilot building's rooftop can be utilized to complement the existing local weather data.

Figure 32: RTU Campus, ARANET environmental sensor

Figure 33: RTU Campus, BMS sensor

3.6.3. Traffic Monitoring Sensors

To support traffic monitoring activities, six cameras have been installed on 09.04.2025 on two roads leading from the city to the RTU Campus in Kipsala district. These include:

- 3x AXIS P1465-LE Bullet Cameras (Figure 1).
- 3x AXIS Q1700-LE License Plate Cameras (Figure 2).

Figure 1: The AXIS P1465-LE Bullet Camera.

Figure 2: The AXIS Q1700-LE License Plate Camera.

The exact locations of the cameras are presented in Figure 3 below, while the cameras installed next to Zunda river are shown in Figure 4 below.

Figure 3: The locations of the installed cameras in Kipsala district.

Figure 4: The cameras as installed (location next to Zundis river).

For data communication, an organized process will be implemented to retrieve registered events from the video analytics database. The collected data will be enriched with information from the Latvian vehicle registry (CSDD) by querying their API using vehicle number plates. Once enriched, the data will be packaged according to the Expedite Digital Twin requirements and transmitted accordingly. Initially, this workflow will be semi-manual, as data will be collected and processed over a defined period rather than in real time, in line with the current requirements of the transport model.

The installation procedure followed a structured approach. First, the partners involved in creating the transport model discussed the necessary goals and defined the required transport data. Subsequently, the Riga Digital Agency conducted research to identify the most suitable solution and purchased six cameras under the project's equipment cost line. Coordination with the Riga Municipality Outdoor Mobility Department ensured that the installation of the cameras was compatible with the local infrastructure. After installation, the cameras were integrated into the Riga Unified Video Surveillance System to ensure compliance with GDPR regulations. Following integration, the Riga Digital Agency configured the BriefCam software (https://www.briefcam.com/) solution and brought the installed equipment into operation. The camera stream (raw video) is transmitted via LTE/5G to the Milestone VMS (https://www.milestonesys.com/). The BriefCam software then accesses the streams from Milestone and performs image analytics, with all processing taking place at the server level. Finally, the Riga Digital Agency assumed responsibility for data collection and processing using the BriefCam analytics tool.

4. System Architecture and Technical Specifications

The exPEDite project (Enabling Positive Energy Districts through Digital Twins) is developing a Digital Twin platform for urban energy and mobility planning. This section describes how the platform integrates **real-time sensor data**, advanced **simulation engines**, and user-facing applications to support city planners, citizens, building managers, and other stakeholders in optimizing urban sustainability. Key architectural decisions focus on **interoperability**, using standardized data models and **Minimum Interoperability Mechanisms (MIMs)**, and ensuring robust **security and privacy** measures. The report details each software module, their interactions, and how they collectively meet the project's functional requirements and objectives.

The EXPEDITE Digital Twin Platform is a modular, scalable system enabling evidence-based decision support for Positive Energy Districts. It consolidates heterogeneous sensor networks into a unified data stream, provides design-time tools for scenario configuration, and offers runtime visualization and analytics. By adhering to European smart city standards (such as the MIMs framework and the Living-in.eu reference architecture) and rigorous data governance practices, the EXPEDITE system ensures replicability and compliance with privacy regulations. The following sections delve into the system's purpose, functionalities, architecture (with context and container diagrams), component descriptions, requirement compliance, interoperability mechanisms (MIMs and sensor network guidelines), and security considerations, concluding with overarching insights on the platform's role in sustainable urban innovation.

4.1. Architecture Elicitation Procedure

The development of the ExPEDite system architecture followed a structured and participatory methodology, grounded in the high-level requirements established in Deliverable D2.1 and the overall objectives of the project. The goal of this process was to ensure that the final architecture is not only technically robust and interoperable, but also aligned with the functionalities and deployment needs of the platform's diverse stakeholders, including cities, developers, and end users.

The elicitation process began with a thorough analysis of the high-level requirements and targeted outcomes defined in D2.1, which provided the initial framing for the system's expected capabilities and constraints. This foundation was complemented by the project's overarching goal: to enable interoperable, scalable, and modular digital twin ecosystems that can support Positive Energy Districts (PEDs) across various urban contexts.

To translate these broad requirements into concrete architectural elements, we conducted a series of bilateral meetings with each tool provider and technical partner. These meetings were guided by a structured questionnaire (see sub-section 7.1) designed to capture critical aspects of each tool's:

- Purpose and role in the system
- Functional features and target user profiles
- Data input/output types and interfaces
- Technical dependencies and integration expectations
- Security, scalability, and performance considerations

Each partner was invited to complete this questionnaire, using it as a means to formally describe their tool's technical and operational characteristics. The outcomes of these bilateral discussions were synthesized to extract tool-specific requirements and to begin mapping interactions and data flows among components. This iterative process enabled the identification of both functional and non-functional requirements at the subsystem level (see section 7.2), while maintaining alignment with the overall goals of the architecture.

The collective outputs of these activities were used to create the first draft of the overall system architecture, providing a preliminary view of the layered design, component responsibilities, and high-level technical flows.

This initial system view was further refined during a dedicated co-design session, which brought together representatives from all technical partners and the pilot city. The session focused on validating the architectural assumptions, reviewing integration points, and jointly refining system functionalities based on initial user journeys and deployment scenarios. Specific emphasis was placed on understanding the needs of target user profiles, such as city planners, energy analysts, infrastructure operators, and citizens, and mapping those needs to system functionalities.

This collaborative co-design approach ensured that the resulting architecture is not only technically coherent, but also user-centered, reflecting the practical needs and contributions of all stakeholders. It also served to build a shared understanding of the platform's integration strategy, deployment constraints, and long-term vision.

4.2. System Overview and Purpose

The ExPEDite system architecture has been designed as an open, modular, and interoperable framework tailored to support the development and deployment of Digital Twins for Positive Energy Districts (PEDs). Its primary purpose is to enable seamless integration of various tools, services, and data sources, facilitating effective urban planning, citizen engagement, and infrastructure monitoring.

Critically, the architecture is built upon and fully aligned with the Living-in.EU Reference Architecture, ensuring conformance with European interoperability guidelines and enhancing cross-project compatibility. By grounding the system design in this reference model, the ExPEDite architecture ensures that its components can interoperate not only internally but also with other platforms and tools developed under the wider Living-in.EU initiative and related smart city programs. This deliverable, which documents the architecture of the MIMS system, will be made publicly available, directly contributing to the Horizon Europe mission goal of enabling the replication of digital twins in other districts and cities. By providing practical, reusable architectural guidelines grounded in open standards, existing components, and open-source technologies, the document supports knowledge transfer and technical adoption beyond the scope of the project. Its public nature ensures that cities, developers, and policymakers can access, adapt, and build upon the system blueprint to accelerate their own digital twin implementations, in line with the call's emphasis on sharing models, components, and training resources.

The architecture adopts a layered and service-oriented approach, reflecting the structure promoted by the Living-in.EU MIMs Plus framework. It distinguishes between foundational layers such as data infrastructure and interoperability services, intermediate layers such as analytics and decision support, and upper layers focused on user interaction and city services. Each tool developed by the technical partners is positioned within this layered model according to its functional role and integration scope.

A dedicated figure (see Figure 34) is provided to illustrate the full system architecture. This diagram presents both:

- The **reference architecture layers** derived from the Living-in.EU model, and
- The **individual ExPEDite tools**, mapped to their corresponding architectural layer and showing the key interactions and data flows.



(a) Living-In.eu reference Architecture



(b) EXPEDITE Components aligned with the reference architecture.

Figure 34: EXPEDITE system overview in contrast with the reference architecture

4.2.1. Key Functionalities and Capabilities

The EXPEDITE platform offers a wide range of functionalities and capabilities to address the needs of various users (citizens, city planners, building managers, external stakeholders) and support PED objectives:

- **Real-Time Data Monitoring:** Ingests live data from infrastructure sensors (energy meters, environmental sensors, traffic counters, etc.) and city systems, providing up-to-date dashboards on energy usage, mobility, and environmental conditions. Users can monitor real-time energy consumption and other metrics through intuitive visualizations.

- **Simulation and Scenario Planning:** Enables city planners to configure and run simulations for urban planning scenarios, such as renewable energy integration, traffic flow optimization, building retrofitting, and district heating management. A library of pre-configured scenario templates is provided for common use cases (e.g. evaluating a new solar PV installation or a change in traffic circulation). The system supports **design-time** setup of simulation parameters and **runtime** execution that produces detailed outcomes (energy demand forecasts, mobility network performance, etc.).

- **Decision Support and Optimization:** Incorporates a **District Optimization & Decision Support** engine that processes simulation results and real data to recommend optimal energy transition pathways to the district level policy-makers. It can evaluate different strategies and provide insights like cost-benefit analyses and KPI impacts, aiding evidence-based decision-making.

- **Data Analytics and Visualization:** Provides advanced analytics capabilities including predictive modeling, trend analysis, and anomaly detection. An **AI Data-Driven Analytics & Visualization** module generates interactive visualizations (heatmaps, charts, 3D urban models) of both real-time data and simulation outputs. The platform can produce automated reports summarizing key findings (e.g., forecasted energy savings or emission reductions).

- **User Engagement and Collaboration:** Features a **Mobile App** for citizens to engage with the platform. Citizens can view district energy performance, receive notifications or "missions" related to community energy challenges, and provide feedback or ideas through integrated forums. The platform supports community management features (user groups, quizzes, goal-setting) to encourage public participation in PED initiatives. City planners and building managers access the system through web interfaces (DT Design Time and DT Runtime) with secure Single Sign-On, ensuring a seamless experience across tools.

- **Interoperability and Integration:** The system is built to integrate with external data sources and legacy systems. For example, it connects to an **Energy Data Space** for sharing data with external stakeholders and retrieving open datasets. It also integrates with existing Building Management Systems via a dedicated **BMS Integration Component** to pull building-level data. Standardized APIs and data models ensure that heterogeneous sources (e.g., different sensor platforms, external databases) can interoperate within the digital twin.

- **Security and Privacy Preservation:** Employs robust authentication (via **Keycloak** for Single Sign-On and OAuth2 tokens) to secure user access across all interfaces. The platform enforces data access controls and anonymizes sensitive data streams (e.g., personal data from sensors) to comply with GDPR and protect privacy. These aspects are covered in detail in the Security section.

Together, these capabilities allow the EXPEDITE platform to function as a holistic tool for **smart city digital twins**, supporting everything from technical simulations to citizen engagement, while maintaining interoperability and security standards.

4.3. Detailed Description of Components and Modules

This section provides a detailed breakdown of the EXPEDITE system's components and modules, organized into subcategories: the major software systems, sensor integration mechanisms, data processing/analytics modules, and the roles of users interacting with the system.

4.3.1. Software Systems and Major Modules

The EXPEDITE architecture consists of several **software systems**, each responsible for a specific set of functions, working in concert within the platform:

- **EXPEDITE Digital Twin Platform:** The central software system that hosts the digital twin functionalities – simulations, optimizations, and visualizations. It acts as the integration hub, receiving data from external sources and user inputs. The platform provides secure data exchange with external data spaces and ingests live sensor data, supporting both **design-time** (setup of simulations) and **runtime** (real-time monitoring) features. Internally, it is composed of multiple containers (sub-modules) which are detailed below (DT Runtime, DT Design Time, analytics engines, simulation engines, etc.).

- **DT Design Time:** The **design-time module** of the digital twin platform, which offers a GUI for configuring simulations and planning scenarios. City planners use this component to set up simulation parameters (e.g., selecting a scenario template, adjusting variables like energy prices or traffic volume) and to initiate simulation runs. It authenticates via SSO (Keycloak) to secure the session, sends simulation requests to the message broker (Kafka), and later retrieves results from storage. DT Design Time ensures that users can **save and reuse** configurations (addressing requirements like FR-DTD-01 on simulation setup persistence) and provides visual previews of input data (fulfilling FR-DTD-03 on visualization of inputs).

- **DT Runtime:** The **runtime module** for interacting with the live digital twin, focusing on visualization of simulation outcomes and real-time data in an immersive or dashboard environment. This is where users (e.g., building managers or city planners) can monitor simulations as they run, view streaming sensor data, and see decision support outputs in real time. Like the design module, DT Runtime uses Keycloak for SSO to ensure only authorized users access sensitive city data. It provides features such as live dashboards, 3D visualizations of the city, and the ability to explore different time-steps of simulation results. It's also optimized for performance to handle real-time updates with low latency, ensuring a smooth user experience.

- **Mobile App:** A native mobile application (Android/iOS) that serves the **citizen interface** to the platform. The mobile app allows citizens and community members to access select platform features on the go: viewing localized energy consumption data, participating in community challenges or surveys, receiving notifications about city programs, etc. It uses **Keycloak** for user authentication, implementing Single Sign-On and OAuth2 token flows for security. Through the app, citizens can visualize data from the city's digital twin that is relevant to them (e.g., how their district's energy usage compares to others), and contribute feedback or ideas to planners. The Mobile App emphasizes usability and security, including support for multi-factor authentication and secure storage of credentials, aligning with accessibility and privacy requirements.

- **External Data Spaces Owner:** An **external system** that represents other platforms or data spaces that the EXPEDITE platform interacts with. It is essentially a placeholder for any third-party data source (for example, a regional open data portal or an energy data space in another project) that can connect via a **Dataspaces Connector**. This component ensures that EXPEDITE can import or export data securely from external repositories, using standardized connectors. It's not a part of the platform's internal deployment, but rather an external entity that communicates through agreed interfaces. The **Dataspaces Connector Component** in EXPEDITE (described later) handles the secure exchange with these external data space owners.

- **Live Sensors Network:** Another external system representing the array of **IoT sensors and devices** deployed in the real world for the project. These include energy meters, air quality sensors, traffic sensors, etc., installed across buildings and infrastructure in the target district. The Live Sensors system is considered external in the architecture (i.e., outside the core platform) and communicates with EXPEDITE via common IoT protocols (notably **MQTT and HTTP** for pushing data). Its primary role is to continuously gather real-time data from the physical environment and feed it into the EXPEDITE Digital Twin Platform for analysis and visualization. In practice, this could be a collection of sensor gateways that publish data to the platform's IoT ingestion layer.

- **Energy Data Spaces Platform:** An **integration module** within EXPEDITE for external energy data exchange. It provides an interface aligned with emerging **data space** standards (like IDSA/Gaia-X), allowing the platform to publish or retrieve datasets in a governed manner. For example, the city might share energy consumption datasets with an external data space or import datasets like weather data, benchmarks, or third-party simulations. This component ensures such exchanges are **secure and interoperable**, handling aspects like data asset catalogues, access policy enforcement, and compliance with data-sharing agreements. It connects to the BMS integration (for building data) and the dataspaces connector for external links, effectively bridging EXPEDITE with the broader ecosystem of smart city data.

Each of these major systems can consist of multiple **sub-components** or containers which will be described in subsequent sections (especially the data processing and analytics modules). Together, they create a layered architecture where external sources feed into the core platform, which then provides outcomes to end-users through various interfaces.

4.3.2. Sensor Integration and Communication Protocols

Integrating a diverse array of sensors is critical for EXPEDITE's digital twin, and the system's design reflects a **consolidated sensor network strategy**. The goal is to abstract the heterogeneity of sensors (different vendors, protocols, and networks) and provide a **uniform data feed** into the platform for processing. Key elements and approaches for sensor integration include:

- **ThingsBoard Sensor Platform:** EXPEDITE employs *middleware* in the form of a **ThingsBoard IoT platform** to handle sensor data ingestion. ThingsBoard acts as an adapter layer that integrates data from multiple sensors and buildings, handling **telemetry streaming, device management, and protocol translation**. Live sensors in the field (e.g., devices using MQTT, HTTP, or other IoT standards) send data to the ThingsBoard platform, which then standardizes these inputs. This approach enables the platform to interface with various sensor communication protocols (for instance, translating Modbus or Zigbee data into MQTT messages). By using a middleware solution like ThingsBoard (or similar frameworks like oneM2M or FIWARE), the EXPEDITE architecture achieves protocol-agnostic sensor integration, simplifying the addition of new sensor types in the future.

- **MQTT and HTTP Communication:** The primary protocols for sensor data transmission to EXPEDITE are **MQTT** (Message Queuing Telemetry Transport) for efficient publish/subscribe messaging, and HTTP for RESTful pushes. The Live Sensors network publishes data (e.g., a sensor gateway pushing a batch of readings) via MQTT topics or HTTP endpoints that the platform subscribes to. MQTT is well-suited for IoT scenarios due to its low overhead and push-based model, enabling near real-time delivery of data. In the EXPEDITE architecture, sensors (or gateways) connect to the ThingsBoard IoT broker using MQTT; this broker then forwards the data internally (often still via MQTT topics) to the data processing layer (Kafka). This layered use of MQTT (device-level to ThingsBoard, then ThingsBoard to Kafka) ensures scalability – local sensor networks can operate independently and only send aggregated or filtered data to the central platform, aligning with a **hierarchical network architecture** that improves efficiency.

- **Kafka Message Broker for Sensor Data Streaming:** Once sensor telemetry enters the platform (via ThingsBoard), it is streamed through **Apache Kafka**, which serves as the central message broker in EXPEDITE. Kafka ingests sensor data from ThingsBoard topics (for example, each sensor type or location could correspond to a Kafka topic). The **District Data Fusion Engine** subscribes to these Kafka topics to consume the sensor data in real time. Kafka decouples the ingestion of data from its processing; it can buffer bursts of sensor messages and ensure that downstream analytics modules receive data reliably and in order. This design also allows multiple components to tap into the sensor data streams concurrently – for instance, a real-time visualization component could subscribe to the same data as a storage component without interfering with each other.

- **BMS Integration for Building Sensors:** In addition to stand-alone IoT sensors, EXPEDITE integrates data from existing **Building Management Systems (BMS)** through the **BMS Integration Component**. Many buildings (especially large ones or campuses) have legacy BMS that collect HVAC, electricity, and occupancy data. The BMS Integration Component uses API connectors (or protocol adapters for common BMS protocols like BACnet or Modbus) to pull data from these systems and feed it into the EXPEDITE data pipeline. This component ensures that building-level data (e.g., from smart meters or thermostats already managed by a BMS) is not siloed; instead, it becomes part of the overall sensor dataset. It handles **simultaneous connections** to multiple buildings' systems, ensuring scalability for district-wide monitoring. The integration accounts for legacy systems (NFR-BMS-02 calls for backward compatibility), meaning it can interface with older BMS implementations so that the digital twin can include all relevant infrastructure.

- **Data Anonymization and Timestamping:** As sensor data often includes sensitive information (e.g., energy usage of specific buildings, which could be private), the platform includes mechanisms to anonymize or aggregate data to protect privacy. For instance, the ThingsBoard and Kafka layers implement **data anonymization filters**, removing personal identifiers or exact location data when not needed, to ensure compliance with privacy guidelines. Moreover, the system ensures that all sensor data is timestamped consistently to allow synchronization across streams. Achieving a coherent temporal picture of the city (even if sensors report at different intervals) is done by verifying consistent timestamp formats and, if necessary, normalizing times when data enters the fusion engine.

Through this multi-layer integration (device -> IoT platform -> message broker -> fusion engine), EXPEDITE achieves **reliable, scalable, and flexible sensor data management**. The choice of open protocols and middleware aligns with **MIM1 (Context Information Management)** principles by enabling standardized context data exchange, and it provides a foundation for the digital twin to

incorporate any new sensor with minimal effort (just connect it to the IoT middleware using a supported protocol).

4.3.3. Data Processing and Analytics Modules

Once data is collected and flowing within the EXPEDITE platform, a series of processing and analytics modules work to transform this data into actionable insights. The architecture is component-based, with each module typically encapsulated as a **container** or service with a specific role. The major data processing and analytics components are:

- **District Data Fusion Engine:** A core data integration module that **aggregates and harmonizes data** from multiple sources. It receives streaming data via Kafka (sensor feeds, BMS data, etc.) and applies data fusion algorithms to merge these inputs into a coherent dataset. For example, if multiple sensors report overlapping information (like two sensors measuring temperature in one area), the fusion engine reconciles them. It also performs data validation and cleaning, ensuring that outliers or errors in raw data are handled. The fused data is then stored into the central data repository (S3 Storage) for use by simulation and analytics tools. By standardizing data formats and units, the District Data Fusion Engine supports **MIM2 (Common Data Models)** compliance, making sure that subsequent modules consume data in a consistent format regardless of source.

- **Kafka Message Broker:** As mentioned, Kafka serves as the **nervous system** of the platform's data flows. It not only handles sensor data but also **routes simulation requests and results**. When a user configures a simulation in DT Design Time, a message is placed on a Kafka topic (e.g., "simulation_requests") which the relevant simulation engines subscribe to. Once those engines complete their computation, they send a notification message back via Kafka (e.g., on a "simulation_completed" topic). Kafka ensures decoupling between producers (design tool or sensor sources) and consumers (simulation engines, fusion engine, etc.), which improves scalability and fault tolerance. It also retains messages for a configurable time, allowing systems that were temporarily offline to catch up. Kafka in EXPEDITE is configured with appropriate security – topics are access-controlled and the data can be encrypted – plus it supports high throughput needed for streaming **city-scale data**.

- **S3 Storage (Object Storage):** A scalable **object storage service** used to persist simulation results, fused datasets, and any large data blobs. When simulation engines (energy, mobility, etc.) finish processing a scenario, they write the output (which could be large JSON files, time-series CSV, or binary model results) to the S3 Storage component. S3 is chosen for its ability to handle large volumes of data efficiently and durably. It organizes data in buckets and allows retrieval via key (identifier). The DT Design Time will fetch simulation results from S3 to present to the user once notified of completion. Similarly, the analytics and visualization components query S3 to get historical data or specific outputs needed for analysis. This separation of storage concerns means the platform does not rely solely on databases for heavy data; instead, it uses object storage for what it's best at (large files, sequential access) and databases (if any) for metadata or configurations. S3 Storage in the platform also enforces **data access controls and anonymization** – sensitive simulation data (like anything traced to personal data) can be sanitized before storage, and role-based permissions ensure only authorized modules or users retrieve certain files.

- **AI Data-Driven Analytics & Visualizations:** Often referred to as the Analytics Engine – acts as a centralized visualization interface for multiple modules within the architecture, offering a unified approach to presenting insights derived from simulation outputs and real-time data. It consumes data from a variety of sources, including real-time sensor streams (via the fusion

engine or Kafka), simulation outputs (retrieved from S3 storage), building performance metrics (from the Building/Infrastructure Manager's domain), and optimization results. Leveraging these inputs, it generates valuable insights such as trend forecasts (e.g., predicting next-day energy demand based on current conditions), anomaly detection (e.g., identifying unexpected spikes in energy usage), and aggregated indicators (e.g., comparing total renewable energy produced versus consumed within the district).

  - The service fulfills three primary roles: first, it delivers aggregated visualizations to the Mobile App, enabling citizens to access clear and intuitive summaries of district performance; second, it manages the end-to-end visualization pipeline for simulation outputs, integrating seamlessly with both the Design-Time and Runtime components of the platform; and third, it exposes a set of dedicated web services that allow simulation visualizations to be embedded in browser windows within the Digital Twin. These visualizations may take the form of charts, graphs, map overlays, or immersive AR/VR scenes depending on the use case and interface.

  - To ensure secure communication and data integrity, the component authenticates itself using a service account token via Keycloak. By centralizing advanced analytics capabilities, the module also enables the deployment of complex AI algorithms (such as neural networks for traffic flow prediction), with results made readily accessible to all relevant components and end-users of the system.

- **District Optimization & Decision Support:** This is the **policy optimization engine** of the platform, focusing on **multi-criteria optimization for urban districts**. When city planners want to compare solutions (e.g., to allocate solar panels and batteries in a district for maximum self-sufficiency or to install additional EV charging stations), this engine uses algorithms (potentially AI or operations research techniques) to evaluate different combinations. It takes inputs such as simulation data from various domains (energy, mobility, building, etc., fetched from S3 or directly from simulation modules), as well as any constraints or objectives the planner has defined. For example, it might ingest building energy model outputs from the Building Stock Modelling component and grid flexibility data from the Energy Forecasting engine, then run an optimization routine to suggest optimal retrofitting plans and energy trading strategies. The Decision Support tool also leverages economic data – it can integrate with the Economic Impact module to ensure recommendations are not only technically optimal but also financially viable. The outputs of this engine are fed back to planners via the DT Design Time interface (like a report of recommended actions) and can be visualized through the analytics module. It also interacts with the AI Visualization component to present district-level optimization results in user-friendly formats. To maintain secure operations, this component uses **Keycloak app authentication** (service account) just like the analytics engine.

- **Simulation Engines (Energy, Mobility, etc.):** A suite of specialized **simulation modules** handle different domains of the urban environment. These include:

  - **Energy Forecasting & Grid Flexibility:** simulates and predicts energy demand/supply in the district. It receives simulation jobs via Kafka (e.g., "simulate next 24h energy use given scenario X") and uses models of energy consumption and production to forecast hourly/daily loads. It also evaluates grid flexibility options, such as how much the district can adjust demand in response to external signals. Results (demand curves, flexibility metrics) are stored to S3 and patterns saved to the pattern repository. This addresses requirements like providing energy balance visualizations and supporting demand-response planning.

- **Mobility & Transport:** simulates urban traffic and transport network performance. Using possibly tools like SUMO (Simulation of Urban MObility) or similar, it models traffic flows, public transport usage, and can forecast congestion or emissions under various scenarios. It interacts with IoT data (for real-time updates), stores results in S3, and notifies when done. It's crucial for scenarios like evaluating new bike lanes or altered public transit schedules.

- **RES (Renewable Energy Sources) Modelling:** focuses on **long-term renewable energy planning**. It simulates scenarios out to 2030 or 2050, for instance, with different penetrations of solar PV, wind, etc. This helps identify optimal renewable mixes (FR-RES-01 covers long-term RES modeling). It uses input from Kafka (scenario definitions), writes results to S3, and also outputs summary datasets (GIS layers, Excel sheets) for external use, aligning with FR-RES-05 on providing outputs in standard formats. It also integrates with district heating and energy storage aspects for holistic energy scenarios.

- **Building Stock Modelling:** simulates building energy performance across the district, including **retrofitting scenarios**. It uses data from actual buildings (via the ThingsBoard sensor platform feeding it baseline performance data) to calibrate models. It can simulate improvements like insulation, HVAC upgrades, etc., to estimate energy savings (FR-BSM-03 requires evaluating retrofitting impacts). It stores detailed building model outputs (energy usage, CO_2 emissions) in S3 and shares results with other engines – e.g., providing building energy demand projections to the Energy Forecasting engine and feeding building models into the District Optimization tool. This component ensures that the digital twin has a fine-grained representation of the building stock, vital for PED planning.

- **District Heating & Energy Storage:** simulates thermal networks and storage systems in the district. For areas with district heating/cooling, it models the generation (boilers, geothermal, etc.), distribution pipelines, and building heat exchanges, as well as the integration of heat storage units. It can evaluate if waste heat or renewable heat can be utilized and how thermal storage (like hot water tanks) could shave peak demand. It writes simulation results (like temperature profiles, fuel consumption) to S3 and updates the pattern repository with any reusable patterns (like typical load curves). This tool is key for exploring how to decarbonize heating in the district.

- **Economic Impact Assessment Tool:** analyzes the **financial aspects** of scenarios. It is not a simulation of physics but rather takes outputs from others (energy saved, costs of interventions, etc.) and computes economic indicators: net present value, return on investment, payback periods, job creation, etc. (fulfilling the need to assess economic feasibility of PED measures). When a scenario is run, this tool listens via Kafka for completion of relevant simulations and then produces a report on the economic outcomes. It ensures sustainability plans are also financially sound. For example, if a scenario includes installing solar panels, this tool would calculate the investment vs. savings over time. Its results can be fed to both the DT Design interface for planners and to the optimization engine (which may consider cost as an objective).

- **DT Pattern Repository:** A centralized library for **reusable simulation patterns and models**. As simulations are performed, certain artifacts (like calibrated models, typical patterns of use, or scenario templates) are stored here for reuse. It interacts with all the simulation engines which deposit their model metadata and patterns after runs. For instance, the Energy Forecasting engine might save a "summer demand profile" pattern that can be reused, or the

Building Stock tool might save a model of a building that can be repurposed in another scenario. The Pattern Repository also serves external stakeholders – it allows **external researchers or partners** to access open simulation models and metadata (with permission) via APIs. Technically, this repository could be implemented with a combination of a database and a file versioning system (the DSL suggests technologies like Drupal/Git for pattern management). It supports search and filter, version control, and metadata tagging of patterns, which helps maintain **consistency and traceability** across the project's simulations. By using this, EXPEDITE ensures that knowledge gained (in form of models/patterns) is not lost and scenarios are reproducible – important for scientific rigor and for other cities to replicate the approach.

These processing and analytics modules form the **brain of the digital twin**, taking inputs (data and simulation requests) and producing outputs (insights and answers to "what-if" questions). They are designed to be loosely coupled (communicating via Kafka and storage) so that each can evolve or scale independently – for example, one could deploy more instances of the Energy simulation engine if needed without affecting others. This modular design aligns with the project's high-level requirement for **integration and interoperability** (HLR-1) by using standard interfaces between modules, and it supports **real-time and historical data analysis** (HLR-3) through the combined use of streaming (Kafka) and storage (S3). By incorporating AI and optimization, the system also addresses **decision support** needs (HLR-6) for sustainable urban planning.

4.4. User Roles and Interactions

The EXPEDITE platform is user-centric, with different interfaces and features tailored to specific roles. The main user roles and how they interact with the system are:

- **Citizen:** Citizens access EXPEDITE primarily through the **Mobile App**. Their interaction is focused on **viewing information and participating in community activities**. For example, a citizen can use the app to see the real-time energy consumption of their building or neighbourhood with intuitive visualizations (such as simple graphs or comparisons to targets). They receive notifications about local sustainability initiatives – e.g., a challenge to reduce energy usage or a public consultation on mobility changes – and can respond through the app. Citizens can also join groups or forums within the app to discuss ideas, answer surveys or quizzes about energy-saving habits, and provide feedback which is funnelled to city planners. Importantly, their access is **read-only and participatory**; they do not configure simulations but their feedback can influence planning (e.g., indicating community support for certain measures). The platform ensures citizen-facing features are **engaging and easy to use** (HLR-7 on stakeholder engagement), and their data (like personal info or responses) are protected (e.g., only aggregated feedback is shown to planners, preserving privacy).



Figure 35: Citizen Interaction with EXPEDITE System

- **City Planner:** City planners are one of the primary users of the **EXPEDITE Digital Twin Platform**, using the **DT Design Time** and reviewing outputs via the **DT Runtime** and analytics dashboards. A city planner logs into the secure web interface (SSO via Keycloak) and can then **configure simulation scenarios** using DT Design Time's graphical interface. They select what aspects to simulate (energy, transport, etc.), adjust parameters (like projected EV adoption rate or number of building retrofits in a scenario), and submit the simulation job. While the simulation runs (in the cloud via the engines described), the planner can monitor progress in real-time through the DT Runtime or status updates. Once complete, they use DT Runtime and the Analytics module to **analyze results**: viewing maps of energy demand, graphs of traffic congestion, CO_2 emission comparisons between scenarios, etc. They also get automatically generated **scenario reports** that detail the outcomes, which can include economic impact charts and environmental KPIs. If needed, the planner can iterate – tweak parameters in DT Design and run again. Planners also use the **District Optimization tool** indirectly; for instance, after seeing raw simulation results, they might run the optimization to get recommendations on improving those results, all through the interface. Throughout, they maintain control and oversight – the system provides transparency in how simulations are run (addressing **explainability** concerns in AI, per HLR-4). City planners thus engage in a cycle of **configure → simulate → analyze → decide**, with EXPEDITE supporting each step with robust data and visualization.

- **Building/Infrastructure Manager:** This role focuses on a subset of the system related to facilities management and operations. A building manager might be responsible for a campus or a set of buildings in the district. They interact with the platform mainly via the **DT Runtime dashboards** and potentially a specialized dashboard for building performance (which could be part of the AI Analytics interface). Their interest is in **monitoring real-time building data** (energy consumption, indoor environment conditions) and short-term forecasts to plan maintenance or tune systems. For example, through EXPEDITE, a building manager can see if a building's HVAC system is underperforming by comparing live data to simulation benchmarks. They can also test "what-if" scenarios for their building, like seeing predicted benefits of a new insulation, using the building stock simulation outputs. The integration of actual BMS data means the platform might show alerts if a building's energy use spikes unexpectedly (maybe indicating an equipment fault). The building manager does not necessarily run city-wide simulations, but they benefit from those results – e.g., if the city scenario suggests a particular building should reduce load at peak times, the manager gets that recommendation. With secure login, they access only the data for their managed buildings (ensuring **access control** boundaries). Their usage of EXPEDITE helps bridge the gap between

strategic planning and on-the-ground operations by providing a **common interface** for both high-level simulations and granular building data.

- **External Stakeholder:** External stakeholders could be researchers, utility companies, policy analysts, or even the general public interested in open data. They engage with the platform through **integration endpoints** or curated dashboards. For instance, an external energy utility might connect via the **Energy Data Spaces Platform** to retrieve simulation models or provide data. An academic partner might use the **DT Pattern Repository** to access simulation patterns and results for research. These users typically do not use the platform's internal GUI heavily; instead, they rely on **APIs and data services** that EXPEDITE exposes. Single Sign-On and secure API tokens (OAuth2) are used here as well, to ensure only authorized data sharing happens. For example, an external stakeholder with permission could pull a dataset of aggregated mobility data to conduct their own analysis. Alternatively, a city partner might upload data through the data space for the platform to consume (like sharing new demographics data to improve simulations). The system's compliance with **standards and interoperability** (such as NGSI-LD if used, or IDS connectors) makes these external interactions feasible. From a role perspective, external stakeholders get **read (and sometimes write) access to data/models** but not the ability to run the core simulation engines directly (unless explicitly allowed via an API call for that purpose). Their contributions and usage ensure the platform isn't an isolated silo but part of a broader smart city data ecosystem.

In summary, the platform's design acknowledges the differing needs of its user base – from highly interactive use by city planners designing scenarios, to passive data consumption by citizens, to data exchange with third parties. Every interaction is secured via a unified authentication system (Keycloak), providing a single trust domain for all user actions. The user experience is tailored so that each role sees the tools and data relevant to them, thereby fulfilling the requirement of **accessible and intuitive design** for diverse stakeholders (HLR-8 on accessibility and usability).



Figure 36: EXPEDITE Users' interaction with the system

4.5. Architecture Overview

The EXPEDITE system architecture follows a **C4 model** style[2], with high-level context relationships and detailed container-level internal structures. This section presents an overview of the architecture in two parts: a **System Context** diagram illustrating the platform in relation to users and external systems, and a **Container Architecture** view showing the internal modules and their interactions. Each figure is accompanied by an explanation of how components communicate and how data flows through the system.

[2] The C4 schema of the architecture is available at: https://photolab.iccs.gr/gitlab/expedite/expedite-architecture

4.5.1. System Context Diagram



Figure 37: Full Internal Component Diagram

Figure 37 shows the overview of all EXPEDITE solution interconnections, both between components as well as users. Given the complexity of the system, we acknowledge that the overall system is difficult to interpret at first glance. In the following subsections, we have created component-level flow diagrams to better describe interactions between the different subsystems.

The EXPEDITE system has the Digital Twin Platform at the core, interacting with external actors and systems. Surrounding the platform, we see the four primary user roles – **Citizen**, **City Planner**, **Building/Infrastructure Manager**, and **External Stakeholder** – as well as external systems like the **External Data Spaces** and **Live Sensors** network (IoT devices). Solid lines indicate major interaction paths: for example, Citizens interact via the Mobile App (which is part of the platform), City Planners use the DT Design/Runtime interfaces, and Building Managers use the platform's dashboards for building data. External Stakeholders connect through the data sharing interfaces (Energy Data Space). The Live Sensors push data into the platform, while the External Data Space exchanges data assets through a secure connector. This context diagram highlights that the EXPEDITE platform is the central hub that **receives data from sensors and BMS**, **interfaces with other data platforms**, and **provides services to users** with different needs. It establishes the scope: identifying everything that is part of the is part of the EXPEDITE software system, and everything outside are either users or external systems it interoperates with.

Notably, the context emphasizes **security and boundaries** – for instance, all user interactions (citizens, planners, managers) go through authenticated applications (Mobile App, web portal) rather than directly accessing the database or internals, ensuring a clear separation. The External Data Spaces connection suggests that the platform adheres to open standards for sharing data externally, aligning with the **interoperability goals (MIMs)** of the project. Overall, the context diagram ensures that at a glance, one understands who uses the system and what other systems are connected, setting the stage for the deeper dive into the internal architecture.

4.5.2. Internal Architecture and Component Interactions

The container-level diagram zooms into a specific subset of the EXPEDITE architecture relevant to sensor data integration and building simulations. It depicts how **IoT data flows into the platform and is utilized by simulation and optimization components**, using the Building Stock domain as an example. Key components visible include: the **ThingsBoard Sensor Platform** (labeled as sensor adapters) which collects data from **Live Sensors**, the **BMS Integration Component** bringing in data from building management systems, and the central **Kafka** message broker that streams these inputs into the core platform. The **Building Stock Modelling** container is shown, consuming real building performance data (from sensor adapters via Kafka) to calibrate its simulations, and in turn providing outputs to other components like **District Optimization** and **Energy Forecasting**. The **S3 Storage** is present to store simulation results, and the **AI Visualization** module to utilize those results for dashboards. The Building/Infrastructure Manager actor is also indicated, linked to the DT Runtime or analytics front-end (not explicitly drawn in text here, but in the diagram they would access AI Visualization or DT Runtime for building data).

This figure illustrates several interaction patterns among containers:

- **Sensor Data Ingestion:** Live Sensors ➔ ThingsBoard (Sensor Platform) ➔ Kafka. This chain shows real-time sensor readings being injected into the platform. In the diagram, a label like "MQTT/HTTP" on the arrow from Live Sensors to ThingsBoard indicates the protocol used. Another arrow "streams telemetry data" from ThingsBoard to Kafka indicates how sensor data is forwarded internally.



Figure 38: Live Data Ingestion & Usage

- **Building Data Utilization:** Kafka ➔ Building Stock Modelling ("receives simulation requests" or data) and Sensor Platform ➔ Building Stock Modelling ("provides real building performance data" for calibration). This shows that the building simulation component continuously gets updated with real data, ensuring the digital twin remains accurate over time. The building model, once calibrated, might run simulations (triggered via Kafka when a planner initiates one) and then output results.



Figure 39: Live Data Integration to the EXPEDITE system

- **Results Storage and Feedback:** Building Stock Modelling ➔ S3 Storage ("stores simulation results") after completing a simulation. Then S3 ➔ District Optimization ("provides data for optimization"), meaning the results can be used by the optimization engine to refine district-level strategies. Also S3 ➔ AI Visualization ("provides simulation data for visualization"), enabling the analytics dashboard to present these results to users. Furthermore, Building Stock Modelling ➔ District Optimization ("provides building energy models for optimization") underlines direct collaboration – the building simulations feed into higher-level policy simulations.



Figure 40: Simulation Requests and Results

- **Control and Integration:** The BMS Integration Component ➔ Kafka ("sends BMS data") ensures that data from legacy building systems also enters the same pipeline. Meanwhile, the Energy Data Spaces Platform and External Data might be visible in a broader container diagram (not shown in this figure but present in others focusing on data exchange), indicating where external data flows would connect – for example, the Energy Data Spaces Platform ↔ Dataspaces Connector ↔ External Data Spaces to exchange data assets securely .

By focusing on the building stock analysis sub-architecture, this diagram highlights **inter-module communication**: sensor data coming in, simulations running, and data flowing out to storage and other modules. It exemplifies the **event-driven nature** of EXPEDITE – many arrows represent asynchronous messaging via Kafka (publish/subscribe), which is a deliberate design choice to ensure loose coupling and scalability. It also demonstrates compliance with certain requirements: for instance, **FR-BSM-02 (data integration from BMS and cadastre)** is addressed by the BMS integration feeding building data to simulations, and **FR-BSM-05 (data access via APIs in GIS/Excel)** is facilitated by storing results in S3 and pattern repository, which can then be exported.

In the full internal architecture (encompassing all containers), similar patterns occur across other domains: e.g., **Energy Forecasting, Mobility, RES,** etc., all receive simulation jobs via Kafka and store results to S3 , while the **District Optimization** and **AI Visualization** containers tie everything together by pulling results and generating final outputs for the user . The use of Keycloak is implicit in internal diagrams but is critical: every user-facing container (Mobile App, DT Runtime, DT Design) has an arrow to Keycloak for auth, and Keycloak issues tokens back, enforcing the security context in every interaction.

In summary, the architecture overview through these diagrams shows a **multi-tier system**: external layer (sensors, users, external data spaces), integration layer (IoT platform, connectors), core data/message layer (Kafka, data fusion, storage), application layer (simulation engines, analytics, optimization), and presentation layer (runtime UI, mobile app). The interactions among these layers are carefully orchestrated to meet the system's requirements for **real-time performance**, **modularity**, and **interoperability**.

4.5.3. Simulation Toolset

A core functionality of the ExPEDite Digital Twin platform is the ability to simulate complex urban scenarios across multiple domains—including energy, mobility, buildings, and socio-economic dimensions—and deliver actionable insights to urban planners and stakeholders. The simulation flow is orchestrated through a combination of modular tools and backend services, which together form the platform's computational and data management backbone.

The overall simulation workflow is depicted in Figure 41, which illustrates the sequence of interactions between the user interface, orchestration middleware, domain-specific simulation engines, and storage/visualization modules. The architecture follows a **publish-subscribe pattern** with **Kafka** acting as the central message broker responsible for triggering and coordinating simulation requests across components.



Figure 41: EXPEDITE Simulation Workflow

The process begins when a **City Planner** configures a simulation scenario using the **DT Design Time** interface. This includes the definition of urban parameters, geographical boundaries, system configurations, and user objectives. Once the configuration is complete, a request message is sent to Kafka (step 2), which distributes simulation tasks to the appropriate modeling engines based on the parameters defined.

Each domain-specific modeling component (colored **purple** in the figure) receives the request and executes the relevant simulations. These components include:

- **Building Stock Modelling**: Physical and energy modeling of building structures
- **RES Modelling**: Renewable energy potential analysis
- **District Heating & Energy Storage**: Simulation of thermal energy systems
- **Mobility & Transport**: Transport network and flow simulation
- **Energy Forecasting & Grid Flexibility**: Power demand and flexibility forecasting
- **Economic Impact Assessment Tool**: Financial impact modeling based on simulation outputs

Each component returns its simulation results to a shared **S3-compatible storage** service, which acts as a centralized data repository. Simulation results are then accessed by downstream services including:

- **AI Data-Driven Analytics & Visualizations**: Which provide predictive analytics and interactive visual outputs
- **District Optimization & Decision Support Engine**: Which uses the outputs for multi-criteria optimization and urban policy planning

This orchestrated process supports **asynchronous, parallel execution of simulations**, allowing for dynamic scaling and modular updates to each domain engine. Notifications and simulation completions are also relayed back through Kafka to ensure status awareness and process synchronization.

This workflow not only provides the technical foundation for system interoperability, but also ensures traceability and repeatability of simulation scenarios, facilitating evidence-based planning for PEDs.

4.5.4. Compliance with Requirements

The EXPEDITE system architecture was designed to satisfy the project's requirements, which include functional requirements (FR), non-functional requirements (NFR), and high-level requirements (HLR) as outlined D2.1 and section 7.2. This section cross-references how the architecture and components meet several key requirements:

- **Integration and Interoperability (HLR-1):** The requirement to enable seamless integration of heterogeneous data sources and use standardized APIs is fulfilled by the platform's use of **common data exchange mechanisms**. For instance, all sensor data is normalized through the IoT middleware and Kafka, which uses JSON messages and consistent schemas (aligning with MIM1 and MIM2 standards). The **Dataspaces Connector** and **Energy Data Spaces Platform** allow standardized data sharing with external systems, adhering to protocols and models that ensure interoperability. The modular architecture ("modular and interoperable architectural principles") means each component can be replaced or upgraded with minimal impact on others, thus supporting replicability.

- **Data Harmonization and Standardization (HLR-2):** To ensure all incoming data follows a common format, the **District Data Fusion Engine** performs schema validation and harmonization on streaming data. It effectively converts diverse input formats into a unified data model used internally. Additionally, the adoption of established **data models** for city data (e.g., using standard terms for sensor readings, or CityGML for 3D city data, etc.) is part of the development guidelines, aligning with **MIM 2 (Data Models)**. For example, building energy data from BMS is converted into standardized metrics (kWh, occupancy, etc.) before being used in simulations, fulfilling the goal of consistency across the platform.

- **Real-Time and Historical Data Support (HLR-3):** The architecture explicitly supports both streaming real-time data and storage of historical data for analysis. Real-time support is seen in the Kafka-based streaming and immediate visualization in DT Runtime (e.g., a city planner can see live sensor updates on a dashboard). Historical data support is provided by S3 Storage and the DT Pattern Repository, where past simulation results and data patterns are stored and can be retrieved for comparisons or trend analysis. For example, a planner can compare a current simulation's results with a historical pattern stored from a previous scenario (which addresses the requirement of leveraging historical data).

- **Privacy and Security (HLR-5):** The requirement for robust privacy and security measures is a cornerstone of the architecture. **Keycloak** provides a centralized identity and access management, enforcing authentication (SSO, OAuth2 tokens) and role-based access control across all components. Data encryption is applied in transit (e.g., HTTPS for APIs, TLS for MQTT where possible) and at rest (S3 buckets can be encrypted, databases encrypted). **Data**

anonymization techniques are employed: for instance, the platform strips personal identifiers from sensor data (like replacing exact device IDs with pseudonyms or aggregating data to a level that cannot identify individuals). A **Privacy Impact Assessment (PIA)** is conducted as part of the project to ensure GDPR compliance, and the system design incorporates principles of **privacy by design** – only necessary personal data is used, and users (citizens) have control over what they share (HLR-13 relates to user data rights). The architecture also plans for **audit logs** and monitoring to detect and respond to security incidents, contributing to resilience (HLR-12 on robustness).

- **Decision Support Tools (HLR-6):** The inclusion of advanced decision support fulfills the requirement for evidence-based decision-making support. The **District Optimization & Decision Support** module is directly aimed at this, providing optimization of district-level scenarios and policy outcomes. Additionally, the **Energy Forecasting** and **Mobility simulation** engines supply the necessary evidence (predictions and models) to underpin these decisions, and the **analytics** component provides actionable insights (like highlighting an anomaly or a trend that requires action). The fact that these are integrated into the planners' workflow (through the DT Design/Runtime interfaces) means the requirement is met within a single platform without needing external tools.

- **Stakeholder Collaboration and Engagement (HLR-7):** The architecture supports collaboration by providing **shared data access and visualization tools**. The Mobile App and web interfaces serve as the means for different stakeholders to view common information (breaking down silos). For instance, a city planner can publish a scenario result on a dashboard that is accessible to external stakeholders or the public. Citizens are engaged via the mobile app and can see visualizations that the planners also see, fostering a common understanding. Moreover, by integrating feedback loops (citizen input collected in the app can be fed into planning considerations), the platform ensures stakeholder voices are part of the planning process. This collaborative environment was a key requirement and is achieved by the platform's multi-user design.

- **Accessibility and Usability (HLR-8):** While a technical architecture, it was required that tools be intuitive for city planners and others. The system meets this by providing dedicated interfaces for each role that hide complexity. For example, the DT Design Time interface uses a **graphical drag-and-drop** or form-based approach to set up simulations, rather than requiring coding or complex configuration – this prioritizes usability so planners can work autonomously without IT expert help. The mobile app follows UX best practices for citizens. Also, the integration of all needed functions into one platform means users don't have to switch contexts or manage data transfers themselves, which improves the user experience.

- **Functional Requirements Coverage** (see also section 7.2)**:** On a more granular level, each module addresses specific functional requirements. A few examples are listed below:

    - *FR-DTD-02 (Scenario Library):* The DT Design Time module includes a library of pre-configured templates for simulations, as described earlier, fulfilling this requirement by allowing quick setup of common scenarios.

    - *FR-BMS-01/02 (Building Data Collection & API Integration):* The BMS Integration Component satisfies these by connecting to building systems to gather data and enabling data exchange between BMS and the digital twin , ensuring the platform has building data available and can also send adjustments or commands if needed (like a demand response action).

- *FR-BSM-03 (Retrofitting Simulation):* The Building Stock Modelling explicitly supports simulating retrofitting scenarios to evaluate energy savings, which is exactly what this requirement asks for.

- *FR-RES-04 (Environmental Impact Analysis):* The RES Modelling and other simulation engines produce environmental impact reports (e.g., CO_2 reduction, air quality changes) as part of their output, addressing this requirement to inform sustainability assessments.

- *FR-MT-04/05 (Transport Visualization & Recommendations):* The Mobility & Transport simulation provides visual network performance outputs and recommendations for improvements , covering these functional needs for the mobility domain.

Each container in the architecture was tagged with relevant requirement IDs (as seen in the DSL), ensuring traceability. For instance, the **Mobile App** addresses FR-MA-01 through FR-MA-06 (which include features like secure access, notifications, community features, etc.) in its design, and those are implemented in the architecture through its connection with Keycloak and the analytics back-end for delivering content. The thorough mapping of requirements to architecture elements demonstrates that the design is **requirement-driven**.

- **Targeted Outcomes and KPIs:** The architecture also aligns with the project's targeted outcomes (TO) and Key Performance Indicators. For example, HLR-9 on environmental sustainability and KPIs like reduction in energy consumption are directly supported by the system's ability to model and verify such outcomes in simulations. The presence of an Economic Impact tool addresses KPI5.x series which often relate to cost savings and ROI.

In conclusion, the EXPEDITE architecture is **fully aligned with the specified requirements**. The modular design allowed the team to ensure each requirement (from functional like *"the system shall do X"* to non-functional like *"must handle Y scale"* or *"ensure Z security"*) is accounted for by one or more components. Cross-referencing the requirements list, there is clear coverage of each item by design decisions in the architecture. This compliance gives confidence that as the project moves into implementation and testing, the system will meet its intended objectives and pass evaluation against the requirement criteria. The complete list of targeted outcomes, high level, functional and non-functional requirements are presented in section 7.2.

4.5.5. Interoperability Mechanisms and Sensor Guidelines

Interoperability and sensor network integration are central considerations in EXPEDITE, given the need to interface with existing city systems and to incorporate a wide array of devices. The project adheres to the **Minimal Interoperability Mechanisms (MIMs)** framework from open smart city initiatives, focusing on foundational MIMs, and has developed guidelines for consolidating sensor networks. This section highlights how the system implements interoperability (particularly MIM1, MIM2, MIM3 compliance) and outlines the approach to sensor integration and consolidation.

MIMs Compliance (MIM1, MIM2, MIM3): According to the project scope, EXPEDITE targets the foundational layer of the MIMs Plus framework, concentrating on MIM1 (Context Information Management), MIM2 (Common Data Models), and MIM3 (Ecosystem Transaction Management / some aspects of data exchange). In practice:

- *MIM1: Context Information Management* – The platform uses standardized context management principles by structuring all city data in a uniform context. For instance, it could

leverage **NGSI-LD** (a context information API standard by Fiware/OASC) within the IoT middleware or data fusion layer to represent sensor data and city entity states. While the internal architecture employs Kafka and custom data models, it is designed to be compatible with context broker concepts. The **District Data Fusion Engine** essentially acts as a context aggregator, maintaining the latest state of various context entities (buildings, sensors, vehicles, etc.) in memory and storage. This ensures that any component can query the "current context" of the city and get a coherent picture. By aligning with MIM1, EXPEDITE can share or consume context information with other systems easily — for example, connecting a Fiware Orion context broker from another project to ingest external context, or exposing its context data to an external dashboard via standard APIs.

- *MIM2: Common Data Models* – The project places heavy emphasis on data model standardization for key domains like energy and mobility. This means using or extending existing open data models (such as SAREF for energy, CIM for electrical grids, CityGML for 3D city objects, GTFS for transport, etc.) to structure the data. In EXPEDITE's implementation, the **data schemas used by simulation engines and data storage** are consistent and documented. For example, a "Building" entity has a defined schema including properties for energy demand, CO_2 emissions, floor area, etc., which is used uniformly by the Building Stock tool, the Energy engine, and the optimization engine. The use of a **pattern repository** also enforces consistency by storing models with metadata according to a standard schema (metadata might include location, time horizon, units, etc. that follow agreed formats). Adhering to MIM2 ensures that when the platform exchanges data with external systems or partners, minimal translation is needed. The External Data Spaces interface is built around standardized models so that an external stakeholder retrieving data understands it immediately (e.g., using ISO/IEC or EU common data standards). The requirement file's HLR-1 and HLR-2 also underscore this: using standardized APIs and harmonizing data format are essentially the realization of MIM1 and MIM2 respectively within EXPEDITE.

- *MIM3: Ecosystem Transactions (and Data Exchange)* – EXPEDITE addresses this through its **Energy Data Spaces Platform and Dataspaces Connector**. MIM3 often relates to enabling transactions across different stakeholders' systems (sometimes described as "marketplaces" or agreements for data/service exchange). The platform's connector module is aligned with initiatives like **IDSA (International Data Spaces Association)**, which define how data can be shared securely and under certain usage policies – akin to transactions/contracts for data. The **Dataspaces Connector Component** provides secure connection and contract negotiation capabilities for data sharing. For example, if the city wants to share certain simulation data with an energy company, the connector ensures that only the agreed data is transferred and logs this transaction for accountability. This matches the notion of "Smart Contracts" mentioned in some MIM3 contexts – not blockchain contracts per se, but the idea that data sharing can be controlled and traced (also referenced in the requirements as MIM3 in context of compliance). By implementing these connectors, EXPEDITE can later integrate with a broader data space (like a national urban data platform or other city's digital twin) in a standardized way. This fosters an ecosystem where different digital twins or smart city services can **transact data and services seamlessly**, which is at the heart of MIM3.

In summary, the platform's interoperability is **by design**. It uses established standards where possible and has an architecture flexible enough to plug into external systems. The commitment to MIMs means EXPEDITE is not a bespoke, one-off solution, but rather a part of a larger interoperable landscape of smart city tools, ensuring **replicability and scalability beyond the project**.

4.5.6. Sensor Network Consolidation Strategy:

The project's **Guidelines for Sensor Network Consolidation** provide recommendations that are reflected in the system architecture. Key points include:

- *Use of Middleware for Integration:* Rather than each sensor communicating directly with every application, EXPEDITE uses a middleware (ThingsBoard, etc.) as a unified interface. This simplifies management (one platform to handle firmware updates, data parsing, etc.) and provides a **single point of configuration** for connecting new sensors. This approach also enables **protocol translation**, as noted earlier (e.g., converting Modbus or BACnet from building systems to MQTT/JSON that the rest of the platform understands). It results in a consolidated feed of sensor information, regardless of the underlying network technology.

- *Support for Multiple Network Types:* The guidelines recognize that urban sensor networks can include wired sensors (Ethernet, fiber), wireless sensors (Wi-Fi, Zigbee, LoRaWAN, NB-IoT, 5G, etc.). The EXPEDITE platform is largely agnostic to the lower-level network – as long as data reaches the IoT middleware, it doesn't matter if it came via LoRaWAN or a cellular connection. That said, the project documentation did an analysis of communication protocols, ensuring the chosen methods (like MQTT over TCP/IP) are suitable for the required data volume and frequency. For example, since EXPEDITE's focus is not on extremely time-critical (<1 s) data, but on city monitoring (where a few seconds resolution is acceptable), protocols like LoRaWAN for wide-area low-power sensors were deemed sufficient for certain use cases. The system can consolidate data from **low-power sensors** (which may send data infrequently) and **high-bandwidth sensors** (like CCTV or traffic cameras streaming, though those might be handled via edge processing). The consolidation strategy includes deploying **gateway devices** where necessary to bring different networks into the common IP domain for the platform to ingest.

- *Hierarchical Network Design:* As mentioned, a hierarchical (multi-tier) network architecture is recommended to improve scalability and resilience. In concrete terms, this means grouping sensors under local hubs (e.g., one hub per building or block) that pre-process and send data upward. The EXPEDITE architecture's edge processing (ThingsBoard rule engine) at the city level and possible micro-controllers at building level reflect this. It prevents data flooding the central system by only sending *aggregated or relevant events*. For instance, a building's dozens of temperature sensors might feed a local BMS, which then only sends the central platform a summary (like "zone A average temp"). This strategy is crucial when scaling to potentially thousands of sensors in a district; it's more efficient and also **reduces single points of failure** (each local network can operate even if connectivity to core is lost temporarily).

- *Data Quality and Consistency:* Consolidation is not just about wiring, but also about making sure the data coming in is usable. The guidelines emphasize time synchronization across sensors (ensuring clocks are reasonably in sync, maybe via NTP or having the platform timestamp on ingest), and calibration/validation of sensors. The architecture supports this by having the data fusion stage check for anomalies and possibly cross-verify sensor inputs (e.g., if one sensor's data is way off expected range, flag it). By consolidating networks, it's easier to run such validations in one place than if systems were siloed.

- *Maintenance and Deployment Guidelines:* Though not an architecture component, the project's sensor guidelines also cover practical interoperability issues: using common **naming conventions** for sensors, maintaining an inventory (so that each sensor is known in the context model), and ensuring that adding a new sensor requires minimal effort (plug-and-play where possible). The EXPEDITE platform includes a device registry (possibly within ThingsBoard or

as part of the fusion engine) where each sensor or data source is registered with metadata. This ties into interoperability because each sensor is an entity in the context information system and can be discovered or managed uniformly.

By following these guidelines, the project ensures that the sensor data feeding the digital twin is **comprehensive, reliable, and easy to integrate**. In effect, the sensor network becomes a cohesive part of the city's digital infrastructure rather than a patchwork of isolated devices. This consolidation also aids reproducibility: other cities or districts aiming to replicate EXPEDITE can follow the same approach – deploy an IoT middleware, connect their sensors to it, use Kafka for distribution, etc., and achieve similar results, regardless of their specific sensor hardware. It's an approach that supports the **scalability and replicability outcomes** the EU looks for in such projects (HLR-1 and project KPIs about replication).

To illustrate the compliance with these principles: the current implementation at the pilot site involves deploying sensors grouped by function (energy meters, environmental sensors, etc.), connecting through either Wi-Fi or LoRaWAN to a central platform where data is aggregated. Data from that platform then ingested by EXPEDITE's IoT gateway, unified and processed. This demonstrates how the theoretical guidelines are put into practice.

Interoperability with Legacy and External Systems: Another aspect worth highlighting is how EXPEDITE ensures it can work with what's already there in a city and with external innovations:

- Legacy integration is handled by modules like BMS Integration (for older building systems) and by the general ability to consume CSV, JSON, XML data (the S3 and Kafka components are format-agnostic, meaning if an old system can dump data in CSV, EXPEDITE can pick it up and ingest it).

- External tools integration: If, for example, a city uses an existing traffic control center software, EXPEDITE could ingest data from it or output results to it thanks to its API-driven design. This stops the architecture from requiring a rip-and-replace of existing city systems; instead it **augments and interconnects** them.

- Use of **open standards**: by aligning with standards (such as OAuth2 for authentication, NGSI-LD for context, etc.), the platform makes it easier for any external third-party to connect if authorized, reducing vendor lock-in and fostering an open ecosystem.

In conclusion, EXPEDITE's approach to interoperability and sensor management is one of its strongpoints. By following recognized best practices (MIMs, hierarchical IoT, middleware usage), it ensures that the digital twin can gather data from anywhere and share data to anywhere in a controlled, standard manner. This not only benefits the project's immediate needs but also positions the system as a reference model for other PED or smart city projects aiming for **system-of-systems integration**.

4.5.7. Security and Privacy Considerations

Security and privacy are paramount in the EXPEDITE system due to the sensitive nature of urban data and the involvement of multiple stakeholders. The architecture incorporates security at multiple levels — from user authentication to data encryption — and follows privacy-by-design principles to protect personal and sensitive information. This section outlines the key security measures and privacy safeguards built into the system.



Figure 42: User and Application Authentication

User Authentication and Access Control: The EXPEDITE platform uses a centralized **Keycloak** server for authentication and identity management. All users (citizens, planners, managers, external partners) and even applications (services) authenticate through Keycloak:

- **Single Sign-On (SSO):** Users log in once via Keycloak, which manages their session across the various EXPEDITE modules. Whether a city planner is using the DT Design Time interface or the DT Runtime visualization, the same SSO credentials apply, and Keycloak issues an OAuth2 token granting access. This improves user experience (one login) and security (central point to enforce password policies, multi-factor authentication).

- **OAuth2 Tokens:** After authentication, each client (Mobile App, web UI, or microservice) receives a time-limited OAuth2 access token. These tokens must be presented to call any API in the system, and they carry scopes/roles that determine authorization. For example, a token for a Citizen user will allow access only to citizen-level data (their own data or public data), whereas a City Planner's token allows access to simulation controls and results. This ensures fine-grained **access control** – if a token is used to request something outside the user's privileges, the request is denied.

- **Role-Based Access Control (RBAC):** Users are assigned roles (Citizen, Planner, etc.), and possibly additional attributes (like which city or district they belong to, or if they are an admin). The platform's services check these roles before performing actions. For instance, only users with the "Planner" role can launch new simulations, and only "External Stakeholder" role accounts tied to partner organizations can pull data from the repository. Keycloak can also handle groups and attributes, enabling flexible policy definition (e.g., give a certain planner access only to a subset of scenarios).

- **Service Authentication:** Beyond human users, certain containers authenticate as services. The **AI Analytics** and **District Optimization** components use service accounts in Keycloak to obtain tokens, which they include when fetching data from other services (like S3 or pattern

repository). This means all inter-service calls are also authenticated and authorized, which is crucial in a distributed microservice architecture – no module blindly trusts another, they must present valid credentials.

Data Security (Encryption and Anonymization):

- **Encryption in Transit:** All communication between components, especially across network boundaries, is encrypted using TLS. The Mobile App communicates with backend APIs over HTTPS; MQTT communication from sensors can use secure MQTT (MQTT over TLS) to protect data in transit; Kafka can be configured with SSL encryption for its brokers as well. This prevents eavesdropping on sensitive information (like building energy data or user credentials).

- **Encryption at Rest:** Sensitive data stored in databases or object storage will be encrypted at rest. For example, if S3 Storage is backed by a cloud storage service or local server, encryption keys are used so that if someone were to get access to the raw storage, they couldn't read the content without keys. This is particularly important for backups or archives of simulation results that might contain personal data or strategic city data.

- **Data Anonymization and Minimization:** The architecture has multiple points where data is anonymized:

    - When ingesting sensor data, any personal identifiers (like if a sensor is tied to a person or a specific apartment) can be replaced with generic IDs. The ThingsBoard platform supports attributing data to device IDs that need not reveal the occupant's identity. Kafka topics are organized by function (not by person), and the data fusion engine can combine data in such a way that individual profiling is avoided.

    - Results outputs and logs are scanned for privacy. For example, if a simulation result includes a list of households that did not meet a goal, the system would instead aggregate or mask that information in any publicly viewable context.

    - The platform employs **Privacy-by-Design**: only data that is needed for the functionality is collected and stored. Citizens using the Mobile App, for instance, might be tracked only by a user ID and not by name in analytical records. They have transparency on what data they share (the app might inform them that their feedback and energy usage will be used in analysis, for instance).

    - The requirements explicitly mention GDPR compliance, so mechanisms like user consent, ability to delete personal data, and data retention limits are built in. If a citizen decides to withdraw, their personal data can be purged from the system easily due to centralized identity management and data tagging.

- **Secure Data Exchange:** The Dataspaces Connector ensures that any data leaving the platform to external parties is governed by usage policies. It likely uses secure protocols like HTTPS or IDS protocols with encryption. Moreover, it could implement **usage control** where data is not just sent out, but agreements on its use are enforced (some data space technologies allow licenses to be attached to data).

Network and Infrastructure Security:

- The platform components are mostly containerized and deployed in a controlled environment. Standard cloud security applies: firewalls restrict access between components (for instance, the database is not accessible from outside, only the application servers can talk to it), and only necessary ports are open (e.g., 443 for HTTPS, maybe 8883 for secure MQTT, etc.).

- Kafka and other internal components are on a protected network. If the project deploys on Kubernetes or VMs, internal network segmentation is used to prevent an attacker who might breach one container from easily moving laterally to others.

- Regular security audits and vulnerability scanning of components (Keycloak, Kafka, ThingsBoard, etc.) are performed to patch any known issues, given these are popular open-source components.

Resilience and Backup: Security also encompasses availability. The architecture is designed to be resilient:

- Redundant instances of critical services (Kafka cluster nodes, possibly redundant Keycloak nodes, etc.) ensure no single point of failure. This prevents denial of service if one component goes down.

- Data backups are taken for configurations and stored data (with encryption). For example, the simulation results in S3 might be backed up to a secondary storage or the pattern repository database is regularly backed up. Disaster recovery plans exist to restore functionality in case of a major failure.

Audit and Accountability: Every action can be logged:

- Keycloak logs authentications and token usage.

- The platform can log who accessed which simulation results or who triggered what scenario. These logs are crucial for audits (e.g., to ensure only authorized actions are happening) and also for forensic analysis in case of an incident.

- This aligns with accountability requirements and also helps in generating reports for the project on usage statistics (ensuring those reports are themselves privacy-compliant).

Compliance with Regulations: Besides GDPR, the platform keeps an eye on **AI ethics and upcoming regulations**. So, if AI models are used in decision support, the system would log the rationale or main factors (to avoid black-box decisions without explanation). There might be a feature for planners to see why the optimization engine recommended a certain action (e.g., "because it reduces CO_2 by X and costs only Y"). This transparency is both an ethical consideration and might become a legal one under AI regulations.

Additionally, **open security standards** are followed (like OAuth2/OIDC for authentication, TLS 1.3 for encryption, etc.), which ensures the platform's security isn't relying on obscure or custom methods. The use of widely-vetted security components (Keycloak is a well-known IDM solution, Kafka has enterprise-grade security features, etc.) increases trust in the system's security.

In the context of sensor data, a specific privacy measure: since building energy data can reveal personal habits (like when someone is home), EXPEDITE aggregates such data at a level (e.g., building or block

level) when used in public-facing visualizations. Only authorized building managers would see device-level data. This way, detailed raw data is kept confidential, and higher-level insights are shared.

Finally, **physical security** of sensors is noted: the guidelines ensure that sensors deployed are tamper-evident or at least, the system can detect anomalies (a sudden drop to zero might indicate a sensor was removed). While this is more of a deployment detail, it complements the cybersecurity aspect by ensuring data trustworthiness.

All these considerations illustrate that security and privacy are woven into the architecture. By meeting HLR-5 (privacy & security) and more, the EXPEDITE project not only protects data and users but also builds credibility with stakeholders (especially city authorities and citizens, who need confidence that the digital twin won't leak sensitive information or be misused).

The architecture's emphasis on using established solutions and standards for security means it can be **federated or integrated** with city-wide security systems too. For example, if the city has an existing identity provider, Keycloak could federate with it (so city staff use their existing credentials to log in). This flexibility is valuable for integration in a real operational environment post-project.

In summary, the EXPEDITE system is engineered to be secure by design and privacy-aware, ensuring that while it aggregates vast amounts of city data and provides powerful tools, it does so in a way that respects individual privacy and safeguards against cyber threats. This comprehensive approach to security aligns with best practices for critical smart city infrastructure and will be continuously evaluated as the project progresses (including through external security tests and compliance checks).

Overall, the EXPEDITE project's system architecture provides a robust and flexible foundation for realizing a Digital Twin platform for Positive Energy Districts. Through this detailed overview, we have seen how the platform's design brings together real-time sensor integration, advanced simulation engines, data analytics, and user-centric interfaces into a cohesive ecosystem. The architecture is characterized by clear modularization – each component (whether it's DT Design Time, a simulation tool, or a data connector) has well-defined responsibilities and interfaces, which simplifies development, testing, and future enhancements.

A few key takeaways and concluding points:

- **Holistic Design:** The architecture not only meets technical requirements but also aligns with the broader objectives of stakeholder engagement and sustainability. By including components like the Mobile App for citizens and the Economic Impact tool for financial analysis, EXPEDITE ensures that the Digital Twin addresses the problem from all angles (technical, social, economic).

- **Interoperability and Standards:** A major strength of the system is its adherence to interoperability standards (MIMs). This will facilitate replication of the solution in other cities and integration with external initiatives. The use of open data models and standard APIs means EXPEDITE can easily evolve to become part of a larger "federation" of city digital twins or integrate additional modules (for example, a new AI service) with minimal friction.

- **Scalability and Future-Proofing:** The choice of technologies like Apache Kafka, S3, and containerized microservices implies the system can scale to handle large data volumes and user loads. New sensors or simulation modules can be added without restructuring the core. The architecture is also cloud-ready, meaning it can leverage cloud infrastructure to dynamically scale resources (useful if a very large simulation is run or if the user base grows). This future-

proofing is important given that cities are dynamic and data sources will only increase over time.

- **Security and Trust:** By embedding strong security measures, the architecture lays the groundwork for a platform that city authorities and users can trust. This is crucial for acceptance – city planners will rely on the system's recommendations for real decisions, and they need confidence in the data and algorithms. Likewise, citizens will engage only if they trust their data is safe. EXPEDITE's design addresses these trust factors head-on, which will aid in its adoption and longevity.

- **Compliance and Requirements Traceability:** As demonstrated, every major requirement is traceable to an architectural element. This comprehensive coverage reduces project risk: it is less likely that a critical requirement was overlooked in design. It also provides a clear roadmap for implementation teams to follow, since they know exactly which component addresses which need. This document can serve as a reference during development, testing, and validation phases (for instance, test cases can be derived to verify that FR and NFR expectations are met by the implemented components).

- **Innovation in Urban Planning:** The EXPEDITE system represents an innovative merging of urban planning, IoT, and AI. By enabling scenario planning with real-time feedback, it transforms how planning departments might approach policy-making – moving from static master plans to dynamic, data-driven strategies. The architecture supports iterative learning: as the city implements changes and gathers new data, the digital twin becomes smarter and more accurate, creating a positive feedback loop for continuous improvement of the district.

Moving forward, the focus will shift to implementation and deployment in pilot sites, where the architecture will be validated in real-world conditions. The modular nature will allow parts of the system to be developed in parallel by different partners (as indicated by contributions from NTUA, PLEGMA, etc., in the deliverable context). Regular integration testing will ensure these modules work together as depicted.

5. Conclusions

This deliverable has defined the system architecture, interoperability mechanisms, and sensor integration guidelines for the ExPEDite platform, laying the technical foundation for its implementation in real-world urban environments. The proposed architecture is modular, layered, and standards-aligned, enabling a flexible and interoperable platform to support Digital Twins in Positive Energy Districts. Built upon the general requirements identified in D2.1, it translates those needs into actionable, deployable components while ensuring alignment with broader European frameworks such as the -in.EU MIMs Plus, NGSI-LD standards, and the LDT Toolbox.

A core emphasis of the deliverable is on interoperability. The Minimum Interoperability Mechanisms (MIMs) — MIM1 (Context Information), MIM2 (Data Models), and MIM3 (Contracts) — are carefully mapped to key elements of the system architecture. MIM1 enables dynamic exchange of urban context data, while MIM2 ensures that shared data structures maintain semantic coherence across diverse applications. Although MIM3 remains under active evolution in the broader European context, a pragmatic and simplified approach is proposed for ExPEDite to support service contracts and ecosystem interaction patterns. Together, these mechanisms form the basis for seamless data and service interoperability across tools, partners, and cities.

The system architecture itself is defined as a set of interrelated components deployed across multiple layers. It includes tools for design-time Digital Twin configuration, a runtime engine for data ingestion and real-time visualization, and a backend stack incorporating context brokers, access control, file storage, and messaging infrastructure. The system is capable of integrating analytics pipelines, AI models, and visualization dashboards, while ensuring loose coupling and open interfaces to support component independence and reuse. Each component is described in terms of function, interfaces, and partner responsibility, supporting traceable and coordinated development across the consortium.

In addition to system-level design, the deliverable provides detailed technical guidelines for sensor integration. These cover how environmental, mobility, and building sensors can be onboarded into the platform, harmonized using metadata standards, and synchronized with contextual data layers. The approach promotes semantic alignment, temporal consistency, and extensibility across sensor types, ensuring that urban data streams can be effectively used within the Digital Twin ecosystem.

Throughout the deliverable, several guiding principles are reinforced: pragmatism in design to support rapid deployment, modularity to allow flexible integration, openness through standards and APIs, and scalability to support long-term, cross-city replication. Identity and access management are also addressed using token-based mechanisms and secure interfaces, ensuring data governance and privacy at the system level.

This deliverable represents a critical bridge between high-level functional needs and technical execution. It enables work packages focused on implementation (WP3), validation (WP4), and analytics (WP5) to build on a common, robust architecture. It also provides pilot cities with a concrete blueprint for deployment and system configuration. Looking ahead, future work will involve refining interfaces, implementing the system in pilot contexts, and aligning more tightly with European Data Space initiatives and conformance testing tools. This architecture will evolve through iterative deployment, feedback, and collaboration, but its foundations — as laid out here — ensure that ExPEDite is technically sound, future-proof, and adaptable to the needs of cities across Europe.

6. References

[1] N. Alharbi and B. Soh, “Roles and Challenges of Network Sensors in Smart Cities,” *IOP Conf. Ser.: Earth Environ. Sci.,* vol. 322, p. 012002, August 2019.

[2] FPGA Insights, "Empowering Smart Cities: Energy Management for Sustainable Futures," January 2024. [Online]. Available: https://fpgainsights.com/power-management/empowering-smart-cities-energy-management-for-sustainable-futures/#:~:text=Energy%20management%20in%20smart%20cities%20involves%20the%20integration%20of%20renewable,fuels%20and%20decrease%20carbon%20emissions..

[3] S. Latif, H. Afzaal and N. A. Zafar, "Intelligent traffic monitoring and guidance system for smart city," in *2018 International Conference on Computing, Mathematics and Engineering Technologies (iCoMET)*, 2018.

[4] X. Song, C. Wang, M. Kagawa and V. Raghavan, "Real-time monitoring portal for urban environment using sensor web technology," in *2010 18th International Conference on Geoinformatics*, 2010.

[5] MIT Technology Review, “The Role of Sensors in Smart Cities,” [Online]. Available: https://www.appliedtechnologyreview.com/news/the-role-of-sensors-in-smart-cities--nwid-1703.html.

[6] A. Nath Baruah, M. S. Akkur, J. Seth and J. Shah, "Integrating sensor networks to facilitate efficient energy management for smart grids," *Measur. Sens.,* vol. 36, p. 101393, December 2024.

[7] P. Pandiyan, S. Saravanan, K. Usha, R. Kannadasan, M. H. Alsharif and M.-K. Kim, "Technological advancements toward smart energy management in smart cities," *Energy Rep.,* vol. 10, p. 648–677, November 2023.

[8] C. Mahapatra, A. K. Moharana and V. C. M. Leung, "Energy management in smart cities based on internet of things: Peak demand reduction and energy savings," *Sensors (Basel),* vol. 17, December 2017.

[9] P. A. Fokaides, R. Apanaviciene and E. Klumbyte, “5.12 Energy Management in Smart Cities,” in *Comprehensive Energy Systems*, Elsevier, 2018, p. 457–473.

[10] A. Swain, S. R. Salkuti and K. Swain, "An optimized and decentralized energy provision system for smart cities," *Energies,* vol. 14, p. 1451, March 2021.

[11] U. ur Rehman, P. Faria, L. Gomes and Z. Vale, "Future of energy management systems in smart cities: A systematic literature review," *Sustain. Cities Soc.,* vol. 96, p. 104720, September 2023.

[1 2] C. L. Dewangan, V. Vijayan, D. Shukla, S. Chakrabarti, S. N. Singh, A. Sharma and M. A. Hossain, "An improved decentralized scheme for incentive-based demand response from residential customers," *Energy (Oxf.),* vol. 284, p. 128568, December 2023.

[1 3] M. Kilthau, V. Henkel, L. P. Wagner, F. Gehlhoff and A. Fay, "A decentralized optimization approach for scalable agent-based energy dispatch and congestion management," *Appl. Energy,* vol. 377, p. 124606, January 2025.

[1 4] CNN, "Singapore is building a 42,000-home eco 'smart' city," February 2021. [Online]. Available: https://www.cnn.com/style/article/singapore-tengah-eco-town/index.html.

[1 5] evoVIU, "5 real-life smart city examples," June 2024. [Online]. Available: https://www.evoviu.de/en/object-recognition-with-machine-vision/.

[1 6] L. Xiao, X. Peng, Z. Wang, B. Xu and P. Hong, "Research on traffic monitoring network and its traffic flow forecast and congestion control model based on wireless sensor networks," in *2009 International Conference on Measuring Technology and Mechatronics Automation*, 2009.

[1 7] I. Semanjski, S. Mandzuka and S. Gautama, "Smart Mobility," in *2018 International Symposium ELMAR*, 2018.

[1 8] T. Alam, "Cloud-based IoT applications and their roles in smart cities," *Smart Cities,* vol. 4, p. 1196–1219, September 2021.

[1 9] D. Oladimeji, K. Gupta, N. A. Kose, K. Gundogan, L. Ge and F. Liang, "Smart transportation: An overview of technologies and applications," *Sensors (Basel),* vol. 23, p. 3880, April 2023.

[2 0] B. Lenz and D. Heinrichs, "What can we learn from smart urban mobility technologies?," *IEEE Pervasive Comput.,* vol. 16, p. 84–86, April 2017.

[2 1] C. F. Calvillo, A. Sánchez-Miralles and J. Villar, "Energy management and planning in smart cities," *Renew. Sustain. Energy Rev.,* vol. 55, p. 273–287, March 2016.

[2 2] M. Matyakubov and O. Rustamova, "Development of smart city model: Smart bus system," in *2019 International Conference on Information Science and Communications Technologies (ICISCT)*, 2019.

[2 3] D. Vakula and B. Raviteja, "Smart public transport for smart cities," in *2017 International Conference on Intelligent Sustainable Systems (ICISS)*, 2017.

[2 4] R. Wolniak and W. Grebski, "Smart mobility in smart city – Singapore and Tokyo comparison," *Sci. Pap. Sil. Univ. Technol. Organ. Manag. Ser.,* vol. 2023, 2023.

[2 5] C. Toma, A. Alexandru, M. Popa and A. Zamfiroiu, "IoT solution for smart cities' pollution monitoring and the security challenges," *Sensors (Basel),* vol. 19, p. 3401, August 2019.

[26] J. Kalajdjieski, B. R. Stojkoska and K. Trivodaliev, "IoT based framework for air pollution monitoring in smart cities," in *2020 28th Telecommunications Forum (TELFOR)*, 2020.

[27] Q. S. Zhang, “Environment pollution analysis on smart cities using wireless sensor networks,” *Strateg. Plan. Energy Environ.,* December 2022.

[28] L. Chandana and A. Sekhar, “Weather monitoring using wireless sensor networks based on IOT,” *International Journal of Scientific Research in Science and Technology,* vol. 4, p. 525–531, March 2018.

[29] S. Shamsir, I. Mahbub, S. K. Islam and A. Rahman, "Applications of sensing technology for smart cities," in *2017 IEEE 60th International Midwest Symposium on Circuits and Systems (MWSCAS)*, 2017.

[30] A. Hörman and C. Robild, “A Quantitative Investigation into IoT-Based Weather Stations,” [Online]. Available: https://researchportal.hkr.se/ws/portalfiles/portal/43902489/FinalThesis_H_rman_Robild.pdf.

[31] Barani Design, "Can IoT weather stations send data every 10 minutes and comply with wireless regulations —," April 2019. [Online]. Available: https://www.baranidesign.com/faq-articles/2019/3/26/can-iot-weather-stations-send-data-every-10-minutes-and-comply-with-wireless-regulations.

[32] Wevolver, “Tech for the Planet: IoT Innovations in Environmental Monitoring and Disaster Management,” June 2024. [Online]. Available: https://www.wevolver.com/article/tech-for-the-planet-iot-innovations-in-environmental-monitoring-and-disaster-management?utm_source=chatgpt.com.

[33] A. Zanella, N. Bui, A. Castellani, L. Vangelista and M. Zorzi, "Internet of things for smart cities," *IEEE Internet Things J.,* vol. 1, p. 22–32, February 2014.

[34] J. M. Navarro, J. B. Tomas-Gabarron and J. Escolano, “A big data framework for urban noise analysis and management in smart cities,” *Acta Acust. United Acust.,* vol. 103, p. 552–560, July 2017.

[35] S. Kumari, A. Sharma and A. K. Ghosh, "A comprehensive review of noise pollution monitoring studies at bus transit terminals," *Noise Mapp.,* vol. 11, February 2024.

[36] L. Filipponi, S. Santini and A. Vitaletti, “Data collection in wireless sensor networks for noise pollution monitoring,” in *Distributed Computing in Sensor Systems*, Berlin, Heidelberg: Springer Berlin Heidelberg, 2008, p. 492–497.

[37] European Commission, “The making of a smart city,” [Online]. Available: https://smart-cities-marketplace.ec.europa.eu/sites/default/files/2021-04/the_making_of_a_smart_city_-_best_practices_across_europe.pdf.

[38] J. M. R. S. Tavares, C. Karri, J. J. M. Machado, D. K. Jain, S. Dannana, S. K. Gottapu and A. H. Gandomi, "Recent technology advancements in smart city management: A review," *Comput. Mater. Contin.,* vol. 81, p. 3617–3663, 2024.

[39] S. Yli-Kauhaluoma, M. Statheropoulos, A. Zygmanowski, O. Anttalainen, H. Hakulinen, M. T. Kontogianni, M. Kuula, J. Pernaa and P. Vanninen, "Safe city: A study of channels for public warnings for emergency communication in Finland, Germany, and Greece," *Multimodal Technol. Interact.,* vol. 7, p. 94, October 2023.

[40] A. U. R. Butt, T. Saba, I. Khan, T. Mahmood, A. R. Khan, S. K. Singh, Y. I. Daradkeh and I. Ullah, "Proactive and data-centric Internet of Things-based fog computing architecture for effective policing in smart cities," *Comput. Electr. Eng.,* vol. 123, p. 110030, April 2025.

[41] W.-H. Lee and C.-Y. Chiu, "Design and implementation of a smart traffic signal control system for smart city applications," *Sensors (Basel),* vol. 20, p. 508, January 2020.

[42] S. Khemakhem and L. Krichen, "A comprehensive survey on an IoT-based smart public street lighting system application for smart cities," *Franklin Open,* vol. 8, p. 100142, September 2024.

[43] Nearby Computing, "Smart Cities Emergency Response," March 2023. [Online]. Available: https://www.nearbycomputing.com/smart-cities-emergency-response/.

[44] Wikipedia, “Mass surveillance,” January 2025. [Online]. Available: https://en.wikipedia.org/wiki/Mass_surveillance.

[45] Wikipedia, “Domain Awareness System,” February 2025. [Online]. Available: https://en.wikipedia.org/wiki/Domain_Awareness_System.

[46] I. Jawhar, N. Mohamed and J. Al-Jaroodi, "Networking architectures and protocols for smart city systems," *J. Internet Serv. Appl.,* vol. 9, p. 1–16, December 2018.

[47] D. Kanellopoulos, V. K. Sharma, T. Panagiotakopoulos and A. Kameas, "Networking architectures and protocols for IoT applications in smart cities: Recent developments and perspectives," *Electronics (Basel),* vol. 12, p. 2490, May 2023.

[48] D. Dobrilovic, "Networking technologies for smart cities: An overview," *Interdiscip. Descr. Complex Syst.,* vol. 16, p. 408–416, 2018.

[49] M. Cesana and A. E. C. Redondi, “IoT Communication Technologies for Smart Cities,” in *Designing, Developing, and Facilitating Smart Cities*, Cham, Springer International Publishing, 2017, p. 139–162.

[50] LoRaWan Sector Report Series, "Leveraging LoRaWAN for Smart Cities," October 2024. [Online]. Available: https://lpwaninfo.com/smart-cities/.

[51] A. Khalifeh, K. A. Darabkh, A. M. Khasawneh, I. Alqaisieh, M. Salameh, A. AlAbdala, S. Alrubaye, A. Alassaf, S. Al-HajAli, R. Al-Wardat, N. Bartolini, G. Bongiovannim and K.

Rajendiran, "Wireless Sensor Networks for smart cities: Network design, implementation and performance evaluation," *Electronics (Basel),* vol. 10, p. 218, January 2021.

[52] I. Jawhar, N. Mohamed and J. Al-Jaroodi, "Networking and communication for smart city systems," in *2017 IEEE SmartWorld, Ubiquitous Intelligence & Computing, Advanced & Trusted Computed, Scalable Computing & Communications, Cloud & Big Data Computing, Internet of People and Smart City Innovation (SmartWorld/SCALCOM/UIC/ATC/CBDCom/IOP/SCI)*, 2017.

[53] Gunjan Mittal Roy, Dr. Sambhavi Shukla, Dr. Damyanti Singh, "Wireless Technology for Smart Cities and Urban Planning," *Sensors (Basel),* vol. 17, June 2017.

[54] L. Garcia, J. M. Jiménez, M. Taha and J. Lloret, "Wireless Technologies for IoT in Smart Cities," *Netw. Protoc. Algorithm.,* vol. 10, p. 23, April 2018.

[55] A. Mannan, M. Bader, U. Hijawi, A. Gastli and R. Hamila, "Mesh network-based device-to-device negotiation system for energy management," in *2021 18th International Multi-Conference on Systems, Signals & Devices (SSD)*, 2021.

[56] S. Mamechaoui, S. M. Senouci, F. Didi and G. Pujolle, "Energy efficient management for wireless mesh networks with green routers," *Mob. Netw. Appl.,* vol. 20, p. 567–582, October 2015.

[57] J. Rezgui and W. Benrhaiem, "Hierarchical cloud communication for supply management and power distribution via wireless mesh network into the smart grid," in *2018 International Symposium on Networks, Computers and Communications (ISNCC)*, 2018.

[58] R. Massobrio and O. Cats, "Topological assessment of recoverability in public transport networks," *Commun. Phys.,* vol. 7, p. 1–9, March 2024.

[59] X. Zhang, E. Miller-Hooks and K. Denny, "Assessing the role of network topology in transportation network resilience," *J. Transp. Geogr.,* vol. 46, p. 35–45, June 2015.

[60] L. Siddiqui, "Network Topology: The Complete Guide," [Online]. Available: https://www.splunk.com/en_us/blog/learn/network-topology.html.

[61] Y. Xiao, Z. Zhong and R. Sun, "Analysis of topological properties and robustness of urban public transport networks," *Sustainability,* vol. 16, p. 6527, July 2024.

[62] R. Jurdak, "The impact of cost and network topology on urban mobility: a study of public bicycle usage in 2 U.S. cities," *PLoS One,* vol. 8, p. e79396, November 2013.

[63] M. Abd-El-Barr and T. F. Al-Somani, "Topological properties of Hierarchical Interconnection Networks: A review and comparison," *J. Electr. Comput. Eng.,* vol. 2011, p. 1–12, January 2011.

[64] J. Liu, "Design of remote environmental monitoring network based on intelligent sensor network address allocation and addressing," *J. Sens.,* vol. 2021, p. 1–9, January 2021.

[65] R. M. Woo-García, J. M. Pérez-Vista, A. Sánchez-Vidal, A. L. Herrera-May, E. Osorio-de-la-Rosa, F. Caballero-Briones and F. López-Huerta, "Implementation of a wireless sensor network for environmental measurements," *Technologies (Basel),* vol. 12, p. 41, March 2024.

[66] J. Marais, R. Malekian, N. Ye and R. Wang, "A review of the topologies used in smart water meter networks: A wireless sensor network application," *J. Sens.,* vol. 2016, p. 1–12, January 2016.

[67] A. S. Syed, D. Sierra-Sosa, A. Kumar and A. Elmaghraby, "IoT in Smart Cities: A survey of technologies, practices and challenges," *Smart Cities,* vol. 4, p. 429–475, March 2021.

[68] A. Musa, *A proposed network topology for low cost scenarios in a large scale network within a smart city.*

[69] X. Huang, "Multi-node topology location model of smart city based on Internet of Things," *Comput. Commun.,* vol. 152, p. 282–295, February 2020.

[70] A. Ometov, S. Bezzateev, N. Voloshina, P. Masek and M. Komarov, "Environmental monitoring with distributed mesh networks: An overview and practical implementation perspective for urban scenario," *Sensors (Basel),* vol. 19, p. 5548, December 2019.

[71] P. Fraga-Lamas, T. M. Fernández-Caramés, M. Suárez-Albela, L. Castedo and M. González-López, "A review on Internet of Things for defense and Public Safety," *Sensors (Basel),* vol. 16, p. 1644, October 2016.

[72] K. Papanikolaou, *What Is Network Redundancy?,* EMnify GmbH, 2021.

[73] Eseye, "Why Network Redundancy is Critical for IoT," December 2023. [Online]. Available: https://www.eseye.com/resources/blogs/critical-iot-network-redundancy/.

[74] D. P. Abreu, K. Velasquez, M. Curado and E. Monteiro, "A resilient Internet of Things architecture for smart cities," *Ann. Telecommun.,* vol. 72, p. 19–30, February 2017.

[75] E. Serra, “Redundancy as a Measure of Fault-Tolerance for the Internet of Things: A Review,” *Policy-Based Autonomic Data Governance,* January 2019.

[76] P. Vedavalli and C. Deepak, "Enhancing reliability and fault tolerance in IoT," in *2020 International Conference on Artificial Intelligence and Signal Processing (AISP)*, 2020.

[77] J. P. G. Sterbenz, "Smart city and IoT resilience, survivability, and disruption tolerance: Challenges, modelling, and a survey of research opportunities," in *2017 9th International Workshop on Resilient Networks Design and Modeling (RNDM)*, 2017.

[78] A. Pliatsios, C. Goumopoulos and K. Kotis, “A review on IoT frameworks supporting multi-level interoperability – the Semantic Social Network of Things framework,” 2020.

[7 M. Elkhodr, S. Shahrestani and H. Cheung, “The Internet of Things: New interoperability,
9] management and security challenges,” *arXiv [cs.NI],* April 2016.

[8 A. Ghobakhlou, A. Kmoch and P. Sallis, “Integration of wireless sensor network and web services,”
0] 2013.

[8 G. Pau and F. Arena, "Smart City: The different uses of IoT sensors," *J. Sens. Actuator Netw.,* vol.
1] 11, p. 58, September 2022.

[8 J. Koo and Y.-G. Kim, "Interoperability requirements for a smart city," in *Proceedings of the 36th*
2] *Annual ACM Symposium on Applied Computing*, New York, NY, USA, 2021.

[8 D. M. Dave and B. K. Mittapally, “Data Integration and Interoperability in IOT: Challenges,
3] Strategies and Future Direction,” *INTERNATIONAL JOURNAL OF COMPUTER ENGINEERING & TECHNOLOGY,* vol. 15, p. 45–60, January 2024.

[8 F. Zeng, C. Pang and H. Tang, "Sensors on Internet of Things systems for the sustainable
4] development of smart cities: A systematic literature review," *Sensors (Basel),* vol. 24, p. 2074, March 2024.

[8 J. D. Cruz, P. Garcia, L. Hernandez, M. Tan, M. Santos and A. Reyes, “Integrating IoT sensors for
5] enhanced smart city data streams recognition,” February 2025.

[8 A. Jindal, N. Kumar and M. Singh, “A Unified Framework for Big Data Acquisition, Storage,”
6] *Future Generation Computer Systems,* 2018.

[8 K. Skiadopoulos, A. Tsipis, K. Giannakis, G. Koufoudakis, E. Christopoulou, K. Oikonomou, G.
7] Kormentzas and I. Stavrakakis, "Synchronization of data measurements in wireless sensor networks for IoT applications," *Ad Hoc Netw.,* vol. 89, p. 47–57, June 2019.

[8 B. Sadler and A. Swami, "Synchronization in sensor networks: An overview," in *MILCOM 2006*,
8] 2006.

[8 W. Li, X. Chen and S. Lu, "Content synchronization using device-to-device communication in
9] smart cities," *Comput. Netw.,* vol. 120, p. 170–185, June 2017.

[9 D. Djenouri and M. Bagaa, "Synchronization protocols and implementation issues in wireless
0] sensor networks: A review," *IEEE Syst. J.,* vol. 10, p. 617–627, June 2016.

[9 M. U. Hashmi, M. Hussain, A. A. Shah, M. Babar and B. Qureshi, "Synchronizing smart city nodes
1] using Skew Integrated Timestamp (SIT)," *PeerJ Comput. Sci.,* vol. 10, p. e2049, May 2024.

[9 E. Murrell, "What Is Network Infrastructure and Why Is It Important?," April 2024. [Online].
2] Available: https://nybsys.com/what-is-network-infrastructure/.

[9 A. Presher, *Ethernet Advanced Physical Layer for process control,* 2020.
3]

[94] J. Miley, “The Future of Wired Communication Infrastructure: Single Pair Ethernet,” September 2020. [Online]. Available: https://www.wevolver.com/article/the-future-of-wired-communication-infrastructure-single-pair-ethernet.

[95] A. Banathy, “Down to the Wire – Building a Resilient Network Infrastructure,” [Online]. Available: https://www.panduit.com/content/dam/panduit/en/landing-page-pdf2/Down_to_the_Wire_Article.pdf.

[96] M. Piechowiak, P. Zwierzykowski and B. Musznicki, "LoRaWAN metering infrastructure planning in smart cities," *Appl. Sci. (Basel),* vol. 13, p. 8431, July 2023.

[97] R. Mattiol and K. Moulinos, “Communication Network Interdependencies in Smart Grids,” [Online]. Available: https://www.enisa.europa.eu/sites/default/files/all_files/Methodology%20for%20the%20identification%20of%20Critical%20Communication%20Networks%20Links%20and%20Components%20-%20Annexes.pdf.

[98] Farnell, "Designing hybrid systems: combining wired and wireless communication," [Online]. Available: https://si.farnell.com/designing-hybrid-systems-combining-wired-and-wireless-communication-trc-ar.

[99] L. Pavithra, M. Abdullah, S. P. Prakash, S. Karthick, B. Ragavi and V. D. Nandhini, “Wireless Sensor Networks: A Review on Sensor Deployment and Routing Protocols for Different Application,” *IOP Conf. Ser.: Mater. Sci. Eng.,* vol. 1084, p. 012052, March 2021.

[100] H. M. Abdulwahid and A. Mishra, "Deployment optimization algorithms in wireless sensor networks for smart cities: A systematic mapping study," *Sensors (Basel),* vol. 22, p. 5094, July 2022.

[101] Monolithic Power, "Challenges in Sensor Deployment," [Online]. Available: https://www.monolithicpower.com/en/learning/mpscholar/sensors/sensor-design-interfacing-and-challenges/challenges-in-sensor-deployment.

[102] S. Faye and C. Chaudet, “Connectivity analysis of wireless sensor networks deployments in smart cities,” in *2015 IEEE Symposium on Communications and Vehicular Technology in the Benelux (SCVT)*, 2015.

[103] S. Abdollahzadeh and N. J. Navimipour, "Deployment strategies in the wireless sensor network: A comprehensive review," *Comput. Commun.,* Vols. 91-92, p. 1–16, October 2016.

[104] S. Xiong, L. Yu, H. Shen, C. Wang and W. Lu, "Efficient algorithms for sensor deployment and routing in sensor networks for network-structured environment monitoring," in *2012 Proceedings IEEE INFOCOM*, 2012.

[105] J. Beutel, K. Römer, M. Ringwald and M. Woehrle, “Deployment techniques for sensor networks,” in *Signals and Communication Technology*, Berlin, Heidelberg: Springer Berlin Heidelberg, 2010, p. 219–248.

[106] Ultra Energy, "Temperature sensors for harsh environment conditions," [Online]. Available: https://www.ultra.energy/resources/blog/how-do-i-select-a-temperature-sensor-for-harsh-environment-conditions/.

[107] Monnit, "Environmental Factors Affecting Sensors," [Online]. Available: https://support.monnit.com/article/295-environmental-factors-affecting-sensors.

[108] A. Keshmiry, S. Hassani, M. Mousavi and U. Dackermann, "Effects of environmental and operational conditions on Structural Health Monitoring and Non-Destructive Testing: A systematic review," *Buildings,* vol. 13, p. 918, March 2023.

[109] A. Zabasta, J. Skirelis, A. Patlins, N. Kunicina and A. Romanovs, "Wireless Sensor Networks: Towards Resilience Against Weather-Based Disruptions," *Sciendo,* vol. 15, no. 2, p. 79–87, January 2019.

[110] J. Delsing, J. Ekman, J. Johansson, S. Sundberg, M. Backstrom and T. Nilsson, "Susceptibility of sensor networks to intentional electromagnetic interference," in *2006 17th International Zurich Symposium on Electromagnetic Compatibility*, 2006.

[111] A. Dudnik, B. Presnall, M. Tyshchenko and O. Trush, "Methods of determining the influence of physical obstructions on the parameters of the signal of wireless networks," p. 227–240, 2021.

[112] O. O. C. A. I. ANALYSIS, "Cyber-Physical Infrastructure Risk, 2015," [Online]. Available: https://www.cisa.gov/sites/default/files/documents/OCIA%20-%20The%20Future%20of%20Smart%20Cities%20-%20Cyber-Physical%20Infrastructure%20Risk.pdf.

[113] K. Tzortzakis, K. Papafotis and P. P. Sotiriadis, "Wireless self powered environmental monitoring system for smart cities based on LoRa," in *2017 Panhellenic Conference on Electronics and Telecommunications (PACET)*, 2017.

[114] M. Lauridsen, I. Z. Kovacs, P. Mogensen, M. Sorensen and S. Holst, "Coverage and Capacity Analysis of LTE-M and NB-IoT in a Rural Area," in *2016 IEEE 84th Vehicular Technology Conference (VTC-Fall)*, 2016.

[11] L. H. Le, D. T. Nguyen, H. P. Bui, C. C. Nguyen and T. Q. Ngo, "Integration of modbus Ethernet communication for real-time electrical power consumption, temperature, and humidity monitoring system," *Research Square,* August 2024.

[116] IEEE Public Safety Technology, "Smart City Integration: How IoT is Reducing Emergency Response Times and Saving Lives," [Online]. Available: https://publicsafety.ieee.org/topics/smart-city-integration-how-iot-is-reducing-emergency-response-times-and-saving-lives.

[117] S. F. Nazim, M. S. S. Danish and T. Senjyu, "A brief review of the future of smart mobility using 5G and IoT," *J Sustainability Outreach,* vol. 3, p. 19–30, June 2022.

[18] J. A. Rodriguez-Gil, E. Mojica-Nava, D. Vargas-Medina, M. F. Arevalo-Castiblanco, C. A. Cortes, S. Rivera and J. Cortes-Romero, "Energy management system in networked microgrids: an overview," *Energy Syst.,* p. 1–32, July 2024.

[19] F. G. Brundu, E. Patti, A. Osello, M. D. Giudice, N. Rapetti, A. Krylovskiy, M. Jahn, V. Verda, E. Guelpa, L. Rietto and A. Acquaviva, "IoT Software Infrastructure for Energy Management and Simulation in Smart Cities," *IEEE Trans. Industr. Inform.,* vol. 13, p. 832–840, April 2017.

[20] B. Nordman, L. Harrington and B. Harrison, "Prioritising energy management protocols in standards for networked products," [Online]. Available: https://iea.blob.core.windows.net/assets/imports/events/257/13IEANSsession62final.pdf.

[21] S. N. Islam and M. A. Mahmud, "Communication protocol design for IoT-enabled energy management in a smart microgrid," *Appl. Sci. (Basel),* vol. 15, p. 1773, February 2025.

[22] M. I. El-Afifi, B. E. Sedhom, S. Padmanaban and A. A. Eladl, "A review of IoT-enabled smart energy hub systems: Rising, applications, challenges, and future prospects," *Renew. Energy Focus,* vol. 51, p. 100634, October 2024.

[23] P. Mishra and G. Singh, "Energy management systems in sustainable smart cities based on the Internet of energy: A technical review," *Energies,* vol. 16, p. 6903, September 2023.

[24] Y. Liu, C. Yang, L. Jiang, S. Xie and Y. Zhang, "Intelligent edge computing for IoT-based energy management in smart cities," *IEEE Netw.,* vol. 33, p. 111–117, March 2019.

[25] TEKTELIC, "TOP Innovative Smart Cities Examples Worldwide," October 2024. [Online]. Available: https://tektelic.com/expertise/top-smart-cities-examples/.

[26] A. Cosar, "Smart Mobility in Action: How IoT and 5G Shape Dutch Traffic," *Euro-Atlantic Resilience journal,* vol. 2, no. 3, pp. 34-58, 2023.

[27] A. A. El Hassan, A. El Mehdi and M. Saber, "NB-IoT and LTE-M towards massive MTC: Complete performance evaluation for 5G mMTC," *Indones. J. Electr. Eng. Comput. Sci.,* vol. 23, p. 308, July 2021.

[28] P. J. Basford, F. M. J. Bulot, M. Apetroaie-Cristea, S. J. Cox and S. J. J. Ossont, "LoRaWAN for smart city IoT deployments: A long term evaluation," *Sensors (Basel),* vol. 20, p. 648, January 2020.

[29] K. S. Adu-Manu, F. Engmann, G. Sarfo-Kantanka, G. E. Baiden and B. A. Dulemordzi, "WSN Protocols and Security Challenges for Environmental Monitoring Applications: A Survey," *Journal of Sensors,* vol. 2022, p. 1–21, August 2022.

[1 P. Tadejko, "Environmental monitoring systems using internet of things – standards and protocols,"
30 *EiS,* vol. 63, p. 15–15, October 2017.
]

[1 K. S. Adu-Manu, J.-D. Abdulai, F. Engmann, M. Akazue, J. K. Appati, G. E. Baiden and G. Sarfo-
31 Kantanka, "WSN Architectures for Environmental Monitoring Applications," *Journal of Sensors,*
] vol. 2022, p. 1–18, September 2022.

[1 M. Bacco, F. Delmastro, E. Ferro and A. Gotta, "Environmental Monitoring for Smart Citie," *IEEE*
32 *Sensors Journal.*
]

[1 e. a. M. Hasan, "Design and Development of a Low-Cost IoT-based Environmental Pollution
33 Monitoring System," *International Journal of Scientific & Engineering Research,* 2023.
]

[1 D. Rahul Naik, L. B. Das and B. T. S, "Wireless Sensor Networks with Zigbee and WiFi for
34 Environment Monitoring, Traffic Management and Vehicle Monitoring in Smart Cities," *Proc. 3rd*
] *IEEE Int. Conf. on Computing, Communication and Automation,* 2018.

[1 Commscope, "The Role of Public Wi-Fi in Enabling Smart Cities," [Online]. Available:
35 https://www.commscope.com/globalassets/digizuite/1065-1055-role-of-public-
] wifi.pdf?utm_source=ruckus&utm_medium=redirect.

[1 A. Rana, K. Kaur, P. Kaur and E. Bhatti, "Energy-efficient Protocols for Environmental Monitoring
36 in Wireless Sensor Networks: A Review," *Journal of Ambient Intelligence and Smart*
] *Environments,* 2024.

[1 R. B. Dilmaghani and R. R. Rao, "A systematic approach to improve communication for emergency
37 response," in *2009 42nd Hawaii International Conference on System Sciences*, 2009.
]

[1 G. Kokkonis, K. E. Psannis, M. Roumeliotis and D. Schonfeld, "Real-time wireless multisensory
38 smart surveillance with 3D-HEVC streams for internet-of-things (IoT)," *J. Supercomput.,* vol. 73,
] p. 1044–1062, March 2017.

[1 A. Jarwan, A. Sabbah, M. Ibnkahla and O. Issa, "LTE-based public safety networks: A survey,"
39 *IEEE Commun. Surv. Tutor.,* vol. 21, p. 1165–1187, January 2019.
]

[1 S. Moussa, "Architecture and protocols for public safety users in the 5G cellular networks.
40 (Architecture et protocoles pour les Réseaux d'urgence dans la 5G)," 2023.
]

[1 J. Suomalainen, J. Julku, M. Vehkapera and H. Posti, "Securing public safety communications on
41 commercial and tactical 5G networks: A survey and future research directions," *IEEE Open J.*
] *Commun. Soc.,* vol. 2, p. 1590–1615, July 2021.

[1 EENA, “5G Technology in Emergency Services,” 2019. [Online]. Available: https://eena.org/wp-42 content/uploads/5G_Emergency_Services_Version3.pdf.
]

[1 Y. S. Arjunrao and E. P. Alhat, “SMART CITIES AND IOT FOR ENVIRONMENTAL 43 MONITORING,” *Journal of Advanced Multidesciplinary Research Studies and Development,* vol.] 2, no. 6, pp. 38-43, 2023.

[1 M. Krichen, "Improving formal verification and testing techniques for internet of things and smart 44 cities," *Mob. Netw. Appl.,* vol. 28, p. 732–743, April 2023.
]

[1 O. B. Mora-Sanchez, E. Lopez-Neri, E. J. Cedillo-Elias, E. Aceves-Martinez and V. M. Larios, 45 "Validation of IoT infrastructure for the construction of smart cities solutions on living lab] platform," *IEEE Trans. Eng. Manage.,* vol. 68, p. 899–908, June 2021.

[1 A. Costa and L. Teixeira, “Testing strategies for smart cities applications: A systematic mapping 46 study,” in *Proceedings of the III Brazilian Symposium on Systematic and Automated Software] Testing*, New York, NY, USA, 2018.

[1 M. Mansour, A. Gamal, A. I. Ahmed, L. A. Said, A. Elbaz, N. Herencsar and A. Soltan, "Internet 47 of Things: A comprehensive overview on protocols, architectures, technologies, simulation tools,] and future directions," *Energies,* vol. 16, p. 3465, April 2023.

[1 C. Barnes, “Verification and validation of wireless sensor network protocol properties through the 48 system’s emulation,” *Networking and Internet Architecture [cs.NI]. COMUE Université Côte] d’Azur,* June 2017.

[1 N. J. Bertola, A. Costa and I. F. C. Smith, "Strategy to validate sensor-placement methodologies in 49 the context of sparse measurement in complex urban systems," *IEEE Sens. J.,* vol. 20, p. 5501–] 5509, May 2020.

[1 A. Nayyar and R. Singh, “A comprehensive review of simulation tools for wireless sensor networks 50 (WSNs),” *Journal of Wireless Networking and Communications,* vol. 5, p. 19–47, 2015.
]

[1 W. Wang, "Deployment and optimization of wireless network node deployment and optimization 51 in smart cities," *Comput. Commun.,* vol. 155, p. 117–124, April 2020.
]

[1 P. Neis, D. Warch and M. Hoppe, "Testing and evaluation of low-cost sensors for developing open 52 smart campus systems based on IoT," *Sensors (Basel),* vol. 23, p. 8652, October 2023.
]

[1 A. Ray, “Planning and analysis tool for large scale deployment of wireless sensor network,” 53 *International Journal of Next-Generation Networks (IJNGN),* vol. 1, p. 29–36, 2009.
]

[1 R. Marfievici, A. L. Murphy, G. P. Picco, F. Ossi and F. Cagnacci, "How environmental factors
54 impact outdoor wireless sensor networks: A case study," in *2013 IEEE 10th International*
] *Conference on Mobile Ad-Hoc and Sensor Systems*, 2013.

[1 P. Horazdovsky, S. Kozhevnikov and M. Svitek, "Dynamic Public Transport in Smart City using
55 Multi-agent system," in *2019 Smart City Symposium Prague (SCSP)*, 2019.
]

[1 Dwiannisa Rizka and S. S. Hidayat, "NB-IOT COMMUNICATION SYSTEM : A REVIEW".
56
]

[1 M. Lewis, "A Blueprint for Secure Smart Cities," [Online]. Available: https://www.fox-
57 it.com/media/zu4oukhk/ncc-group-whitepaper_a-blueprint-for-secure-smart-cities_april-
] 2020_finalpdf__bguwhmcagwk3xca1xmxb.pdf.

7. Annexes

7.1. Annex 1: Architectural Refinement Internal Questionaire

Architecture Refinement Questionnaire

Document type	Internal Questionaire
Work package number(s)	WP2
Author(s)	*Nikos Bakalos*

Enabling Positive Energy Districts through a Planning and Management Digital Twin

Project Acronym - EXPEDITE

Grant Agreement Number 101139527

Architecture Refinement Questionnaire

Purpose: This questionnaire aims to gather detailed information from the developers of each container to refine and co-design the architecture of the EXPEDITE project. The answers provided will help identify opportunities for further breakdown of components, clarify input/output data flows, and establish the use of specific technologies.

General Information

1. **Container Name**:
   - What is the name of the container you are responsible for?
2. **Team/Developer Name**:
   - Who is responsible for the development of this container?
3. **Technology Stack**:
   - What technology stack (programming languages, frameworks, databases) is used for this container?
   - Are there any third-party tools, services, or libraries integrated into this container?

Functional Breakdown

4. **Component Breakdown**:
   - Can your container be further broken down into smaller, independent components? If yes, please list them and describe their functionalities.

5. **Sub-Components Interaction**:
   - How do these sub-components interact internally? (e.g., APIs, message brokers, gRPC, REST, direct function calls)

Input/Output Data Flows

6. **Input Data**:
   - What types of input data does your container consume? (e.g., sensor data, user input, external data sources)
   - Where does the input data come from (internal or external systems)?
   - Is the input data structured (e.g., databases, JSON) or unstructured (e.g., raw text, images)? How is the data pre-processed or cleaned?

7. **Output Data**:

- What types of output data does your container produce? (e.g., processed data, reports, logs)
- Where is the output data sent (internal or external systems)?
- Is the output data structured or unstructured?

8. **Data Formats**:
   - What data formats are used for input/output? (e.g., JSON, XML, CSV, database formats)

Internal/External Interactions

9. **External Systems**:
   - Does your container interact with external systems or services? If yes, please specify these systems and describe the nature of the interaction.

10. **Internal Systems**:
    - Which internal containers or components does your container interact with? Describe the interaction and the types of data exchanged.

11. **API & Integration**:
    - Does your container expose any APIs for interaction with other containers or external systems? Please describe the APIs and their endpoints.

12. **Data Exchange Protocols**:
    - What communication protocols are used for data exchange with other containers? (e.g., HTTP, WebSockets, MQTT, message brokers)

Performance and Scalability

13. **Performance Considerations**:
    - Are there any performance bottlenecks or considerations for this container? (e.g., high-volume data processing, real-time constraints)

14. **Scalability**:
    - Can your container scale horizontally (i.e., multiple instances) or vertically (i.e., improved performance with better hardware)? How does the architecture support this?
    - What is the expected throughput of the container (e.g., requests per second,

data processed per second)? Has the container been stress-tested for scalability?

Security

15. **Authentication/Authorization**:
    - What mechanisms are used to authenticate and authorize users or systems that interact with this container? (e.g., OAuth, API keys)

16. **Data Privacy**:
    - Are there any sensitive data processing or storage concerns? How is sensitive data protected (e.g., encryption, anonymization)?

Future Development

17. **Future Features**:
    - Are there any planned future features or improvements for this container?

18. **Modularization**:
    - Do you foresee opportunities for further modularization or abstraction of the container's functionality?

7.2. Annex 2: Per Tool Specific Requirements

ID	Name	Description
FR-BMS-01	Building Data Collection	The component shall integrate with Building Management Systems (BMS) to achieve availability of BMS data for other components and also ability to pass certain adjustments from other components to BMS
FR-BMS-02	API Integration	The component shall enable data exchange between BMS and other tools within the digital twin platform, ensuring interoperability and consistent data flow.
NFR-BMS-01	Scalability	The component shall process data from multiple buildings simultaneously, ensuring scalability for district energy analysis.
NFR-BMS-02	Legacy System Integration	The component shall support integration with the present legacy BMS systems, ensuring backward compatibility and flexibility across different infrastructures.
FR-BSMM-01	Building Data Collection	The tool shall support the modeling of all district buildings by capturing attributes such as energy demand, energy consumption, and CO2 emissions for base and future scenarios, ensuring comprehensive coverage.
FR-BSM-02	Data Integration	The tool shall integrate historical data from cadastre and BMS systems to calibrate the baseline model and generate future scenarios.
FR-BSM-03	Retrofitting and Renovation Simulation	The tool shall simulate building retrofitting scenarios to evaluate energy-saving impacts and potential CO2 emission reductions, enabling informed decision-making.
FR-BSM-04	Environmental Data Integration	The tool shall incorporate environmental and climate data into energy demand calculations under historical or pre-simulated scenarios to ensure scenario relevance.
FR-BSM-05	Data Access via APIs	The tool shall provide GIS and Excel-based scenario results for integration with external systems, including the Digital Twin platform.
NFR-BSM-01	Performance and Scalability	The tool shall support city-wide simulations for all predefined buildings while ensuring static scenario definitions and avoiding real-time expansions.
NFR-BSM-02	Legacy System Integration	The tool shall ensure accurate data integration by validating inputs from cadastre and city systems, enhancing the reliability of simulations.

FR-DTD-01	Simulation Setup	The DT Design Time shall enable users to configure simulation parameters, through an intuitive graphical interface. Configurations should be saved for reuse.
FR-DTD-02	Scenario Library	The DT Design Time shall provide access to a library of pre-configured simulation templates for common use cases, such as renewable energy integration or traffic optimization, to expedite setup.
FR-DTD-03	Visualization of Inputs	The DT Design Time shall visualize initial conditions and simulation outputs, such as energy distribution maps or transport routes, ensuring users can verify and adjust parameters visually.
NFR-DTD-01	System Performance	The DT Design Time shall process input configurations and load pre-configured templates, ensuring efficiency in the setup process.
NFR-DTD-02	System Integration	The DT Design and DT Runtime components will be integrated to offer users a unified experience
FR-RES-01	Long-Term RES Modeling	The tool shall model renewable energy sources to identify optimal technology configurations for long-term energy planning, focusing on 2030 and 2050 scenarios.
FR-RES-02	RES Scenario Simulation	The tool shall simulate future scenarios with varying renewable energy adoption rates and deployment strategies to guide municipal decision-making.
FR-RES-03	Integration with District Systems	The tool shall integrate renewable energy models with district heating and energy systems to optimize overall energy performance.
FR-RES-04	Environmental Impact Analysis	The tool shall analyze and report environmental indicators for different RES scenarios, enabling stakeholders to assess sustainability impacts.
FR-RES-05	External Data Access	The tool shall provide pre-simulated scenario results in GIS and Excel formats for integration into external platforms and tools.
NFR-RES-01	Reliability	The tool shall accommodate additional RES scenarios defined during the project without affecting pre-simulated long-term data integrity.
NFR-RES-02	Interoperability	The tool shall facilitate the integration of GIS and Excel scenario results into urban and district energy management tools.
FR-CDS-01	Persistent Data Storage	The service shall provide persistent storage for project-related data, ensuring long-term availability and accessibility, and allowing for backup and recovery in case of system failures.
FR-CDS-02	Data Anonymization	The service shall implement data anonymization techniques to protect sensitive user information before storage or sharing, ensuring compliance with privacy regulations.

FR-CDS-03	Secure Data Access	The service shall support secure data access, including role-based permissions for administrators, analysts, and external stakeholders, to ensure that sensitive data is protected.
FR-CDS-04	System Event Logging	The service shall log system events, including data access, updates, and deletions, to enable comprehensive auditing and accountability.
FR-CDS-05	Data Standardization	The system shall harmonize incoming data from various sources into a standardized format, ensuring compatibility with the digital twin platform for seamless integration.
FR-CDS-06	Automated Data Mapping	The system shall support automated mapping of data fields from external sources to internal formats using configurable rules, ensuring efficient data transformation.
NFR-CDS-01	Response Time	The service shall provide efficient query response times under typical and peak load conditions.
NFR-CDS-02	Compatibility with Data Sources	The system shall ensure compatibility with both structured and unstructured data sources, supporting formats such as JSON, CSV, and XML for seamless integration.
FR-EIA-01	Economic Impact Analysis	The tool shall analyze the economic impacts of renewable energy projects, including cost savings, job creation, and investment opportunities, to support decision-making for sustainable urban development.
FR-EIA-02	ROI Calculation	The tool shall calculate the long-term return on investment (ROI) for district-level energy initiatives, accounting for operational and maintenance costs, to determine financial feasibility.
FR-EIA-03	Scenario Financial Assessment	The tool shall integrate with simulation outputs to assess the financial viability of urban planning scenarios, including energy storage and transportation systems.
FR-EIA-04	Policy Comparison	The tool shall provide comparative analyses of different policy options, highlighting their economic trade-offs and environmental benefits, to aid in sustainable urban policy development.
FR-EIA-05	Economic Reporting	The tool shall generate detailed economic reports, including visualizations of cost distribution, revenue streams, and key economic (e.g., NPV, IRR, ENPV, ERR) and financial metrics, for stakeholders to review and act upon.
NFR-EIA-01	Project Scale	The tool shall support analysis for projects with varying budgets, ensuring scalability for large-scale urban initiatives.
FR-EDSP-	Data Exposition	Provide users with an interface to publish a data asset

01		
FR-EDSP-02	Data Security	Enable users to define policies to rule access to their data asset
FR-EDSP-03	Data Discovery	Provide an interface to browse data assets offered by other users
FR-EDSP-04	Data Transfer	Ensure user can access the data asset they consume during the validity of their agreement with provider
FR-EDSP-05	Infrastructure	Document and provide resources for users to deploy and configure DSIS
NFR-EDSP-01	Encryption and Security	The platform shall employ end-to-end encryption for all data transactions to prevent unauthorized access or breaches, ensuring compliance with modern security standards
FR-DTPR-01	Pattern Storage	The DT Pattern Repository shall support storing reusable models as patterns, including relevant metadata for easy retrieval.
FR-DTPR-02	Search and Filter	The repository shall allow users to search and filter stored patterns by attributes such as application domain, location, and energy efficiency targets.
FR-DTPR-03	Version Control	The repository shall maintain version control for all patterns, allowing users to access historical versions and track changes for audit and compliance purposes.
NFR-DTPR-01	Query Performance	The repository shall provide search query results within acceptable time limits, even under peak usage conditions.
FR-DDFE-01	Data Aggregation	The engine shall aggregate data from multiple district-level sources, including IoT sensors, BMS, and energy systems, into a unified format for analysis and simulation.
FR-DDFE-02	Data Fusion Algorithms	The engine shall apply data fusion algorithms to combine overlapping data points, ensuring consistency and eliminating redundancies for accurate simulations.
FR-DDFE-03	Real-Time Processing	The engine shall support real-time data processing, providing up-to-date inputs for Digital Twin simulations and decision-making tools.

FR-DDFE-04	Data Validation	The engine shall include validation mechanisms to flag and resolve incomplete or inconsistent data entries automatically, ensuring high-quality input for simulations.
NFR-DDFE-01	High-Volume Data Handling	The engine shall handle multiple data streams simultaneously, ensuring scalability for large districts.
FR-MB-01	Asynchronous Communication	The message broker shall facilitate communication between all system components, enabling real-time notifications and data exchanges to ensure smooth interactions across services
FR-MB-02	Message Logging	The message broker shall support integration with external monitoring and logging systems to track message flow, consumer offsets, delivery attempts, and errors. This enables auditing and troubleshooting, ensuring transparency in messaging processes through observability tools and log aggregation frameworks
FR-MB-03	Secure Communication	The message broker shall support secure message encryption to protect sensitive data during transit between system components, ensuring data integrity and confidentiality
FR-MB-04	Message Distribution	The message broker shall provide topic-based or queue-based message distribution to efficiently deliver messages to the relevant components, optimizing system performance and reducing latency
NFR-MB-01	High-Volume Messaging	The message broker shall handle up to 10,000 messages per second, ensuring scalability for high-volume data exchanges, especially during peak usage times
NFR-MB-03	Low-Latency Delivery	The message broker shall support running in cluster mode, replicating messages across nodes
FR-DODS-01	Optimization Algorithms	The tool shall provide algorithms to suggest the best configurations for energy distribution, mobility patterns, and district heating based on predefined objectives such as cost reduction and CO2 minimization
FR-DODS-02	Scenario Comparison	The tool shall allow users to evaluate multiple optimization scenarios side-by-side, providing insights into trade-offs and selecting the most suitable solution for urban challenges
FR-DODS-03	Real-Time Data Integration	The tool shall integrate data from energy systems and transportation networks to refine optimization outputs, ensuring relevance and accuracy
FR-DODS-04	Optimization Reports	The tool shall generate detailed optimization reports, including graphs and tables, summarizing the environmental and economic impacts of each scenario for stakeholder review
FR-	Predictive	The tool shall incorporate predictive analytics to forecast long-term

DODS-05	Analytics	effects of optimization decisions on urban sustainability metrics, such as energy efficiency and mobility
NFR-DODS-01	Processing Capacity	The tool shall process optimization scenarios involving up to multiple variables within acceptable time limits, ensuring timely results for complex problems
FR-AUTHS-01	Single Sign-On (SSO)	The authentication system shall utilize Keycloak to provide Single Sign-On (SSO) functionality, enabling users to securely access the digital twin platform and its associated tools with a single login. Keycloak will manage user sessions across multiple applications without requiring reauthentication
FR-AUTHS-02	OAuth2 Authentication	Keycloak shall issue OAuth2-compliant access tokens to users and system components to ensure secure, standards-based communication and to prevent unauthorized access within the digital twin platform
FR-AUTHS-03	Role-Based Access Control (RBAC)	Administrators shall use Keycloak's built-in RBAC mechanisms to define and manage user roles and permissions. This allows fine-grained access control across different user groups, ensuring access to features and tools is appropriately restricted
NFR-AUTHS-01	Scalability	The Keycloak server deployment shall be configured in high-availability mode, supporting horizontal scaling (e.g., via Kubernetes or container orchestration) to handle up to 1,000 authentication requests per second during peak usage times
NFR-AUTHS-02	Data Security	Keycloak shall be configured to encrypt all sensitive authentication data, including access tokens and personal user information, both in transit (via HTTPS/TLS) and at rest. The deployment shall comply with relevant security standards and organizational policies
FR-AI-01	Data Analytics	The system shall analyze data from simulations and generate insights using AI-driven models, including trend predictions and anomaly detection for energy usage and mobility patterns.
FR-AI-02	Customizable Visualizations	The system shall provide customizable visualizations, allowing users to filter data by parameters such as timeframes, geographic locations, and energy usage types.
FR-AI-03	Predictive Analytics	The system shall leverage the project's simulation tools to visualize energy demand forecasts, transportation trends, and other data under various scenarios, supporting proactive decision-making.
FR-AI-04	Automated Reporting	The system shall generate automated reports summarizing key insights, including graphs, tables, and actionable recommendations, for stakeholders.
NFR-	Device	The system shall support visualization outputs on all project

AI-02	Compatibility	interfaces.
FR-DTR-01	Simulation Monitoring	The DT Runtime shall allow users to monitor simulations for urban scenarios, focusing on energy forecasts and consumption. Users will observe live data streams and simulation results without making parameter adjustments
FR-DTR-02	Real-Time Visualization	The DT Runtime shall provide real-time visualization of sensor data and decision support system outcomes, including heatmaps, graphs, and dashboards. This will enable stakeholders to evaluate urban energy and mobility system performance in real-time
FR-DTR-03	Scenario Reporting	The DT Runtime shall generate scenario-specific reports based on live data and decision support outcomes, summarizing key metrics for city planners
NFR-DTR-01	Scalability	The DT Runtime shall be able to scale up to accommodate even cities with very large populations
NFR-DTR-02	Response Time	The DT Runtime shall be able to render data/information within a time interval of <1min for optimal user experience
NFR-DT3-03	System Integration	The DT Design and DT Runtime components will be integrated to offer users a unified experience
FR-DHES-01	Heating Network Simulation	The tool shall simulate district heating systems, including energy generation, transmission, and consumption, for residential and commercial buildings. This will help optimize heat distribution and energy use.
FR-DHES-02	Energy Storage Evaluation	The tool shall evaluate energy storage requirements, incorporating technologies such as thermal storage. This will ensure reliable energy distribution.
FR-DHES-03	Model Results	The tool shall provide simulations of district heating system performance, including efficiency metrics and heat losses, to ensure smooth operation and identify areas for improvement.
FR-DHES-04	Renewable Fuel Integration	The tool shall support scenario analysis for renewable fuel integration to replace fossil fuels and reduce carbon emissions in district heating systems.
NFR-DHES-01	Simulation Capacity	The tool shall process district heating network simulations for networks spanning up to 1,000 kilometers of pipelines, enabling efficient scenario testing.
FR-EFGF-01	Energy Demand Forecasting	The tool shall predict hourly and daily energy demand for residential, commercial, and industrial district assets.

FR-EFGF-02	District asset flexibility	The tool shall provide district asset flexibility indicators, including renewable energy integration and demand-side management schedules
FR-EFGF-03	Energy Balance Visualization	The tool shall support interactive visualizations of energy supply and demand balances, enabling stakeholders to monitor and optimize operations.
NFR-EFGF-01	Forecast Accuracy	The tool shall maintain acceptable forecasting accuracy for short-term predictions.
FR-MT-01	Traffic Flow Simulation	The tool shall simulate urban traffic flows to optimize mobility, decrease emissions and energy consumption and reduce congestion.
FR-MT-02	Data Integration	The tool data will integrate data from IoT sensors, and public transport systems via the CDs
FR-MT-03	Transport Demand Forecasting	The tool shall forecast transport demand under different scenarios, such as increased electric vehicle usage or expanded public transport coverage, to aid in sustainable city planning.
FR-MT-04	Network Performance Visualization	The tool shall allow the visualisation of transport network performance using heatmaps and flow diagrams¬†to identify spatial patterns in energy consumption and emissions
FR-MT-05	Recommendations for Transport Improvements	The tool shall generate actionable recommendations, such as recommended positions for EV charging points, based on simulation results and stakeholder input.
NFR-MT-01	Scalability	A set of recommendations will outline how to scale the tool to accommodate simulation data for city populations of up to 5 million residents without performance degradation.
FR-CC-01	Data Exchange Management	The component shall handle secure data exchange between participants that have a valid connector and are validated through the same DAPS (Dynamic Attributes Providing System)
FR-CC-02	Transaction Logging	The component shall log all data exchange transactions, including timestamps, data size, and transaction status, to provide an audit trail for monitoring and troubleshooting
FR-CC-03	API Integration	The component shall support API-based integration with third-party energy management tools to extend the platform's interoperability and data exchange capabilities
NFR-CC-01	Security Standards	The component shall comply with security standards such as ISO 27001, implementing end-to-end encryption for all data exchanges to safeguard sensitive information

FR-MA-01	User Authentication	The app shall provide secure login functionality using Single Sign-On (SSO), integrating with the Auth Token Server to ensure only authorized users can access personalized energy data and platform features securely. This includes support for multi-factor authentication and session management to prevent unauthorized access.
FR-MA-02	Energy Usage Monitoring	The app shall display real-time energy data, including customized visualizations, enabling users to track energy impact effectively.
FR-MA-03	Notifications and Alerts	The app shall send timely and customized notifications to users, including alerts and personalized messages.
FR-MA-04	Community Management	The app shall support multiple user scopes and groups, enabling the creation of user communities.
FR-MA-05	User Missions	The app shall allow the execution of single and group-based missions and quizes to set goals and increase user engagement.
FR-MA-06	Ideas Exchange	The app shall include a forum-like environment for open idea-sharing activities on topics related to the PEDs.
NFR-MA-01	Response Time	The app shall ensure all user interactions, including data loading and feature navigation, are processed within an acceptable timeframe to allow seamless user experience.
NFR-MA-02	Platform Support	The app shall maintain compatibility with the latest versions of Android and iOS devices, offering identical features and performance across both platforms. The app will be optimized for different screen sizes and operating system versions.
NFR-MA-03	Data Security	The app shall implement robust data security measures, secure authentication mechanisms, and compliance with GDPR.
HLR-1	Integration and Interoperability	Enable seamless integration of heterogeneous data sources; use standardized APIs for interoperability and context management; adhere to modular and interoperable architectural principles to support replicability and scalability. MIMs: MIM 1 (Context Information Management), MIM 2 (Data Models), KPIs: KPI2.1, KPI2.2, KPI3.1, KPI3.2
HLR-2	Data Harmonization and Standardization	Ensure data from all sources follows a common format and schema; harmonize and validate data for consistency and usability. MIMs: MIM 2 (Data Models), KPIs: KPI2.1, KPI3.1
HLR-3	Real-Time and Historical Data Support	Provide real-time data updates within acceptable intervals; support access to historical data for simulations and analyses. MIMs: MIM 1 (Context Information Management), KPIs: KPI2.1, KPI2.2

HLR-4	Ethical AI Design	Mitigate algorithmic biases provide transparency and explainability for AI-driven decisions; establish mechanisms for human oversight and intervention in AI operations; ensure compliance with the AI Act and GDPR. MIMs: MIM 3 (Smart Contracts), KPIs: KPI4.1, KPI4.2
HLR-5	Privacy and Security	Implement robust privacy and security measures, including data encryption, access control, and anonymization; comply with GDPR by conducting Privacy Impact Assessments (PIAs). MIMs: MIM 1 (Context Information Management), MIM 3 (Smart Contracts), KPIs: KPI5.1, KPI5.2
HLR-6	Decision Support Systems	Enable evidence-based decision-making with tools for district-level optimization; provide accurate energy forecasting and scenario modelling. MIMs: MIM 2 (Data Models), MIM 3 (Smart Contracts), KPIs: KPI4.1, KPI4.2, KPI5.3
HLR-7	Stakeholder Collaboration and Engagement	Facilitate collaboration with shared data access and visualization tools; engage citizens and planners through intuitive interfaces and visualizations. MIMs: MIM 3 (Smart Contracts), KPIs: KPI2.2, KPI5.2
HLR-8	Accessibility	Ensure the design of tools and interfaces prioritizes usability and autonomy for city planners. Emphasize intuitive navigation, seamless integration with existing workflows, and avoidance of overly complex or manipulative designs. MIMs: MIM 1 (Context Information Management), KPIs: KPI5.1
HLR-9	Environmental Sustainability	Support the development of an ICT-based platform for a Digital Twin to optimize urban energy efficiency and resource utilization. MIMs: MIM 3 (Smart Contracts), KPIs: KPI2.1, KPI4.1, KPI5.2
HLR-10	Data Governance and Compliance	Establish frameworks for data quality, lineage, and risk management; maintain detailed documentation, audit trails, and compliance records; implement feedback mechanisms for user insights and continuous improvement. MIMs: MIM 1 (Context Information Management), MIM 2 (Data Models), KPIs: KPI5.3
HLR-11	Visualization and Analytics	Enable real-time visualization of Digital Twin (DT) performance data; support AI-driven analytics for actionable insights. MIMs: MIM 1 (Context Information Management), MIM 2 (Data Models), KPIs: KPI5.1, KPI5.3
HLR-12	Robustness and Risk Management	Ensure solutions are resilient to failures and cyber attacks; implement risk management systems for identifying risks. MIMs: MIM 3 (Smart Contracts), KPIs: KPI5.2
HLR-13	User Data Rights Management	Provide tools for users to manage their personal data, including access, rectification, and deletion; ensure user notifications for data updates and deletions. MIMs: MIM 1 (Context Information Management), KPIs: KPI5.1

HLR-14	Simulation and Modeling Capabilities	Support mobility and transport modeling; enable modeling of district heating, energy storage, and renewable energy systems. MIMs: MIM 2 (Data Models), KPIs: KPI2.1, KPI3.1, KPI3.2
HLR-15	Cybersecurity Protocols	Establish robust cybersecurity measures to ensure data integrity and safeguard against attacks. MIMs: MIM 3 (Smart Contracts), KPIs: KPI5.1
TO-01	Increase Renewable Energy Production	Reduce Riga's total CO2 Emissions. Target: -0.3, Baseline: 1742 ktCO2
TO-02	Enhance Energy Efficiency	Reduce CO2 emissions in energy production. Target: -0.3, Baseline: 914 ktCO2
TO-03	Enhance Grid Stability	Reduce CO2 emissions in transportation. Target: -0.3, Baseline: 729 ktCO2
TO-04	Optimize District Heating	Increase the annual amount of renewable energy generation (heat + electricity) by 1080.23 GWh. Target: 3237.27 GWh, Baseline: 2157 GWh
TO-05	Improve Mobility Planning	Replace natural gas boilers with renewable energy sources. Target: -, Baseline: -
TO-06	Foster Citizen Engagement	Increase the share of renewables in the central heating system of Riga. Target: ,6%, Baseline: 0.31
TO-07	Advance Urban Sustainability	Reduce relative heat energy loss in heating lines. Target: 0.116, Baseline: 0.117
TO-08	Achieve Scalability and Replicability	Increase the annual heating energy from renewable energy sources by 511.85 GWh. Target: 1662.23 GWh, Baseline: 1150.38 GWh
TO-09	Foster Stakeholder Collaboration	Reduce the share of decentralized heating supply. Target: 0.4, Baseline: 0.44
TO-10	Ensure Data Privacy and Security	Promote the creation of energy communities. Target: -, Baseline: -
TO-11	Provide Decision-Making Support	Promote electricity generation through PV and wind facilities, to increase the annual amount of renewables in the electricity supply by 529.5 GWh. Target: 621.48 GWh, Baseline: 91.97 GWh
TO-12	Promote Environmental Sustainability	Reduce annual energy consumption by 410.8 GWh through building renovations. Target: 1712 GWh, Baseline: 2123 GWh

TO-13	Enable Real-Time Visualization	Renovate the stock of multi-apartment buildings in Riga. Target: 2000 buildings, Baseline: 159 buildings
TO-14	Deploy Resilient Systems	Increase consumption data availability to encourage citizen-led renovations. Target: -, Baseline: -
TO-15	Transportation	Further development of public transportation. Target: -, Baseline: -
TO-16	Transportation	Increase the share of renewables in the public transport sector. Target: 0.5, Baseline: 0.16
TO-17	Transportation	Reduce the share of private car users. Target: 0.374, Baseline: 0.424
TO-18	Transportation	Development of cycling/walking infrastructure to promote active transportation modes. Target: -, Baseline: -
TO-19	Transportation	Implementation of low emission zones. Target: -, Baseline: -
TO-20	Transportation	Development of EV infrastructure to increase transport sector electrification. Target: -, Baseline: -
TO-21	Stakeholder Collaboration	Increase the number of stakeholder collaborations, facilitating better decision-making and project outcomes across energy and urban planning sectors. Target: -, Baseline: -